
FRONT APRON TO COWL SIDE UPPER MEMBER (ASSY)


F16751A

REPLACEMENT
With the radiator side support removed.

REMOVAL




F16751

POINT
1 Remove the [A], [B] and [C] at the same time.

PART NAME
[A] Front Apron To Cowl Side Lower Member [B] Cowl Top Side Reinforcement
[C] Cowl Top To Cowl Inner No.2 Brace (LH), Cowl Top To Cowl Inner No.1 Brace (RH)

INSTALLATION

- Temporarily install the new parts and measure each part of the new parts in accordance with the body dimension diagram. (See the body dimension diagram)
- Inspect the fitting of the related parts around the new parts before welding. This affects the appearance of the finish.
- After welding, apply the polyurethane foam to the corresponding parts.
- After welding, apply body sealer and under-coating to the corresponding parts.
- After applying the top coat layer, apply anti-rust agent to the inside of the necked section structural weld spots.



POINT

1 Inspect the fitting of the front fender and hood, etc., before welding, since this affects the appearance of the finish.

PART NAME

[A] Front Apron To Cowl Side Lower Member [B] Cowl Top Side Reinforcement
[C] Cowl Top To Cowl Inner No.2 Brace (LH), Cowl Top To Cowl Inner No.1 Brace (RH)