031IY–02

TORQUE SPECIFICATION

Part Tightened	N·m	kgf·cm	ft·lbf
Intermediate shaft x Center support bearing assy No. 1 (Front)			
1st	182	1,850	134
Loosen nut			
2nd	69	700	51
Intermediate shaft x Center support bearing assy No. 1 (Rear)			
1st	182	1,850	134
Loosen nut			
2nd	69	700	51
Propeller shaft assy x Front flange	74	750	54
Propeller shaft assy rear x Rear differential	74	750	54
Intermediate shaft rear flange x Propeller shaft assy rear	29	296	21
Center support bearing assy No. 1 (front) x Body	37	375	27
Center support bearing assy No. 1 (rear) x Body	37	375	27
Front wheel set nut	103	1,050	76
Lower ball joint x Lower suspension arm	127	1,300	94
Tie rod end x Steering knuckle	49	500	36
Axle hub x Front drive shaft	294	3,000	217
Front disc brake caliper assy x Steering knuckle	107	1,090	79
Front speed senser set bolt	8.0	82	71 in. lbf
Flexible hose and speed sensor wire harness x Shock absorber	19	192	14
Rear wheel set nut	103	1,050	76
Speed sensor x Rear axle carrier	8.0	82	71
Axle hub x Rear drive shaft	294	3,000	217
Rear axle carrier sub–assy x Rear disc brake caliper	78	800	58
Front stabilizer Link assy x Shock absorber	74	755	55
Shock absorber x Steering knuckle	230	2,345	170
Front axle carrier x Lower ball joint	123	1,250	90
Rear axle carrier sub–assy x Rear axle hub & bearing	75	765	55
Rear shock absorber x Flexible hose	19	192	14
Rear axle carrier sub–assy x Strut rod assy rear	80	816	59
Rear axle carrier sub–assy x Rear suspension arm assy No.1 LH	112	1,140	83
Rear axle carrier sub–assy x Rear suspension arm assy No.2 LH	112	1,140	83
Disc brake dust cover front x Steering knuckle	8.3	85	74 in. lbf
Rear shock absorber x Rear axle carrier	180	1,840	133