BRAKE

030MU–05

SERVICE DATA

Brake pedal height (from asphalt sheet)	160 to 170 mm (6.229 to 6.693 in.)
Brake pedal free play	Pedal free play: 2.0 to 3.0 mm (0.079 to 0.118 in.)
Stop light switch clearance	0.5 to 2.6 mm (0.020 to 0.102 in.)
Pedal reserve distance from asphalt sheet at 490 N (50 kgf, 110.2 lbf)	More than 92 mm (3.6 in.)
Brake booster push rod to piston clearance (w/ SST)	Clearance: 0 mm (0 in.)
Front brake pad thickness	Standard thickness: 12.7 mm (0.500 in.) Minimum thickness: 1.0 mm (0.039 in.)
Front brake disc thickness	Standard thickness: 28.0 mm (1.102 in.) Minimum thickness: 26.0 mm (1.024 in.)
Front brake disc runout	Maximum disc runout: 0.05 mm (0.0020 in.)
Rear brake pad thickness	Standard thickness: 10.0 mm (0.394 in.) Minimum thickness: 1.0 mm (0.039 in.)
Rear disc brake thickness	Standard thickness: 10.0 mm (0.394 in.) Minimum thickness: 8.5 mm (0.335 in.)
Rear brake disc runout	Maximum disc runout: 0.15 mm (0.0059 in.)