030MV–06

TORQUE SPECIFICATION

Part Tightened		N·m	kgf·cm	ft·lbf
Brake line union nut		15	155	11
Bleeder plug		8.3	85	73 in.·lbf
Brake booster clevis lock nut		26	265	19
Stop lamp switch lock nut		17	173	13
Brake pedal sub–assy x Brake pedal support sub–assy		37	375	27
Brake pedal support assy x Reinforcement		20	204	15
Brake master cylinder x Brake booster		13	130	9
Front suspension brace x Body		80	816	59
Brake booster x Body		13	130	9
Wheel nut		103	1,050	76
Front brake cylinder mounting x Steering knuckle		107	1,090	79
Front brake cylinder x Front brake cylinder mounting		34	350	25
Front brake cylinder x Flexible hose		29	300	21
Rear brake cylinder mounting x Rear axle		78	800	58
Rear brake cylinder x Rear brake cylinder mounting		43	440	32
Rear brake cylinder x Flexible hose		29	300	21
Brake actuator assy x Actuator bracket		5.4	55	48 in.·lbf
Brake actuator bracket x Body		19	194	14
Front speed sensor x Steering knuckle		8.0	82	71 in.·lbf
Front speed sensor wire harness clamp x Shock absorber and body	Bolt A	5.0 N·m	51	44 in.·lbf
	Bolt B	19 N·m	192	14
Rear speed sensor x Rear axle		8.0	82	71 in.·lbf
Rear speed sensor wire harness clamp x Shock absorber and body		5.0	51	44 in.·lbf
Deceleration sensor x Body		14	143	10
Yawrate sensor protector x Deceleration sensor		14	143	10
Yawrate sensor x Body		14	143	10
Yawrate sensor protector x Yawrate sensor		14	143	10
Skid control ECU assy x Body		5.0	51	44 in.·lbf