■ PERFORMANCE AND SPECIFICATION

1. Performance

Front A/C (Without Rear A/C)			
Heater	Heater Output	W	5750
	Air Flow Volume	m^3/h	350
	Power Consumption	W	210
Cooler	Cooling Capacity	W	6100
	Air Flow Volume	m^3/h	530
	Power Consumption	W	260
Front A/C (With Rear A/C)			
Heater	Heater Output	W	5630
	Air Flow Volume	m^3/h	340
	Power Consumption	W	210
Cooler	Cooling Capacity	W	6100
	Air Flow Volume	m^3/h	510
	Power Consumption	W	260
Rear A/C (Manual & Automatic)			
Heater	Heater Output	W	2170
	Air Flow Volume	m^3/h	120
	Power Consumption	W	50
Cooler	Cooling Capacity	W	3600
	Air Flow Volume	m^3/h	360
	Power Consumption	W	200

2. Specifications

Ventilation and Heater Core				
Front A/C (Manual & Automatic)				
	Heater Core	Type		SFA (Straight Flow Aluminum) -II
		Size W × H × L	mm (in.)	201.6 × 150 × 27 (7.9 × 5.9 × 1.1)
		Fin Pitch	mm (in.)	1.5 (0.06)
	Blower	Motor Type		K70-11T
		Fan Type		Semi Sirocco
		Fan Size (Dia. × H)	mm (in.)	165 × 70 (6.5 × 2.8)
Rear A/C (Manual & Automatic)				
	Heater Core	Type		SFA (Straight Flow Aluminum) -II
		Size W × H × L	mm (in.)	130 × 191.1 × 21 (5.1 × 7.5 × 0.8)
		Fin Pitch	mm (in.)	1.8 (0.07)
	Blower	Motor Type		K62-11.5T
		Fan Size (Dia. × H)	mm (in.)	140 × 70 (5.5 × 2.8)

Air Conditioning				
Front & Rear A/C Common Parts				
Condenser	Type			MF (Multi-Flow)-IV
	Size W × H × L	mm (in.)		440.6 × 720 × 16 (17.3 × 28.3 × 0.6)
	Fin Pitch	mm (in.)		3.15 (0.12)
Compressor with Motor Assembly	Type			ES27
	Oil Type			ND11
	Oil Volume		Without Rear A/C	120 to 135 cc
			With Rear A/C	225 to 240 cc
Refrigerant	Type			HFC 134a
	Charge Volume		Without Rear A/C	550 to 650 g
			With Rear A/C	720 to 820 g
Front A/C (Manual & Automatic)				
Evaporator	Type			RS (Revolutionary super-slim Structure)
	Size W × H × L	mm (in.)		266.3 × 251 × 38 (10.5 × 9.9 × 1.5)
	Fin Pitch	mm (in.)		2.6 (0.10)
Rear A/C (Manual & Automatic)				
Evaporator	Type			RS (Revolutionary super-slim Structure)
	Size W × H × L	mm (in.)		145.7 × 251 × 50 (5.7 × 9.9 × 2.0)
	Fin Pitch	mm (in.)		3.4 (0.13)