# SERVICE SPECIFICATIONS

## SERVICE DATA

EG07L-1L

| | | | |
|---|---|---|---|
| Thermostat | Valve opening temperature | | 80 — 84°C (176 — 183°F) |
| | Valve lift | at 95°C (203°F) | 8 mm (0.31 in.) or more |
| Radiator cap | Relief valve opening pressure | STD | 74 — 103 kPa (0.75 — 1.05 kgf/cm², 10.7 — 14.9 psi) |
| | | Minimum | 59 kPa (0.6 kgf/cm², 8.5 psi) |

EG

## TORQUE SPECIFICATIONS

EG07M-1Q

| Part tightened | N·m | kgf·cm | ft·lbf |
|---|---|---|---|
| Engine coolant drain plug x Drain plug union | 13 | 130 | 6 |
| Water pump x Timing chain cover | 9 | 90 | 80 in.·lbf |
| Water pump x Cylinder block | 20 | 200 | 15 |
| Fan x Fluid coupling | 5.5 | 55 | 49 in.·lbf |
| Fluid coupling x Water pump | 20.5 | 210 | 15 |
| Alternator drive belt adjusting bar x Alternator | 19 | 195 | 14 |
| Alternator bracket x Alternator | 59 | 600 | 44 |
| Water inlet x Timing chain cover | 20 | 200 | 15 |