PRECAUTION

IF VEHICLE IS EQUIPPED WITH MOBILE COMMUNICATION SYSTEM

IN02R-02

For vehicles with mobile communication systems such as two–way radios and cellular telephones, observe the following precautions.

(1) Install the antenna as far as possible away from the ECU and sensors of the vehicle's electronic system.
(2) Install the antenna feeder at least 20 cm (7.87 in.) away from the ECU and sensors of the vehicle's electronics systems. For details about ECU and sensors locations, refer to the section on the applicable component.
(3) Do not wind the antenna feeder together with the other wiring. As much as possible, also avoid running the antenna feeder parallel with other wire harnesses.
(4) Confirm that the antenna and feeder are correctly adjusted.
(5) Do not install powerful mobile communications system.

FOR USING OBD II SCAN TOOL OR HAND–HELD TESTER

IN08Q-01

CAUTION: Observe these for safety reasons:

- Before using the OBD II scan tool or hand–held tester, the OBD II scan tool,s instruction book or hand–held tester,s operator manual should be read thoroughly.
- Be sure to rote all cableas securely when driving with the OBD II scan tool or hand–held tester connected to the vihicle. (I.e. Keep cables away from feet, pedals, steering wheel and shift lever.)
- Two persons are required when test driving with the OBD II scan tool or hand–held tester, one person to drive the vehicle and one person to operate the OBD II scan tool or hand–held tester.