BRAKE

SERVICE DATA

SS0BH–06

Front brake pad thickness		
(2WD)	STD	
	Europe	9.6 mm (0.378 in.)
	Others	9.5 mm (0.374 in.)
	Minimum	1.0 mm (0.039 in.)
(4WD and Prerunner)	STD	9.5 mm (0.374 in.)
	Minimum	1.0 mm (0.039 in.)
Front brake disc thickness		
(2WD)	STD	25.0 mm (0.984 in.)
	Minimum	23.0 mm (0.906 in.)
(4WD and Prerunner)	STD	20.0 mm (0.787 in.)
	Minimum	18.0 mm (0.709 in.)
Front brake disc runout		
(2WD)	Maximum	0.07 mm (0.0028 in.)
(4WD and Prerunner)	Maximum	0.07 mm (0.0028 in.)
Rear brake drum inside diameter		
(2WD)	STD	270.0 mm (10.630 in.)
	Maximum	272.0 mm (10.709 in.)
(4WD and Prerunner)	STD	295.0 mm (11.614 in.)
	Maximum	297.0 mm (11.693 in.)
Rear brake shoe lining thickness		
(2WD)	STD	5.5 mm (0.217 in.)
	Maximum	1.0 mm (0.039 in.)
(4WD and Prerunner)	STD	6.0 mm (0.236 in.)
	Maximum	1.0 mm (0.039 in.)
Rear brake drum to shoe clearance		0.6 mm (0.024 in.)