STEERING

SERVICE DATA

SS1HC–04

POWER STEERING FLUID (2KD–FTV)		
Oil level rise	Maximum	5 mm (0.20 in.)
Oil pressure at idle speed with valve closed	Minimum	8,336 kPa (85 kgf/cm^2, 1,209 psi)
PS VANE PUMP (2KD–FTV)		
Pump rotating torque	Maximum	0.3 N·m (2.8 kgf·cm, 2.4 in.·lbf)
Pump shaft and front housing bushing oil clearance	STD	0.035 – 0.042 mm (0.0014 – 0.0017 in.)
	Maximum	0.047 mm (0.0019 in.)
Vane plate height	Minimum	8.6 mm (0.339 in.)
Vane plate thickness	Minimum	1.397 mm (0.0550 in.)
Vane plate length	Minimum	14.991 mm (0.5902 in.)
Vane plate and pump rotor groove clearance	Maximum	0.033 mm (0.0013 in.)
Vane plate length	Pump rotor and cam ring mark	
	None	14.999 – 15.001 mm (0.59001 – 0.59059 in.)
	1	14.997 – 14.999 mm (0.59043 – 0.59051 in.)
	2	14.995 – 14.997 mm (0.59035 – 0.59043 in.)
	3	14.993 – 14.995 mm (0.59027 – 0.59035 in.)
	4	14.991 – 14.993 mm (0.59020 – 0.59027 in.)
Flow control valve spring length	Minimum	36.9 mm (1.453 in.)