

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
Master cylinder x Piston stopper bolt	10	100	7
Master cylinder x Reservoir	1.7	18	16 in.·lbf
Master cylinder x Brake booster	13	130	9
Brake line union nut	15	155	11
Push rod lock nut	25	260	19
Brake booster x Pedal bracket	15	155	11
Hydraulic brake booster clevis lock nut	25	260	19
Hydraulic brake booster x Pedal bracket	13	130	9
Accumulator x Booster pump motor	54	550	36
Reservoir set screw	1.7	17.5	15.2 in.·lbf
Front disc brake caliper x Flexible hose	30	310	22
Front disc brake mounting bolt x Steering knuckle	123	1,250	90
Bleeder plug	11	110	8
Parking brake bellcrank bracket x Backing plate	13	130	9
Rear drum brake wheel cylinder x Backing plate	10	100	7
Rear disc brake caliper installation bolt	26	270	20
Rear disc brake caliper x Flexible hose	30	310	22
Rear disc brake torque plate x Rear backing plate	103	1,050	76
Front speed sensor installation bolt	8.0	82	71 in.·lbf
Front speed sensor harness clamp bolt	13	130	9
Rear speed sensor installation bolt	8.0	82	71 in.·lbf
Rear speed sensor harness clamp bolt	13	130	9
LSP & BV x LSP & BV bracket	13	130	9
LSP & BV bracket x Frame	29	300	22
LSP & BV x Load sensing spring assembly	18	185	13
Load sensing spring assembly x Shackle No.1	18	185	13
Shackle No.1 x Shackle No.2	13	130	9
Shackle No.2 x Axle housing	29	300	22
Shackle No.2 x Bracket	13	130	9
Vacuum pump x Vacuum hose union bolt	14	140	10
Vacuum pump x Oil inlet union bolt	14	140	10
Vacuum pump x Check valve	74	750	54