

LUBRICANT

FRONT DRIVE SHAFT (IFS)		
Item	Capacity	Classification
Outboard joint grease	368 – 378 g (13 – 13.3 oz.)	
Inboard joint grease	293 – 303 g (10.3 – 10.7 oz.)	
FRONT DIFFERENTIAL (RFS)		
Item	Capacity	Classification
Hypoid gear oil (w/o Diff. lock)	2.80 liters (2.9 US qts, 2.5 Imp.qts)	Hypoid gear oil API GL-5
(w/ Diff. lock)	2.65 liters (2.8 US qts, 2.3 Imp.qts)	Above –18 °C (0°F) SAE 90
		Below –18 °C (0°F) SAE 80W-90 or 80W
FRONT DIFFERENTIAL (IFS)		
Item	Capacity	Classification
Hypoid gear oil	1.70 liters (1.80 US qts, 1.50 Imp.qts)	Hypoid gear oil API GL-5
		Above –18 °C (0°F) SAE 90
		Below –18 °C (0°F) SAE 80W-90 or 80W
REAR DIFFERENTIAL		
Item	Capacity	Classification
Hypoid gear oil Normal	3.30 liters (3.49 US qts, 2.90 Imp.qts)	Hypoid gear oil API GL-5
w/ Diff. lock	3.20 liters (3.38 US qts, 2.82 Imp.qts)	Above –18 °C (0°F) SAE 90
		Below –18 °C (0°F) SAE 80W-90 or 80W
Hypoid gear oil LSD	3.30 liters (3.49 US qts, 2.90 Imp.qts)	Hypoid gear oil LSD API GL-5
w/ LSD		Above –18 °C (0°F) SAE 90
		Below –18 °C (0°F) SAE 80W-90 or 80W