


CIRCUIT DESCRIPTION

WIRING DIAGRAM



INSPECTION PROCEDURE

HINT:

Troubleshoot each trouble symptom in accordance with the chart below .

MIL remains on	Start inspection from step 1
MIL does not light up	Start inspection from step 3

1	Clear DTC.
----------	-------------------

- (a) Connect the hand-held tester or the OBD II scan tool to the DLC3.
- (b) Turn the ignition switch ON and push the hand-held tester or the OBD II scan tool main switch ON.
- (c) Read the DTC (See page [DI-3](#)).
- (d) Clear the DTC (See page [DI-3](#)).
- (e) Check that MIL does not light up.


Standard: MIL does not light up

OK

Repair circuit indicated by output code
(See page [DI-36](#)).

NG

2	Check harness and connector (Check for short in wire harness).
----------	---



- (a) Disconnect the E9 ECM connector.
- (b) Turn the ignition switch ON.
- (c) Check that MIL does not light up.

Standard: MIL does not light up

OK

Replace ECM (See page [SF-60](#)).

NG

Check and repair harness and connector between combination meter and ECM (See page [IN-36](#)).

3 Check that MIL lights up.

Check that MIL lights up when turning the ignition switch ON.

Standard: MIL lights up

OK

System OK.

NG

4 Inspect combination meter assy (MIL circuit).

See the combination meter troubleshooting on page [BE-63](#).

NG

Repair or replace bulb or combination meter assembly.

OK

Check and repair harness and connector between combination meter and ECM (See page [IN-36](#)).