

DTC	P0101	Mass or Volume Air Flow Circuit Range/Performance Problem
------------	--------------	--

CIRCUIT DESCRIPTION

Refer to DTC P0100, P0102 and P0103 on page [DI-61](#).

DTC No.	DTC Detecting Condition	Trouble Area
P0101	After engine is warmed up, conditions (a), (b), (c) and (d) continue for more than 10 seconds: (2 trip detection logic) (a) Throttle valve fully closed (b) Voltage output of the mass air flow meter is more than 2.2 V. (c) Engine coolant temperature is more than 70 °C (158 °F). (d) Engine speed is less than 900 rpm.	• Mass air flow meter
	Conditions (a), (b) and (c) continue for more than 6 seconds with engine speed: (2 trip detection logic) (a) Engine speed is more than 0 rpm. (b) VTA is more than 0.1 V. (c) Voltage output of the mass air flow meter is less than 0.25 V.	

MONITOR DESCRIPTION

The MAF (Mass Air Flow) meter helps the ECM calculate the amount of air flowing through the throttle valve. The ECM uses this information to determine the fuel injection time and provide a proper air fuel ratio. Inside the MAF meter, there is a heated platinum wire exposed to the flow of intake air. By applying a specific current to the wire, the ECM heats this wire to a given temperature. The flow of incoming air cools the wire and an internal thermistor, affecting their resistance. To maintain a constant current value, the ECM varies the voltage applied to these components in the MAF meter. The voltage level is proportional to the air flow through the MAF meter. The ECM interprets this voltage as the intake air amount. If there is a defect in the MAF meter or an open or short circuit, the voltage level will deviate outside the normal operating range. The ECM interprets this deviation as a defect in the MAF meter and sets a DTC.

Example:

If the voltage is more than 2.2 V at idle or less than 0.25 V at idle OFF, the ECM interprets this as a defect in the MAF meter and sets a DTC.

MONITOR STRATEGY

Related DTCs	P0101	Mass air flow meter rationality
Required sensors/components	Main sensors/components	Mass air flow meter
	Related sensors/components	Engine speed sensor, Engine coolant temperature sensor, Throttle position sensor
Frequency of operation	Continuous	
Duration	10 sec. (High voltage) 6 sec. (Low voltage)	
MIL operation	2 driving cycles	
Sequence of operation	None	

TYPICAL ENABLING CONDITIONS

Item	Specification	
	Minimum	Maximum
The monitor will run whenever the following DTCs are not present	See "List of disable a monitor" (on page DI-3)	
High voltage:		
Engine speed	–	900 rpm
Idle	ON	
Engine coolant temperature	70°C (158°F)	–
Low voltage:		
Engine speed	0 rpm	–
Throttle position	0.1 V	–

TYPICAL MALFUNCTION THRESHOLDS

Detection Criteria	Threshold
Mass air flow meter voltage (High voltage)	More than 2.2 V
Mass air flow meter voltage (Low voltage)	Less than 0.25 V

INSPECTION PROCEDURE

HINT:

Read freeze frame data using the hand-held tester or the OBD II scan tool. Freeze frame data records the engine conditions when a malfunction is detected. When troubleshooting, freeze frame data can help determine if the vehicle was running or stopped, if the engine was warmed up or not, if the air-fuel ratio was lean or rich, and other data from the time the malfunction occurred.

1	Are there any other codes (besides DTC P0101) being output?
---	--

PREPARATION:

- (a) Connect the hand-held tester or the OBD II scan tool to DLC3.
- (b) Turn the ignition switch ON and push the hand-held tester or OBD II scan tool main switch ON.
- (c) When using hand-held tester, enter the following menus: DIAGNOSIS / ENHANCED OBD II / DTC INFO / CURRENT CODES.

CHECK:

Read the DTC using the hand-held tester or the OBD II scan tool.

RESULT:

Display (DTC output)	Proceed to
"P0101" and other DTCs	A
Only P0101	B

HINT:

If any other codes besides P0101 are output, perform the troubleshooting for those codes first.

