

1998 MY Catalyst Deterioration Monitor (P0420, P0430)

To return to monitor description, see page [Ca-1](#).

MONITOR STRATEGY

Required sensors/Components	Main	Front heated oxygen sensor (or A/F sensor) and Rear heated oxygen sensor
	Sub	Crankshaft position sensor, ECT sensor, IAT sensor and MAF sensor (or MAP sensor)
Frequency of operation	Once per driving cycle	
Duration	Included in the Typical Malfunction Thresholds	
MIL operation	2 driving cycles	
Sequence of operation	None	

TYPICAL ENABLING CONDITIONS

The monitor will run whenever the following DTCs are not present	See page In-39
Included in the Typical Malfunction Thresholds	—

TYPICAL MALFUNCTION THRESHOLDS

Engine Family	Detection Criteria	Threshold (Duration)	Typical Enabling Condition
5E-FE	Catalyst deterioration level	0.5 or more for (15 min.)	• Closed Loop • Engine RPM is 3,500 rpm or less • Intake air amount is between 5 and 12 liters/sec. • Catalyst is warmed up • ECT is more than 80°C (176°F)
2JZ-GE	Catalyst deterioration level	0.6 or more (for 45 sec.)	• Closed Loop • Engine RPM is 3,000 rpm or less • Intake air amount is between 8 and 18 g/sec. • Catalyst is warmed up • ECT is more than 80°C (176°F)
2JZ-GTE	Catalyst deterioration level	0.5 or more (for 30 sec.)	• Closed Loop • Engine RPM is 3,000 rpm or less • Intake air amount is between 10 and 16 g/sec. • Catalyst is warmed up • ECT is more than 80°C (176°F)
1MZ-FE (50 states) Avalon, Camry and ES300	Catalyst deterioration level	0.32 or more (for 60 sec.)	• Closed Loop • Engine RPM is 3,000 rpm or less • Intake air amount is between 15 and 30 g/sec. • Catalyst is warmed up • ECT is more than 70°C (158°F)
1MZ-FE (California) Avalon, Camry and ES300	Catalyst deterioration level	0.5 or more (for 40 sec.)	• Closed Loop • Engine RPM is 2,700 rpm or less • Intake air amount is between 6 and 26 g/sec. • Catalyst is warmed up • ECT is more than 50°C (122°F)

1MZ-FE Sienna	Catalyst deterioration level	0.4 or more (for 60 sec.)	• Closed Loop • Engine RPM is 3,000 rpm or less • Intake air amount is between 15 and 30 g/sec. • Catalyst is warmed up • ECT is more than 70°C (158°F)
2RZ-FE and 3RZ-FE	Catalyst deterioration level	0.7 or more (for 120 sec.)	• Closed Loop • Engine RPM is 3,000 rpm or less • Intake air amount is between 8 and 30 g/sec. • Catalyst is warmed up • ECT is more than 80°C (176°F)
3RZ-FE Prerunner	Catalyst deterioration level	0.7 or more detected 4 times during 1 driving cycle (for 300 sec.)	• Battery voltage is 11 V or more • Closed Loop • Engine RPM is 3,000 rpm or less • Intake air amount is between 8 and 30 g/sec. • Catalyst is warmed up • IAT is -10°C (14°F) or more • ECT is more than 80°C (176°F) • 20 sec. have passed after above conditions are met
3S-FE (California)	Catalyst deterioration level	1.0 or more (for 36 sec.)	• Closed Loop • Engine RPM is 2,500 rpm or less • Intake air amount is between 4 and 14 liters/sec. • A/F sensor voltage is between 3.0 and 3.5 V • Catalyst is warmed up • ECT is more than 80°C (176°F) • IAT is -10°C (14°F) or more
3S-FE (Federal)	Catalyst deterioration level	0.7 or more (for 100 sec.)	• Closed Loop • Engine RPM is 3,000 rpm or less • Intake air amount is between 5 and 14 liters/sec. • Catalyst is warmed up • ECT is more than 80°C (176°F)
5S-FE Camry (Federal)	Catalyst deterioration level	0.7 or more (for 100 sec.)	• Closed Loop • Engine RPM is 3,000 rpm or less • Intake air amount is between 5 and 14 liters/sec. • Catalyst is warmed up • ECT is more than 80°C (176°F) • IAT is -10°C (14°F) or more
5S-FE Camry (California)	Catalyst deterioration level	1.0 or more (for 36 sec.)	• IAT is -10°C (14°F) or more • Closed Loop • Engine RPM is 2,500 rpm or less • Intake air amount is between 4 and 14 liters/sec. • A/F sensor voltage is between 3.0 and 3.5 V • Catalyst is warmed up • ECT is more than 80°C (176°F)

5S-FE Celica	Catalyst deterioration level (vehicle running)	0.6 or more (detected 4 times during 1 driving cycle for 15 min.) [A/T] 0.55 or more (detected 4 times during 1 driving cycle for 15 min.) [M/T]	• Battery voltage is 11 V or more • IAT is -10°C (14°F) or more • Closed Loop • Engine RPM is 3,000 rpm or less • Intake air amount is between 5 and 19 liters/sec. • Catalyst is warmed up • ECT is more than 80°C (176°F) • 16 sec. have passed after above conditions are met
	Catalyst deterioration level (Idling)	0.5 or more (detected 4 times during 1 driving cycle for 15 min.)	• Closed Loop • Intake air amount is between 1.5 and 3 liters/sec. • Shift position is D (A/T) • Vehicle speed is less than 3 km/h • Catalyst is warmed up • ECT is more than 80°C (176°F) • 16 sec. have passed after above conditions are met
1UZ-FE	Catalyst deterioration level	0.6 or more (for 45 sec.)	• Closed Loop • Engine RPM is 3,000 rpm or less • Intake air amount is between 5 and 25 g/sec. • Catalyst is warmed up • ECT is more than 30°C (86°F)
2UZ-FE	Catalyst deterioration level	0.6 or more (detected 4 times during 1 driving cycle for 9 min.)	• Battery voltage is 11 V or more • IAT is -10°C (14°F) or more • Closed Loop • Engine RPM is 3,000 rpm or less • Intake air amount is between 10 and 25 g/sec. • Catalyst is warmed up • ECT is more than 80°C (176°F) • 15 sec. have passed after above conditions are met
5VZ-FE Prerunner	Catalyst deterioration level	0.6 or more (detected 4 times during 1 driving cycle for 8 min.)	• Battery voltage is 11 V or more • IAT is -10°C (14°F) or more • Closed Loop • Engine RPM is 3,000 rpm or less • Intake air amount is between 10 and 20 g/sec. • Catalyst is warmed up • 14 sec. have passed after above conditions are met
5VZ-FE except Prerunner	Catalyst deterioration level	0.6 or more (for 56 sec.) [M/T] 0.6 or more (for 70 sec.) [A/T]	• Closed Loop • Engine RPM is 3,000 rpm or less • Intake air amount is between 10 and 20 g/sec. • Catalyst is warmed up • ECT is more than 70°C (158°F)
1ZZ-FE	Catalyst deterioration level	0.5 or more (for 39 sec.) [Federal] 0.35 or more (for 39 sec.) [California]	• Closed Loop • Engine RPM is 3,000 rpm or less • Intake air amount is between 4.8 and 12 g/sec. • Catalyst is warmed up • ECT is more than 65°C (149°F)

OBD MONITOR DRIVE PATTERNS

See page [In-13](#)

MODE 06 DATA (MONITOR RESULT)

- (a) Checking monitor status (See page [In-43](#))
- (b) Detecting Mode 06 data (See page [In-44](#))