

2003 MY for Shift Solenoid "D" Control Circuit (Shift Solenoid Valve S4) Monitor (P0768)

To return to monitor description, see page [Cm-368](#).

MONITOR STRATEGY

Required sensors/Components	Main	Shift solenoid valve No.4
	Sub	None
Frequency of operation	Continuous	
Duration	0.032 sec.	
MIL operation	Immediate	
Sequence of operation	None	

TYPICAL ENABLING CONDITIONS

Item		Specification	
		Minimum	Maximum
The monitor will run whenever the following DTCs are not present.		See page In-39	

Engine family	Item	Specification	
		Minimum	Maximum
All models	Condition (A)		
	Solenoid	ON	
	Time after solenoid OFF to ON	More than 0.08 sec.	–
	Condition (B)		
	Solenoid	OFF	
	Time after solenoid OFF to ON	More than 0.08 sec.	–

TYPICAL MALFUNCTION THRESHOLDS

Engine family	Detection criteria	Threshold
All models	Condition (A)	
	Number of solenoid ON/OFF change with intelligent power MOS diagnosis signal failure (Fail at solenoid resistance 8 Ω or less)	2 times Fail, 2 times (0.016 sec.)
	Condition (B)	
	Number of solenoid ON/OFF change with intelligent power MOS diagnosis signal failure (Fail at solenoid resistance 100 kΩ or more)	2 times Fail, 2 times (0.016 sec.)