

1997 MY VSV for Vapor Pressure Sensor Monitor (P0446)

To return to monitor description, see page [Ev-24](#).

MONITOR STRATEGY

Related DTCs	P0446	• VSV for vapor pressure sensor malfunction • Purge line leak
Required sensors/Components	Main	Vapor pressure sensor
	Sub	EVAP VSV, VSV for vapor pressure sensor, IAT sensor, ECT sensor and MAF sensor (or MAP sensor)
Frequency of operation	Once per driving cycle	
Duration	Within 20 sec.	Purge line leak
	Within 10 sec.	VSV for vapor pressure sensor malfunction
MIL operation	2 driving cycles	
Sequence of operation	None	

TYPICAL ENABLING CONDITIONS

Item	Specification	
	Minimum	Maximum
The monitor will run whenever the following DTCs are not present	See page In-39	
IAT	–10°C (14°F)	–
(a) ECT at engine start	10°C (50°F)	35°C (95°F)
(b) IAT at engine start	10°C (50°F)	35°C (95°F)
Difference between (a) and (b)	–	7°C (45°F)
Time after engine start	300 sec.	–
Intake air amount (MAF sensor equipped)	–	0.6 g/rev.
Intake manifold vacuum (MAP sensor equipped)	–	–200 mmHg (–26.7 kPa)
EVAP VSV duty signal	20 %	–
“Run” (7 km/h [4 mph] or more) and “stop” (3 km/h [2 mph] or less)	Once	

TYPICAL MALFUNCTION THRESHOLDS

Engine Family	Detection Criteria	Threshold
5E-FE	• Change in canister pressure after purge cut • Canister pressure at 7 to 12 sec. after purge cut	3 mmHg (0.4 kPa) or more Between –3 mmHg (–0.4 kPa) and 3 mmHg (0.4 kPa)
	• Change in canister pressure after VSV for vapor pressure sensor ON • Change in canister pressure • Change in fuel tank pressure	Less than 2.9 mmHg (0.39 kPa) Less than 1.1 mmHg (0.15 kPa) 4.8 mmHg (0.64 kPa) or more
1MZ-FE	• Change in canister pressure after purge cut • Canister pressure at 7 to 12 sec. after purge cut	3 mmHg (0.4 kPa) or more Between –3 mmHg (–0.4 kPa) and 3 mmHg (0.4 kPa)
	• Change in canister pressure after VSV for vapor pressure sensor ON • Change in canister pressure • Change in fuel tank pressure	Less than 2.9 mmHg (0.39 kPa) Less than 1.08 mmHg (0.14 kPa) 1.9 mmHg (0.25 kPa) or more

3RZ-FE	• Change in canister pressure after purge cut • Canister pressure at 7 to 12 sec. after purge cut	3.5 mmHg (0.47 kPa) or more Between –3 mmHg (–0.4 kPa) and 3 mmHg (0.4 kPa)
	• Change in canister pressure after VSV for vapor pressure sensor ON • Change in canister pressure • Change in fuel tank pressure	Less than 2 mmHg (0.27 kPa) Less than 0.83 mmHg (0.11 kPa) 1.1 mmHg (0.15 kPa) or more
3S-FE	• Change in canister pressure after purge cut • Canister pressure at 7 to 12 sec. after purge cut	3.5 mmHg (0.47 kPa) or more Between –3 mmHg (–0.4 kPa) and 3 mmHg (0.4 kPa)
	• Change in canister pressure after VSV for vapor pressure sensor ON • Change in canister pressure • Change in fuel tank pressure	Less than 2.9 mmHg (0.39 kPa) Less than 1.1 mmHg (0.15 kPa) 6.8 mmHg (0.90 kPa) or more
5S-FE	• Change in canister pressure after purge cut • Canister pressure at 7 to 12 sec. after purge cut	3 mmHg (0.4 kPa) or more Between –3 mmHg (–0.4 kPa) and 3 mmHg (0.4 kPa)
	• Change in canister pressure after VSV for vapor pressure sensor ON • Change in canister pressure • Change in fuel tank pressure	Less than 2.9 mmHg (0.39 kPa) Less than 1.1 mmHg (0.15 kPa) 2.6 mmHg (0.35 kPa) or more
1UZ-FE LS400	• Change in canister pressure after purge cut • Canister pressure at 7 to 12 sec. after purge cut	3 mmHg (0.4 kPa) or more Between –3 mmHg (–0.4 kPa) and 3 mmHg (0.4 kPa)
	• Change in canister pressure after VSV for vapor pressure sensor ON • Change in canister pressure • Change in fuel tank pressure	Less than 2.9 mmHg (0.39 kPa) Less than 1.1 mmHg (0.15 kPa) 4 mmHg (0.53 kPa) or more
1UZ-FE SC400	• Change in canister pressure after purge cut • Canister pressure at 7 to 12 sec. after purge cut	3 mmHg (0.4 kPa) or more Between –3 mmHg (–0.4 kPa) and 3 mmHg (0.4 kPa)
	• Change in canister pressure after VSV for vapor pressure sensor ON • Change in canister pressure • Change in fuel tank pressure	Less than 2.9 mmHg (0.39 kPa) Less than 0.64 mmHg (0.09 kPa) 4 mmHg (0.53 kPa) or more
5VZ-FE Tacoma and 4runner	• Change in canister pressure after purge cut • Canister pressure at 7 to 12 sec. after purge cut	3 mmHg (0.4 kPa) or more Between –3 mmHg (–0.4 kPa) and 3 mmHg (0.4 kPa)
	• Change in canister pressure after VSV for vapor pressure sensor ON • Change in canister pressure • Change in fuel tank pressure	Less than 2 mmHg (0.27 kPa) Less than 0.55 mmHg (0.07 kPa) 0.7 mmHg (0.09 kPa) or more
5VZ-FE T100	• Change in canister pressure after purge cut • Canister pressure at 7 to 12 sec. after purge cut	3 mmHg (0.4 kPa) or more Between –3 mmHg (–0.4 kPa) and 3 mmHg (0.4 kPa)
	• Change in canister pressure after VSV for vapor pressure sensor ON • Change in canister pressure • Change in fuel tank pressure	Less than 2.9 mmHg (0.39 kPa) Less than 0.55 mmHg (0.07 kPa) 0.7 mmHg (0.09 kPa) or more

OBD MONITOR DRIVE PATTERNS

See page [In-13](#)

MODE 06 DATA (MONITOR RESULT)

- Checking monitor status (See page [In-43](#))
- Detecting Mode 06 data (See page [In-44](#))