

LUBRICANT

Item	Capacity			Classification
	Liters	US qts	Imp. qts	
Engine oil				API grade SF or SF/ CC, multigrade viscosity oil
Dry fill	8.0	8.5	7.0	
Drain and refill				
w/ Oil filter change w/o Oil filter change	7.8 7.0	8.2 7.4	6.9 6.2	
Automatic transmission fluid				ATF DEXRON® II
Dry fill				
w/o Oil cooler w / Oil cooler	15.0	15.9	13.2	
Drain and refill	15.4 6.0	16.3 6.3	13.6 5.3	
Transfer oil	2.1	2.2	1.8	API GL-4 or GL-5, SAE 90
Differential oil				API GL-5 hypoid gear oil Above -18°C (0°F) SAE 90 Below -18°C (0°F) SAE 80W or SAE 80W-90
Front	3.0	3.2	2.6	
Rear	2.5	2.6	2.2	
Chassis grease Propeller shaft	—			Lithium base, N LG I No.2
Wheel bearing grease	—			Lithium base, multipurpose, NLGI No.2
Steering knuckle and front axle shaft grease	—			Molybdenum disulphide lithium base, NLGI No.2
Brake fluid	—			SAE J 1703 or FMVSS No.116 DOT3
Power steering fluid				ATF DEXRON® or DEXRON® II
Total	810 cc	27.4 oz		
Reservoir tank	390 cc	13.2 oz		