

AUTOMATIC TRANSMISSION

Specifications

Engine stall revolution		1,950 ± 150 rpm		
Engine idle speed	N range	650 rpm		
Time day	N range → D range	Less than 0.7 seconds		
	N range → R range	Less than 1.2 seconds		
Line pressure (wheel locked)				
Engine idling	D range	3.7 – 4.3 kg/cm ²	53 – 61 psi	363 – 422 kPa
	R range	4.5 – 5.5 kg/cm ²	64 – 78 psi	441 – 539 kPa
At stall	D range	11.1 – 13.6 kg/cm ²	158 – 193 psi	1,089 – 1,334 kPa
	R range	14.0 – 17.0 kg/cm ²	199 – 242 psi	1,373 – 1,667 kPa
Governor pressure				
Output shaft rpm	(Vehicle speed reference)			
1,000	(approx. 32 km/h, 20 mph)	0.8 – 1.2 kg/cm ²	11 – 17 psi	78 – 118 kPa
1,800	(approx. 57 km/h, 35 mph)	1.9 – 2.6 kg/cm ²	27 – 37 psi	186 – 255 kPa
3,500	(approx. 111 km/h, 69 mph)	5.6 – 6.3 kg/cm ²	80 – 90 psi	547 – 618 kPa
Throttle cable adjustment				
Throttle valve fully closed		Between boot end face and inner cable stopper		
		0.5 – 1.5 mm	0.020 – 0.059 in.	
Throttle valve fully opened		32 – 34 mm	1.26 – 1.34 in.	
Torque converter installation		15.7 mm (0.618 in.) or more		
Torque converter runout	Limit	0.30 mm	0.0118 in.	
Drive plate runout	Limit	0.20 mm	0.0079 in.	

Shift point schedule km/h (mph)	D range (throttle valve fully open)						(fully closed)		2 range	L range
	1 → 2	2 → 3	3 → O/D	O/D → 3	3 → 2	2 → 1	Lock-up ON	Lock-up OFF	3 → 2	2 → 1
Tire size: P235/75R 15	33–46 (21–27)	75–88 (47–55)	110–123 (68–76)	101–114 (63–71)	66–78 (41–48)	28–41 (17–25)	71–82 (44–51)	65–76 (40–47)	77–90 (48–56)	36–48 (22–30)
Tire size: 31 X 10.5 R15	36–50 (22–31)	81–95 (50–59)	118–132 (73–82)	109–123 (68–76)	71–84 (44–52)	31–44 (19–27)	76–88 (47–55)	70–82 (43–51)	83–97 (52–60)	38–52 (24–32)

Oil pump	Body clearance	STD	0.07 – 0.15 mm	0.0028 – 0.0059 in.
		Limit	0.3 mm	0.012 in.
	Tip clearance	STD	0.14 – 0.24 mm	0.0055 – 0.0094 in.
		Limit	0.3 mm	0.012 in.
	Side clearance	STD	0.02 – 0.05 mm	0.0008 – 0.0020 in.
		Limit	0.1 mm	0.004 in.
	Drive and driven gear thickness		18.435 – 18.450 mm	0.7258 – 0.7264 in.
			18.451 – 18.486 mm	0.7264 – 0.7278 in.
	Pump body bushing inside diameter			
		STD	42.050 – 42.075 mm	1.6555 – 1.6565 in.
		Limit	42.13 mm	1.6587 in.
		Front	24.000 mm	24.021 in.
		Rear	26.500 – 26.521 mm	1.0433 – 1.0441 in.
		Front	24.07 mm	0.9476 in.
Rear	26.57 mm	1.0461 in.		

Specifications (Cont'd)

Oil pump (Cont'd)	Pump cover bushing inside diameter	STD	Front	24.000 mm	24.021 in.
			Rear	26.500 – 26.521 mm	1.0433 – 1.0441 in.
		Limit	Front	24.07 mm	0.9476 in.
			Rear	26.57 mm	1.0461 in.
O / D planetary gear and O / D direct clutch	O / D input shaft (O / D planetary gear) thrust clearance	STD		0.40 – 0.90 mm	0.0157 – 0.0354 in.
		Limit		0.90 mm	0.0354 in.
	O / D input shaft thrust bearing race thickness			0.8 mm	0.031 in.
				1.0 mm	0.039 in.
				1.4 mm	0.055 in.
				1.10 – 1.70 mm	0.0433 – 0.0669 in.
	Piston stroke				
	O / D direct clutch drum bushing inside diameter	STD		26.500 – 26.521 mm	1.0433 – 1.0441 in.
		Limit		26.57 mm	1.0461 in.
	O / D planetary gear bushing inside diameter	STD		12.000 – 12.018 mm	
		Limit		12.07 mm	0.4752 in.
	Planetary pinion gear thrust clearance	STD		0.20 – 0.59 mm	0.0079 – 0.0232 in.
		Limit		0.80 mm	0.315 in.
O / D brake	Piston stroke O / D case bushing inside diameter			1.25 – 1.85 mm	0.0492 – 0.0728 in.
		STD		33.100 – 33.150 mm	1.3031 – 1.3051 in.
		Limit		33.20 mm	1.3071 in.
Front clutch	Input shaft (forward clutch hub) thrust clearance	STD		0.30 – 0.70 mm	0.0118 – 0.0276 in.
		Limit		0.70 mm	0.0276 in.
	Input shaft spacer thickness			0.9 mm	0.035 in.
				1.2 mm	0.047 in.
				1.5 mm	0.059 in.
				1.8 mm	0.071 in.
				2.1 mm	0.083 in.
				3.93 – 4.23 mm	0.1547 – 0.1665 in.
	Piston stroke				
	Front clutch plate thickness			1.8 mm	0.071 in.
				2.0 mm	0.079 in.
				2.2 mm	0.087 in.
				2.4 mm	0.094 in.
Rear clutch	Piston stroke Rear clutch flange thickness			1.70 – 1.90 mm	0.0669 – 0.748 in.
				5.0 mm	0.197 in.
				5.2 mm	0.205 in.
				5.4 mm	0.213 in.
				5.6 mm	0.220 in.
Second brake	Center support thrust clearance	STD		0.30 – 0.70 mm	0.0118 – 0.0276 in.
		Limit		0.90 mm	
	Center support thrust washer thickness			1.8 mm	0.071 in.
				2.1 mm	0.083 in.
				2.4 mm	0.094 in.
				2.6 mm	0.102 in.
	Piston stroke			1.60 – 1.80 mm	0.0630 – 0.0709 in.

Specifications (Cont'd)

Second brake (Cont'd)	Center support bushing	STD	35.000 – 35.025 mm	1.3780 – 1.3789 in.	
	inside diameter	Limit	35.08 mm	1.3811 in.	
	Front planetary sun gear bushing	STD	24.000 – 24.021 mm	0.9449 – 0.9457 in.	
	inside diameter	Limit	24.07 mm	0.9476 in.	
	Second brake flange thickness		5.0 mm	0.197 in.	
			5.2 mm	0.205 in.	
			5.4 mm	0.213 in.	
			5.6 mm	0.220 in.	
Planetary gears and output shaft	Output shaft bushing inside diameter	STD	17.000 – 17.018 mm	0.6693 – 0.6700 in.	
	Planetary pinoin gear thrust clearance	Limit	17.07 mm	0.6720 in.	
		STD	0.20 – 0.50 mm	0.0079 – 0.0197 in.	
		Limit	0.75 mm	0.0295 in.	
1st and reverse brake	Piston stroke		3.3 – 3.8 mm	0.130 – 0.150 in.	
	1st and reverse brake flange thickness		6.65 mm	0.2618 in.	
			7.05 mm	0.2776 in.	
			7.45 mm	0.2933 in.	
Transmission case	Bushing inside diameter	STD	64.000 – 64.050 mm	2.5197 – 2.5216 in.	
		Limit	64.10 mm	2.5236 in.	
Valve body spring	Spring	Free length mm (in.)	Coil outer diameter mm (in.)	Total No. of coils	Color
	(Front upper valve body)				
	Check ball	13.0 (0.512)	8.4 (0.331)	8.0	None
	Primary throttle valve	25.3 (0.996)	9.2 (0.362)	9.5	White
	Primary down–shift plug	26.9 (1.059)	9.0 (0.354)	10.5	Blue
	Secondary regulator valve	46.0 (1.811)	13.3 (0.524)	15.0	None
	Secondary throttle valve	25.3 (0.996)	9.2 (0.362)	9.5	White
	Secondary down–shift plug	32.6 (1.283)	9.7 (0.382)	13.0	White
	Throttle valve sleeve	10.8 (0.425)	18.2 (0.717)	4.0	None
	(Rear upper valve body)				
	2–3 shift valve	42.2 (1.661)	8.9 (0.350)	22.0	White
	2–3 shift timing valve	29.4 (1.157)	8.6 (0.339)	15.5	None
	3–4 shift valve	38.3 (1.508)	9.7 (0.382)	17.0	None
	Detent regulator valve	30.4 (1.197)	7.4 (0.291)	16.0	White
	Lock–up signal valve	47.6 (1.874)	13.7 (0.539)	16.0	Blue
	O / D clutch exhaust valve	33.3 (1.311)	8.2 (0.323)	14.0	Yellow
	Intermediate modulator valve	22.5 (0.886)	7.7 (0.303)	12.0	Pink
	(Lower valve body)				
	Check valve	27.7 (1.091)	8.2 (0.323)	13.0	None
	Check ball	13.0 (0.512)	8.4 (0.331)	8.0	None
	1–2 shift valve	26.6 (1.047)	6.9 (0.272)	16.0	None
	3–2 kick–down orifice control valve	32.5 (1.280)	8.3 (0.327)	14.0	Blue
	2nd lock valve	29.4 (1.158)	8.3 (0.327)	14.0	Brown

Specifications (Cont'd)

Valve body spring (Cont'd)	Spring	Free length mm (in.)	Coil outer diameter mm (in.)	Total No. of coils	Color
	Lock-up relay valve	32.4 (1.278)	9.3 (0.366)	15.0	Pink
	Primary regulator valve	58.2 (2.291)	20.9 (0.823)	11.0	None
	Accumulator control valve	25.1 (0.988)	12.5 (0.492)	8.5	Red
	Low coast modulator valve	30.0 (1.181)	7.3 (0.287)	16.0	Yellow
	1-2 relay valve	22.9 (0.902)	5.1 (0.201)	15	None
Accumulator spring	B0	64.1 (2.524)	21.1 (0.831)	13.0	None
	B2	65.0 (2.559)	25.1 (0.988)	8.5	Yellow
	C1	92.3 (3.634)	17.9 (0.708)	20.0	None
	C2	80.0 (3.150)	21.8 (0.858)	15.0	White

Torque Specifications

Part tightened		kg-cm	ft-lb	N-m
Engine x Transmission	14 mm head bolt	380	27	37
	17 mm head bolt	730	53	72
Torque converter x Drive plate		290	21	28
Frame crossmember set bolt		620	45	61
Frame crossmember set nut		600	43	59
Oil cooler pipe union nut		350	25	34
Propeller shaft x Transfer		900	65	88
Propeller shaft x Differential		900	65	88
Oil pump cover x Oil pump body	10 mm head bolt	90	78 in.-lb	8.8
	12 mm head bolt	210	15	21
Lower valve body cover x Lower valve body		55	48 in.-lb	5.4
Front upper valve body x Lower valve body		55	48 in.-lb	5.4
Rear upper valve body x Lower valve body		55	48 in.-lb	5.4
Manual detent spring x Lower valve body		55	48 in.-lb	5.4
Parking lock pawl x Transfer adaptor		195	14	19
Transmission rear cover x Transmission case		80	69 in.-lb	7.8
Front accumulator cover x Transmission case		80	69 in.-lb	7.8
Governor cover x Governor valve body support		100	7	10
Transfer adaptor x Transmission case		380	27	37
Center support set bolt		250	18	25
O / D case set bolt		250	18	25
Oil pump x Transmission case		210	16	21
Valve body x Transmission case		100	7	10
Oil strainer x Valve body	8 mm head bolt	55	48 in.-lb	5.4
	10 mm head bolt	100	7	10
Lock-up relay valve body plate x Valve body				
	8 mm head bolt	55	48 in.-lb	5.4
	10 mm head bolt	100	7	10

Torque Specifications (Cont'd)

Part tightened	kg-cm	ft-lb	N·m
Oil pan x Transmission case	70	61 in.-lb	6.9
Transmission housing x Transmission case	650	47	64
A/T fluid temperature sensor x Transmission case	350	25	34
Oil cooler union x Transmission case	300	22	29
Neutral start switch x Transmission case	130	9	13
Neutral start switch x Manual valve shaft	70	61 in.-lb	6.9
Oil cooler pipe x Oil cooler union	350	25	34
Control shaft x Transmission case	130	9	13
Under cover x Body	290	21	28
Rear mounting x Transmission	600	43	59
Transmission control rod x Control lever	130	9	13

TRANSFER Specifications

Input shaft snap ring	Mark		
	A	2.0 mm	0.0787 in.
	B	2.1 mm	0.0827 in.
	C	2.2 mm	0.0866 in.
	D	2.3 mm	0.0906 in.
	E	2.4 mm	0.0945 in.
	F	2.5 mm	0.0984 in.
	G	2.6 mm	0.1024 in.
	H	2.7 mm	0.1063 in.
	J	2.8 mm	0.1102 in.
Idle low gear thrust clearance	STD	0.125 – 0.275 mm	0.0049 – 0.0108 in.
	Limit	0.275 mm	0.0108 in.
Idle low gear oil clearance	STD	0.015 – 0.068 mm	0.0006 – 0.0027 in.
	Limit	0.068 mm	0.0027 in.
High speed gear thrust clearance	STD	0.10 – 0.25 mm	0.0039 – 0.0098 in.
	Limit	0.25 mm	0.0098 in.
High speed gear oil clearance	STD	0.015 – 0.071 mm	0.0006 – 0.0028 in.
	Limit	0.071 mm	0.0028 in.
Center differential backlash adjusting shim		1.70 mm	0.0669 in.
		1.85 mm	0.0728 in.
		2.00 mm	0.0787 in.
		2.15 mm	0.0846 in.
		2.30 mm	0.0906 in.
		2.45 mm	0.0965 in.
		2.60 mm	0.1024 in.
		2.75 mm	0.1083 in.
		2.90 mm	0.1142 in.
		3.05 mm	0.1201 in.
Center differential backlash	Limit	0.05 mm	0.0020 in.