

SERVICE SPECIFICATIONS

SERVICE DATA

IG03C-01

Firing order	—		1—5—3—6—2—4		
High—tension cord	Resistance (Maximum)		25 kΩ per cord		
Spark plug	Recommended spark plug Recommended spark plug Correct electrode gap	ND NGK	K16R-U BKR5EYA 0.8 mm (0.031 in.)		
Ignition coil	Primary coil resistance (Cold) Primary coil resistance (Hot) Secondary coil resistance (Cold) Secondary coil resistance (Hot)		0.36 — 0.55 Ω 0.45 — 0.65 Ω 9.0 — 15.4 kΩ 11.4 — 18.1 kΩ		
Distributor	Air gap Signal generator (pickup coil) resistance (Cold) Signal generator (pickup coil) resistance (Hot)		0.2 — 0.4 mm (0.008 — 0.016 in.) 185 — 275 Ω 240 — 325 Ω		
	Distributor advance angle (Part No.)	Governor		Vacuum	
		Dis. rpm	Advance angle	kPa (mmHg, in.Hg)	Advance angle
		19100-66010	500 740 1,150 1,626 2,659 3,000	Advance begins 2.3° 7.0° 6.4° 14.0° 13.8°	13.3 (100, 3.94) 25.3 (190, 7.48) 36.0 (270, 10.62)

IG

V00796

TORQUE SPECIFICATIONS

IG017-02

Part tightened	N·m	kgf·cm	ft·lbf
Spark plug x Cylinder head	20	200	14
Distributor x Cylinder head	18	180	13

IG