

LUBRICANT

Item	Capacity			Classification
	Liters	US qts	Imp. qts	
Engine oil				API grade SG, multigrade viscosity oil
Dry fill	8.0	8.5	7.0	
Drain and refill				
w/ Oil filter change	7.8	8.2	6.9	
w/o Oil filter change	7.0	7.4	6.2	
Automatic transmission fluid				ATF DEXRON® II
Dry fill				
w/ Oil cooler	15.4	16.3	13.6	
w/o Oil cooler	15.0	15.9	13.2	
Drain and refill	6.0	6.3	5.3	
Transfer oil	1.3	1.4	1.1	API GL-4 or GL-5, SAE 75W-90
Differential oil				API GL-5 hypoid gear oil Above -18°C (0°F) SAE 90 Below -18°C (0°F) SAE 80W or SAE 80W-90
Front	2.8	2.9	2.4	
Rear	2.8	2.9	2.4	
Power steering fluid				ATF DEXRON® II
Gear box	0.51	0.13	0.11	
Total	0.75	0.20	0.17	
Chassis grease	—			Lithium base, NLGI No.2
Propeller shaft				
Wheel bearing grease	—			Lithium base, multipurpose NLGI No.2
Brake fluid	—			SAE J 1703 or FMVSS No. 116 DOT3