

SERVICE SPECIFICATIONS

IG05M-01

SERVICE DATA

Ignition timing	w/ Terminals TE1 and E1 connected	3° BTDC @ idle
Firing order	—	1 - 5 - 3 - 6 - 2 - 4
High-tension cord	Resistance (Maximum)	25 kΩ per cord
Spark plug	Recommended spark plug ND	K16R-U
	Recommended spark plug NGK	BKR5EYA
	Correct electrode gap	0.8 mm (0.031 in.)
Ignition coil	Primary coil resistance (Cold)	0.36 - 0.55 Ω
	Primary coil resistance (Hot)	0.45 - 0.65 Ω
	Secondary coil resistance (Cold)	9.0 - 15.4 kΩ
	Secondary coil resistance (Hot)	11.4 - 18.1 kΩ
Distributor	Air gap	0.2 - 0.4 mm (0.008 - 0.016 in.)
	Signal generator (pickup coil) resistance (Cold)	
	G1 - G⊖	185 - 275 Ω
	G2 - G⊖	185 - 275 Ω
	NE - G⊖	185 - 275 Ω
	Signal generator (pickup coil) resistance (Hot)	
	G1 - G⊖	240 - 325 Ω
	G2 - G⊖	240 - 325 Ω
	NE - G⊖	240 - 325 Ω

IG017-02

TORQUE SPECIFICATIONS

Part tightened	N·m	kgf·cm	ft·lbf
Spark plug x Cylinder head	20	200	14
Distributor x Cylinder head	18	180	13