

SERVICE SPECIFICATIONS

TORQUE SPECIFICATIONS

BO18T-01

Part tightened	N	kgf-cm	ft-lbf
	• _ m	—	—
HOOD			
Hood hinge x Hood	18	185	13
Hood lock x Body	8	80	69 in.lbf
FRONT DOOR	—	—	—
Door hinge x Body	24	240	17
Door hinge x Door panel	24	240	17
Door lock x Door panel	5	50	43 in.-lbf
Window regurater x Door panel	5	50	43 in.-lbf
REAR DOOR	—	—	—
Door hinge x Body	24	240	17
Door hinge x Door panel	24	240	17
Door lock x Door panel	5	50	43 in. lbf
Window regurater x Door panel	5	50	43 in.-lbf
WINDSHELD	—	—	—
Wiper arm x Body	20	205	15
BACK DOOR GLASS	—	—	—
Rear wiper arm x Body	5.4	55	48 in.-lbf
SEAT	—	—	—
Front Seat	—	—	—
Seat track x Body	39	400	29
Seat track x Seat	29	300	22
Seat adjuster x Seatback	52	530	38
Second Seat	—	—	—
Seat cushion hinge x Body	39	400	29
Seat hinge x Seatback	41	420	30
Seat adjuster x Seatback	52	530	38
Third Seat	—	—	—
Seatback hinge x Seatback	18	185	13
Seat adjuster x Seatback	52	530	38
SEAT BELT	—	—	—
Adjustable anchor x Body	43	440	32
ELR x Body	4.9	50	43 in.lbf
Outer belt anchor x Body	43	440	32
Inner belt x Seat	43	440	32
SIDE STEP	—	—	—
Side step bracket x Body	13	130	9
Side step bracket x Side panel	5.4	55	4.8 in.lbf