

SERVICE SPECIFICATIONS

EG06P-06

SERVICE DATA

VSV for EVAP	Resistance	30 – 33Ω et 20 ° C (68 ° -F)
VSV for EGR	Resistance	30 – 34Ω et 20 ° C (68 ° -F)
VSV for PAIR	Resistance	37 – 44 Ω at 20 ° C (68 ° -F)

TORQUE SPECIFICATIONS

EG06Q-06

Part tightened	N-m	kgf-cm	ft-lbf
Charcoal canister x Charcoal canister bracket	14	145	10
Charcoal canister bracket x Body	18	185	13
TVV x Cylinder head	29	300	22
EGR valve x Air intake chamber for stud bolt	10	105	8
EGR valve x Air intake chamber for nut	19	195	14
EGR valve x EGR pipe	64	650	47
EGR valve x EGR gas temp. sensor	20	200	14
EGR valve x EGR vacuum modulator	18	185	13
PAIR reed valve x Cylinder head	20	200	14
Air pipe x PAIR reed valve	21	210	15
Air pipe x No. 1 exhaust manifold	21	210	15
Air pipe x No.2 exhaust manifold	21	210	15
Air pipe x Cylinder head	20	200	14
Converter insulator cover x TWC	11	110	8
No.1 front exhaust pipe x TWC	39	400	29
No.2 front exhaust pipe x TWC	39	400	29
No.1 front exhaust pipe x No.1 exhaust manifold	62	630	46
No.2 front exhaust pipe x No.2 exhaust manifold	62	630	46
No.1 support bracket x Transmission	24	240	17
No.1 support bracket x Clamp bolt	19	195	14
TWC x No.3 front exhaust pipe	39	400	29