

SERVICE SPECIFICATIONS

IG08M-01

SERVICE DATA

Ignition timing	w/ Terminals TE1 and E1 connected	3° BTDC @ idle
Firing order	—	1-5-3-6-2-4
High-tension cord	Resistance (Maximum)	25 k Ω per cord
Spark plug	Recommended spark plug Recommended spark plug Correct electrode gap	ND NGK K18R-U 6KR5EYA 0.8 mm (0.031 in.)
Ignition coil	Primary coil resistance (Cold) Primary coil resistance (Hot) Secondary coil resistance (Cold) Secondary coil resistance (Hot)	0.36 – 0.55 Ω 0.45 – 0.65 Ω 9.0 – 15.4 k Ω 11.4 – 18.1 k Ω
Distributor	Air gap Signal generator (pickup coil) resistance (Cold) G, – G(–) G2–G(–) NE –G(–) Signal generator (pickup coil) resistance (Hot) G1– G(–) G2–G(–) NE–G(–)	0.2 – 0.4 mm (0.008 – 0.016 in.) 185 – 275 Ω 185–275 Ω 185 – 275 Ω 240–3250 240–3250 240–325 Ω

TORQUE SPECIFICATIONS

IG017-02

Part tightened	N-m	kgf-cm	ft-lbf
Spark plug x Cylinder head	20	200	14
Distributor x Cylinder head	18	180	13