

PREPARATION SST(SPECIAL SERVICE TOOLS)

MA00X-02

	09607-60020 Front Wheel Adjusting Nut Wrench	
---	--	--

EQUIPMENT

MA00B-02

Belt tension gauge	
Dial indicator or dial indicator with magnetic base	
Micrometer	
Mirror	Brake hose
Torque wrench	
Vernier calipers	

COOLANT

MA00A-09

Item	Capacity	Classification
Engine coolant (w/ Front heater and rear heaters)	14.2 liters (15.0 US qts, 12.4 Imp. qts)	Ethylene-glycol base

LUBRICANT

MA00C-08

Item	Capacity	Classification
Engine oil Drain and refill w/ Oil filter change w/o Oil filter change	7.4 liters (7.8 US qts, 6.5 Imp. qts) 6.9 liters (7.3 US qts, 6.1 Imp. qts)	API grade SG or SH, Energy- Conserving II or ILSAC multigrade and recommended viscosity oil
Automatic transmission fluid Drain and refill	6.0 liters (6.3 US qts, 5.3 Imp. qts)	ATF DEXRON® II
Transfer oil Drain and refill w/ ABS w/o A BS	1.3 liters (1.4 US qts, 1.1 Imp. qts) 1.7 liters (1.8 US qts, 1.5 Imp. qts)	API GL-4 or GL-5 SAE 75W-90
Differential oil Drain and refill Front (w/o Differential lock) Front (w/ Differential lock) Rear	2.8 liters (2.9 US qts, 2.4 Imp. qts) 2.65 liters (2.8 US qts, 2.3 Imp. qts) 3.25 liters (3.4 US qts, 2.9 Imp. qts)	API GL-5 hypoid gear oil Above -18° C (0° F) SAE 90W Below -18° C (0° F) SAE 80W-90 or 80W