

SERVICE SPECIFICATIONS

MA002-06

SERVICE DATA

Drive belt tension		
Generator	New belt	125 ± 25 lbf
Generator	Used belt	80 ± 20 lbf
A/C compressor	New belt	125 ± 25 lbf
A/C compressor	Used belt	80 ± 20 lbf
Spark plug Recommended spark plug	ND	K16R-U
Spark plug Recommended spark plug	NGK	BKR5EYA
Spark plug Correct electrode gap		0.8 mm (0.031 in.)
Firing order		1 – 5 – 3 – 6 – 2 – 4
Valve clearance	Intake	0.15 – 0.25 mm (0.006 – 0.010 in.)
Valve clearance	Exhaust	0.25 – 0.35 mm (0.010 – 0.014 in.)
Front brake	Minimum	4.0 mm (0.157 in.)
Pad thickness	Minimum	30.0 mm (1.181 in.)
Disc thickness	Maximum	0.15 mm (0.0059 in.)
Disc runout		
Rear brake (Disc)	Minimum	1.0 mm (0.039 in.)
Pad thickness	Minimum	16.0 mm (0.630 in.)
Disc thickness	Maximum	0.15 mm (0.0059 in.)
Disc runout		
Rear brake (Drum)	Minimum	1.5 mm (0.059 in.)
Lining thickness	Maximum	297.0 mm (11.693 in.)
Drum inside diameter		40 mm (1.57 in.) or less
Steering wheel freeplay		

MA00U-05

TORQUE SPECIFICATIONS

Part tightened	N-m	kgf-cm	ft-lbf
Front seat mounting bolts	37	375	27