

SERVICE SPECIFICATIONS

PR02J-01

SERVICE DATA

Propeller shaft runout	Limit	0.8 mm (0.031 in.)
Spider bearing axial play		Less than 0.05 mm (0.0020 in.)
Snap ring thickness	Mark Color	
Front propeller shaft	1 –	2.100 – 2.150 mm (0.0827 – 0.0846 in.)
	2 –	2.150 – 2.200 mm (0.0846 – 0.0866 in.)
	3 –	2.200 – 2.250 mm (0.0866 – 0.0886 in.)
	– Brown	2.250 – 2.300 mm (0.0886 – 0.0906 in.)
	– Blue	2.300 – 2.350 mm (0.0908 – 0.0925 in.)
	6 –	2.350 – 2.400 mm (0.0925 – 0.0945 in.)
	7 –	2.400 – 2.450 mm (0.0945 – 0.0965 in.)
	8 –	2.450 – 2.500 mm (0.0965 – 0.0984 in.)
Rear propeller shaft	– –	2.00 mm (0.0787 in.)
	– Brown	2.03 mm (0.0799 in.)
	– Blue	2.06 mm (0.0811 in.)
	– –	2.09 mm (0.0823 in.)

PR02K-01

TORQUE SPECIFICATIONS

Part tightened	N-m	kgf-cm	ft-lbf
Front propeller shaft x Front differential	74	750	54
Front propeller shaft x Transfer	74	750	54
Rear propeller shaft x Rear differential	88	900	65
Rear propeller shaft x Transfer	88	900	65