









PREPARATION

SST (SPECIAL SERVICE TOOLS)

SAOTN-02

	09214-76011 Crankshaft Pulley Replacer	
	09223-15020 Oil Seal & Bearing Replacer	
	09305-00010 Oil Seal Puller	
	09308-10010 Oil Seal Puller	
	09313-30021 Detent Ball Plug Socket	
	09316-60010 Transmission & Transfer Bearing Replacer	
	(09316-00010) Replacer Pipe	
	(09316-00020) Replace "A"	
	(09316-00050) Replacer- "D"	
	09330-00021 Companion Flange Holding Tool	
	09504-00011 Differential Side Bearing Adjusting Nut Wrench	
	09506-30012 Differential Drive Pinion Rear Bearing Cone Replacer	
	09556-22010 Drive Pinion Front Bearing Remover	

	09557-22022 Companion Flange Remover & Replacer	
	(09557-22050) No. 3 Bolt	
	09608-30012 Front Hub & Drive Pinion Bearing Tool Set	
	(09608-00060) Drive Pinion Front Bearing Cup Replacer	
	(09608-04060) Front Hub Outer Bearing Cup Replacer	
	09726-40010 Lower Control Shaft Bearing Replacer	
	09950-00020 Bearing Remover	
	09950-20017 Universal Puller	

1Y0T-01

	09905-00012 Snap Ring No. 1 Expander	
	09905-00013 Snap Ring Pliers	

8A0TQ-01

EQUIPMENT

Dial indicator	
Torque wrench	

LUBRICANT

Item	Capacity	Classification
Differential oil (w/o Differential lock) (w/ Differential lock)	2.8 liters (2.9 US qts, 2.5 Imp.qts) 2.65 liters (2.8 US qts, 2.3 Imp.qts)	API GL-5 Hypoid gear oil [Above - 18° C (0° F)] SAE 90 [Below -18° C (0° F)] SAE 80W or 80W -90