










PREPARATION

SST (SPECIAL SERVICE TOOLS)


SA100-01

	09214-76011 Crankshaft Pulley Replacer	
	(09252-10010) No. 1 Replacer Handle	
	09308-00010 Oil Seal Puller	
	09308-10010 Oil Seal Puller	
	O^315-00021 Clutch Release Bearing Remover & Replacer	
	09316-60010 Transmission & Transfer Bearing Replacer	
	(09316-00010) Replacer Pipe	
	(09316-00020) Replacer "A"	
	09504-00011 Differential Side Bearing Adjusting Nut Wrench	
	09504-22011 Differential Side Bearing Replacer	
	09506-35010 Differential Drive Pinion Rear Bearing Replacer	
	09550-10012 Replacer Set 'B'	
	09550-60010 Differential Side Bearing Replacer	

	(09558-10010) Rear Axle Shaft Oil Seal Replacer	
	09557-22010 Drive Pinion Front Bearing Remover	
	(09557-10010) Differential Drive Pinion Front Bearing Replacer	
	09608-35014 Axle Hub & Drive Pinion Bearing Tool Set	
	(09608 -06020) Handle	
	(09608-06110) Front Hub Inner & Drive Pinion Front Bearing Cup Replacer	
	(09608-06180) Drive Pinion Rear Bearing Cup Replacer	
	09726-40010 Lower Control Shaft Bearing Replacer	
	09950-00020 Bearing Remover	
	09950-20017 Universal Puller	

RECOMMENDED TOOLS

SA17Y-01

	09025-00010 Small Torque Wrench	
---	---------------------------------	--

EQUIPMENT

SA17Z-01

Dial indicator	
Torque wrench	

LUBRICANT

Item	Capacity	Classification
Differential oil	3.25 liters (3.4 US qts, 2.9 Imp.qts)	API GL-5 Hypoid gear oil [Above - 18* C (0° F)] SAE 90 (Below - 1 8° C (0 F)) SAE 80W or 80W-90