

PREPARATION EQUIPMENT

Belt tension gauge	
Dial indicator or dial indicator with magnetic base	
Micrometer	
Mirror	Brake hose
Torque wrench	
Vernier calipers	

COOLANT

Item	Capacity	Classification
Engine coolant		Ethylene-glycol base
w/ Front heater	12.5 liters (13.2 US qts, 11.0 Imp-qts)	
w/ Front heater and rear heaters	13.4 liters (14.2 US qts, 11.8 Imp-qts)	

LUBRICANT

Item	Capacity	Classification
Engine oil		API grade SH, Energy-Conserving II multi-grade engine oil or IL-SAC multigrade engine oil and recommended viscosity oil, with SAE 5W-30 being preferred engine oil
Drain and refill		
w/ Oil filter change	7.4 liters (7.8 US qts, 6.5 Imp-qts)	
w/o Oil filter change	6.9 liters (7.3 US qts, 6.1 Imp-qts)	
Automatic transmission fluid		ATF DEXRON® II
Drain and refill	1.9 liters (2.0 US qts, 1.7 Imp-qts)	
Transfer oil		API GL-4 or GL-5
Drain and refill	1.7 liters (1.8 US qts, 1.5 Imp-qts)	SAE 75W-90
Differential oil		API GL-5 hypoid gear oil
Drain and refill		Above-18°C (0°F) SAE 90
Front w/o Differential lock	2.8 liters (3.0 US qts, 2.5 Imp-qts)	Below-18°C (0°F) SAE 80W-90
w/ Differential lock	2.65 liters (2.8 US qts, 2.3 Imp-qts)	or 80W
Rear	3.25 liters (3.4 US qts, 2.9 Imp-qts)	