

SERVICE SPECIFICATIONS

SERVICE DATA

Drive belt tension		
Generator	New belt	125 ± 25 lbf
	Used belt	80 ± 20 lbf
A/C compressor	New belt	125 ± 25 lbf
	Used belt	80 ± 20 lbf
Spark plug		
Recommended spark plug	ND	K16R-U
	NGK	BKR5EYA
Correct electrode gap		0.8 mm (0.031 in.)
Firing order		1 – 5 – 3 – 6 – 2 – 4
Valve clearance	Intake	0.15–0.25 mm (0.006–0.010 in.)
	Exhaust	0.25–0.35 mm (0.010–0.014 in.)
Front brake		
Pad thickness	Minimum	1.0 mm (0.039 in.)
Disc thickness	Minimum	30.0 mm (1.181 in.)
Disc runout	Maximum	0.15 mm (0.0059 in.)
Rear brake		
Pad thickness	Minimum	1.0 mm (0.039 in.)
Disc thickness	Minimum	16.0 mm (0.630 in.)
Disc runout	Maximum	0.15 mm (0.0059 in.)
Parking brake		
Lining thickness	Minimum	1.0 mm (0.039 in.)
Drum inside diameter	Maximum	231 mm (9.09 in.)
Steering wheel freeplay	Maximum	40 mm (1.57 in.)

TORQUE SPECIFICATIONS

Part tightened	N·m	kgf·cm	ft·lbf
Front seat mounting bolts	39	400	29