







REAR DIFFERENTIAL

PREPARATION



SST (SPECIAL SERVICE TOOLS)

	09214-76011 Crankshaft Pulley Replacer	Oil seal installation
	09308-00010 Oil Seal Puller	Drive pinon front bearing outer race removal
	09308-10010 Oil Seal Puller	
	09315-00021 Clutch Release Bearing Remover & Replacer	Side bearing installation
	09316-60010 Transmission & Transfer Bearing Replacer	Drive pinon front bearing outer race installation
	(09316-00010) Replacer Pipe	
	(09316-00020) Replacer "A"	
	09330-00021 Companion Flange Holding Tool	
	09504-00011 Differential Side Bearing Adjusting Nut Wrench	
	09504-22011 Differential Side Bearing Replacer	
	09506-35010 Differential Drive Pinion Rear Bearing Replacer	
	09550-10012 Replacer Set "B"	Side bearing

	(09252-10010) No. 1 Replacer Handle—	
	(09557-10010) Differential Drive Pinion Front Bearing Replacer	
	(09558-10010) Rear Axle Shaft Oil Seal Replacer—	
	09550-60010 Differential Side Bearing Replacer	
	09556-22010 Drive Pinion Front Bearing Remover	
	09608-30012 Front Hub & Drive Pinion Bearing Tool Set	Side bearing removal
	(09608-04060) Front Hub Outer Bearing Cup Replacer—	
	09608-35014 Axle Hub & Drive Pinion Bearing Tool Set	Drive pinion front and rear bearing outer race installation
	(09608-06020) Handle—	
	(09608-06110) Front Hub Inner & Drive Pinion Front Bearing Cup Replacer—	
	(09608-06180) Drive Pinion Rear Bearing Cup Replacer	
	09726-40010 Lower Control Shaft Bearing Replacer	Dust deflector installation
	09950-00020 Bearing Remover	Drive pinion rear bearing removal
	09950-30010 Puller A Set	Companion frange

	09950-40010 Puller B Set	Side bearing removal
---	---------------------------------	-----------------------------

RECOMMENDED TOOLS

	09025-00010 Torque Wrench (30 kgf-cm) .	
	09044-00020 Torx Socket E10 .	

EQUIPMENT

Dial indicator or dial indicator with magnetic base	
Micrometer	
Torque wrench	

LUBRICANT

Item	Capacity	Classification
Differential oil	3.25 liters (3.4 US qts, 2.9 Imp.qts)	Hypoid gear oil API GL-5 [Above – 18°C (0°F)] SAE 90 [Below – 18°C (0°F)] SAE 80W or 80W-90

SSM (SPECIAL SERVICE MATERIALS)

08826-00090	Seal Packing 1281, THREE BOND 1281 or equivalent (FIG)	Cover X Differential carrier Actuator X Differential carrier
08833-00070	Adhesive 1324, THREE BOND 1324 or equivalent	Shift fork shaft set bolt Pinion shaft pin