

## TORQUE SPECIFICATION

| Part tightened                                        | N·m | kgf·cm | ft·lbf     |
|-------------------------------------------------------|-----|--------|------------|
| Crossmember x Frame                                   | 61  | 620    | 45         |
| Crossmember x Engine rear mounting                    | 74  | 750    | 54         |
| Transfer x Transmission                               | 69  | 700    | 51         |
| Filler and drain plug                                 | 37  | 380    | 27         |
| Oil pump plate and separator x Rear extension housing | 4.9 | 50     | 43 in.·lbf |
| Oil pump cover x Rear extension housing               | 4.9 | 50     | 43 in.·lbf |
| Lever lock pin                                        | 12  | 120    | 9          |
| Oil strainer x Rear case                              | 4.9 | 50     | 43 in.·lbf |
| Oil receiver x Front case                             | 12  | 120    | 9          |
| Case cover x Rear case                                | 37  | 380    | 27         |
| Rear extension housing x Rear case                    | 37  | 380    | 27         |
| Front extension housing x Front case                  | 37  | 380    | 27         |
| Center Diff Lock Indicator switch                     | 37  | 380    | 14         |
| L4 position switch                                    | 37  | 380    | 27         |
| Neutral position switch                               | 37  | 380    | 27         |
| Screw plug x Front case                               | 19  | 190    | 14         |
| Screw plug x Rear extension housing                   | 29  | 300    | 22         |
| Motor actuator x Front case                           | 18  | 185    | 13         |
| Differential front case x Differential rear case      | 98  | 1000   | 72         |
| (Temporarily tighten)                                 | 88  | 900    | 65         |
| Front case x Rear case                                | 37  | 380    | 27         |
| Rear case x Retainer                                  | 39  | 400    | 28         |
| Dynamic damper x Rear extension housing               | 37  | 380    | 27         |