MAJOR TECHNICAL SPECIFICATIONS

Item / Area				Europe			
Body Type				3-Door Wagon			
Vehicle Grade				-			
Model Code				GRJ125L-GJAEKW	KDJ125R-GJFEYW	KDJ125L-GJFEYW	KDJ125R-GJAEYW
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4365 (171.9), 4405 (173.4)*1	4365 (171.9), 4405 (173.4)*1	4365 (171.9), 4405 (173.4)*1	4365 (171.9), 4405 (173.4)*1
		Width	mm (in.)	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4
		Height	mm (in.)	1850 (72.8)*7, 1865 (73.4)*5, *7	1850 (72.8)*7, 1865 (73.4)*5, *7	1850 (72.8)*7, 1865 (73.4)*5, *7	1850 (72.8)*7, 1865 (73.4)*5, *7
	Wheel Base		mm (in.)	2455 (96.7), 2449 (96.4)*8	2455 (96.7), 2449 (96.4)*8	2455 (96.7), 2449 (96.4)*8	2455 (96.7), 2449 (96.4)*8
	Tread	Front	mm (in.)	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11
		Rear	mm (in.)	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11
	Room	Length	mm (in.)	1805 (71.1)	1805 (71.1)	1805 (71.1)	1805 (71.1)
		Width	mm (in.)	1530 (60.2)	1530 (60.2)	1530 (60.2)	1530 (60.2)
		Height	mm (in.)	1260 (49.6)	1260 (49.6)	1260 (49.6)	1260 (49.6)
	Cargo Space	Length	mm (in.)	-	-	-	-
		Width	mm (in.)	-	-	-	-
		Height	mm (in.)	-	-	-	-
	Overhang	Front	mm (in.)	855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)
		Rear	mm (in.)	1055 (41.5), 1095 (43.1)*4	1055 (41.5), 1095 (43.1)*4	1055 (41.5), 1095 (43.1)*4	1055 (41.5), 1095 (43.1)*4
	Min. Running Ground Clearance		mm (in.)	207 (8.1)	207 (8.1)	207 (8.1)	207 (8.1)
	Angle of Approach		degrees	31°, 32° *4	31°, 32° *4	31°, 32° *4	31°, 32° *4
	Angle of Departure		degrees	29°, 30° *4	29°, 30° *4	29°, 30° *4	29°, 30° *4
	Curb Weight	Front	kg (lb)	890 - 970 (1962 - 2138)*15	970 - 1080 (2138 - 2381)*15	970 - 1080 (2138 - 2381)*15	980 - 1090 (2161 - 2403)*15
		Rear	kg (lb)	880 - 940 (1940 - 2072)*15	880 - 940 (1940 - 2072)*15	880 - 940 (1940 - 2072)*15	880 - 940 (1940 - 2072)*15
		Total	kg (lb)	1770 - 1910 (3902 - 4211)*15	1850 - 2020 (4079 - 4453)*15	1850 - 2020 (4079 - 4453)*15	1860 - 2030 (4101 - 4475)*15
	Gross Vehicle Weight	Front	kg (lb)	990 (2183)*15	1120 (2469)*15	1120 (2469)*15	1130 (2491)*15
		Rear	kg (lb)	1610 (3549)*15	1480 (3263)*15	1480 (3263)*15	1470 (3241)*15
		Total	kg (lb)	2600 (5732)*15	2600 (5732)*15	2600 (5732)*15	2600 (5732)*15
	Fuel Tank Capacity		ℓ (Imp. gal.)	87 (19.1)	87 (19.1)	87 (19.1)	87 (19.1)
	Luggage Compartment Capacity		m^3 (cu.ft.)	-	-	-	-
Performance	Max. Speed		km/h (mph)	180 (111.9)	175 (108.7)	175 (108.7)	175 (108.7)
	Max. Cruising Speed		km/h (mph)	180 (111.9)	175 (108.7)	175 (108.7)	175 (108.7)
	Max. Permissible Speed	1st Gear	km/h (mph)	23 (14)*13, 58 (36)*14	15 (9)*13, 37 (23)*14	15 (9)*13, 37 (23)*14	17 (11)*13, 44 (27)*14
		2nd Gear	km/h (mph)	39 (24)*13, 100 (62)*14	28 (17)*13, 71 (44)*14	28 (17)*13, 71 (44)*14	30 (19)*13, 76 (47)*14
		3rd Gear	km/h (mph)	57 (35)*13, 146 (91)*14	41 (25)*13, 105 (65)*14	41 (25)*13, 105 (65)*14	43 (27)*13, 112 (70)*14
		4th Gear	km/h (mph)	80 (50)*13, 180 (112)*14	51 (32)*13, 130 (81)*14	51 (32)*13, 130 (81)*14	61 (38)*13, 156 (97)*14
	Min. Turning Radius	Tire	m (ft.)	5.2 (17.1)	5.2 (17.1)	5.2 (17.1)	5.2 (17.1)
		Body	m (ft.)	5.6 (18.4)	5.6 (18.4)	5.6 (18.4)	5.6 (18.4)
Engine	Engine Type			1GR-FE	1KD-FTV	1KD-FTV	1KD - FTV
	Valve Mechanism			24 - Valve, DOHC	16 - Valve, DOHC	16 - Valve, DOHC	16 - Valve, DOHC
	Bore × Stroke		mm (in.)	94.0 × 95.0 (3.70 × 3.74)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
	Displacement		cm^3 (cu.in.)	3956 (241.4)	2982 (182.0)	2982 (182.0)	2982 (182.0)
	Compression Ratio			10.0:1	17.9:1	17.9:1	17.9:1
	Fuel System			EFI	Common-Rail Type	Common-Rail Type	Common-Rail Type
	Research Octane No. or Cetane No. (Diesel)			95 or higher	48 or higher	48 or higher	48 or higher
	Max. Output		kW/rpm	183/5200 (EEC)	122/3400 (EEC)	122/3400 (EEC)	122/3400 (EEC)
	Max. Torque		N·m/rpm	380/3800 (EEC)	410/1800 - 2600 (EEC)	410/1800 - 2600 (EEC)	410/1800 - 2600 (EEC)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55	12 - 64, 12 - 55 × 2*19	12 - 64, 12 - 64 × 2*19	12 - 64, 12 - 55 × 2*19
	Alternator Output		Watts	960	960, 1200*19	960, 1200*19, 1560 *19	960
	Starter Output		kW	1.6, 2.0*19	2.2, 2.7*19	2.2, 2.7*19	2.7, 3.0*19
Chassis	Clutch Type			-	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	-
	Transmission Type			A750F	RA61F	RA61F	A750F
	Transmission Gear Ratio	In First		3.520	4.171	4.171	3.520
		In Second		2.042	2.190	2.190	2.042
		In Third		1.400	1.488	1.488	1.400
		In Fourth		1.000	1.193	1.193	1.000
		In Fifth		0.716	1.000	1.000	0.716
		In Sixth		-	0.799	0.799	-
		In Reverse		3.224	3.607	3.607	3.224
	Transfer Gear Ratio H4/L4			1.000/2.566	1.000/2.566	1.000/2.566	1.000/2.566
	Differential Gear Ratio (Front/Rear)			3.727/3.727	3.909/3.909	3.909/3.909	3.909/3.909
	Differential Gear Size (Front/Rear)		in.	8.0/8.0	8.0/8.0	8.0/8.0	8.0/8.0
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Drum , 210	Drum , 210	Drum , 210	Drum , 210
	Brake Booster Type and Size		in.	Single 10", Hydraulic*20	Single 10", Hydraulic*20	Single 10", Hydraulic*20	Single 10", Hydraulic*20
	Proportioning Valve Type			-	-	-	-
	Suspension Type	Front		Double wishbone	Double wishbone	Double wishbone	Double wishbone
		Rear		4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
	Steering Gear Ratio (Overall)			15.6	15.6	15.6	15.6
	Power Steering Type			Integral Type	Integral Type	Integral Type	Integral Type

*1: With Back door - mounted Spare Tire
*2: With Underfloor - mounted Spare Tire
*4: With Over Fender
*5: With 265/65 R17 Tires +15 mm (0.6 in.)
*6: With Air Suspention
*7: With Roof Rail +40 mm (1.6 in.)
*8:With Coil Suspention and Gross Vehicle Weight
*9: With Air suspention on Rear and Gross Vehicle Weight
*11: With 265/65 R17 Tires
*13: Transfer in Low
*14: Transfer in High
*15: 5 Seater
*16: 8 Seater
*19: Option
*20: With VSC

	Europe					
	3-Door Wagon	5-Door Wagon				
		-				
	KDJ125L-GJAEYW	GRJ120R-GKAEKW	GRJ120L-GKAEKW	KDJ120R-GKFEYW	KDJ120L-GKFEYW	KDJ120R-GKAEYW
5	4365 (171.9), 4405 (173.4)*1	4810 (189.4), 4850 (190.9)*1, 4715 (185.6)*2	4810 (189.4), 4850 (190.9)*1, 4715 (185.6)*2	4810 (189.4), 4850 (190.9)*1, 4715 (185.6)*2	4810 (189.4), 4850 (190.9)*1, 4715 (185.6)*2	4810 (189.4), 4850 (190.9)*1, 4715 (185.6)*2
	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4
	1850 (72.8)*7, 1865 (73.4)*5,*7	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7
	2455 (96.7), 2449 (96.4)*8	2790 (109.8), 2785 (109.6)*8, 2790 (109.8)*9	2790 (109.8), 2785 (109.6)*8, 2790 (109.8)*9	2790 (109.8), 2785 (109.6)*8, 2790 (109.8)*9	2790 (109.8), 2785 (109.6)*8, 2790 (109.8)*9	2790 (109.8), 2785 (109.6)*8, 2790 (109.8)*9
	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11
10	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11
	1805 (71.1)	2520 (99.2)	2520 (99.2)	2520 (99.2)	2520 (99.2)	2520 (99.2)
	1530 (60.2)	1530 (60.2)	1530 (60.2)	1530 (60.2)	1530 (60.2)	1530 (60.2)
	1260 (49.6)	1260 (49.6)	1260 (49.6)	1260 (49.6)	1260 (49.6)	1260 (49.6)
	-	-	-	-	-	-
15	-	-	-	-	-	-
	-	-	-	-	-	-
	855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)
	1055 (41.5), 1095 (43.1)*4	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2
	207 (8.1)	207 (8.1)	207 (8.1)	207 (8.1)	207 (8.1)	207 (8.1)
20	31°, 32° *4	31°, 32° *4	31°, 32° *4	31°, 32° *4	31°, 32° *4	31°, 32° *4
	29°, 30° *4	26°, 27°*4, 25°*6, 26°*4, *6	26°, 27°*4, 25°*6, 26°*4, *6	26°, 27°*4, 25°*6, 26°*4, *6	26°, 27°*4, 25°*6, 26°*4, *6	26°, 27°*4, 25°*6, 26°*4, *6
	980 - 1090 (2161 - 2403)*15	980 - 1070 (2161 - 2359)*15, *16	980 - 1070 (2161 - 2359)*15, *16	1060 - 1170 (2337 - 2579)*15, *16	1060 - 1170 (2337 - 2579)*15, *16	1070 - 1180 (2359 - 2601)*15, *16
	880 - 940 (1940 - 2072)*15	890 - 960 (1962 - 2116)*15 930 - 1010 (2050 - 2227)*16	890 - 960 (1962 - 2116)*15 930 - 1010 (2050 - 2227)*16	890 - 960 (1962 - 2116)*15 930 - 1010 (2050 - 2227)*16	890 - 960 (1962 - 2116)*15 930 - 1010 (2050 - 2227)*16	890 - 960 (1962 - 2116)*15 930 - 1010 (2050 - 2227)*16
	1860 - 2030 (4101 - 4475)*15	1870 - 2030 (4123 - 4475)*15 1910 - 2080 (4211 - 4586)*16	1870 - 2030 (4123 - 4475)*15 1910 - 2080 (4211 - 4586)*16	1950 - 2130 (4299 - 4696)*15 1990 - 2180 (4387 - 4806)*16	1950 - 2130 (4299 - 4696)*15 1990 - 2180 (4387 - 4806)*16	1960 - 2140 (4321 - 4718)*15 2000 - 2190 (4409 - 4828)*16
25	1130 (2491)*15	1130 (2491)*15, 1110 (2447)*16	1130 (2491)*15, 1110 (2447)*16	1240 (2734)*15, 1235 (2723)*16	1240 (2734)*15, 1235 (2723)*16	1250 (2756)*15, 1245 (2745)*16
	1470 (3241)*15	1720 (3792)*15, 1740 (3836)*16	1720 (3792)*15, 1740 (3836)*16	1610 (3549)*15, 1615 (3560)*16	1610 (3549)*15, 1615 (3560)*16	1600 (3527)*15, 1605 (3538)*16
	2600 (5732)*15	2850 (6283)*15, *16	2850 (6283)*15, *16	2850 (6283)*15, *16	2850 (6283)*15, *16	2850 (6283)*15, *16
	87 (19.1)	87 (19.1)	87 (19.1)	87 (19.1)	87 (19.1)	87 (19.1)
	-	-	-	-	-	-
30	175 (108.7)	180 (111.9)	180 (111.9)	175 (108.7)	175 (108.7)	175 (108.7)
	175 (108.7)	180 (111.9)	180 (111.9)	175 (108.7)	175 (108.7)	175 (108.7)
	17 (11)*13, 44 (27)*14	23 (14)*13, 58 (36)*14	23 (14)*13, 58 (36)*14	15 (9)*13, 37 (23)*14	15 (9)*13, 37 (23)*14	17 (11)*13, 44 (27)*14
	30 (19)*13, 76 (47)*14	39 (24)*13, 100 (62)*14	39 (24)*13, 100 (62)*14	28 (17)*13, 71 (44)*14	28 (17)*13, 71 (44)*14	30 (19)*13, 76 (47)*14
	43 (27)*13, 112 (70)*14	57 (35)*13, 146 (91)*14	57 (35)*13, 146 (91)*14	41 (25)*13, 105 (65)*14	41 (25)*13, 105 (65)*14	43 (27)*13, 112 (70)*14
35	61 (38)*13, 156 (97)*14	80 (50)*13, 180 (112)*14	80 (50)*13, 180 (112)*14	51 (32)*13, 130 (81)*14	51 (32)*13, 130 (81)*14	61 (38)*13, 156 (97)*14
	5.2 (17.1)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
	5.6 (18.4)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)
	1KD - FTV	1GR-FE	1GR-FE	1KD-FTV	1KD-FTV	1KD-FTV
	16 - Valve, DOHC	24 - Valve, DOHC	24 - Valve, DOHC	16 - Valve, DOHC	16 - Valve, DOHC	16 - Valve, DOHC
40	96.0 × 103.0 (3.78 × 4.06)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
	2982 (182.0)	3956 (241.4)	3956 (241.4)	2982 (182.0)	2982 (182.0)	2982 (182.0)
	17.9:1	10.0:1	10.0:1	17.9:1	17.9:1	17.9:1
	Common-Rail Type	EFI	EFI	Common-Rail Type	Common-Rail Type	Common-Rail Type
	48 or higher	95 or higher	95 or higher	48 or higher	48 or higher	48 or higher
45	122/3400 (EEC)	183/5200 (EEC)	183/5200 (EEC)	122/3400 (EEC)	122/3400 (EEC)	122/3400 (EEC)
	410/1800 - 2600 (EEC)	380/3800 (EEC)	380/3800 (EEC)	410/1800 - 2600 (EEC)	410/1800 - 2600 (EEC)	410/1800 - 2600 (EEC)
	12 - 64, 12 - 64 × 2*19	12 - 55	12 - 55	12 - 64, 12 - 55 × 2*19	12 - 64, 12 - 64 × 2*19	12 - 64, 12 - 55 × 2*19
	960	960	960	960, 1200*19	960, 1200*19, 1560 *19	960
	2.7, 3.0*19	1.6, 2.0*19	1.6, 2.0*19	2.2, 2.7*19	2.2, 2.7*19	2.7, 3.0*19
50	-	-	-	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	-
	A750F	A750F	A750F	RA61F	RA61F	A750F
	3.520	3.520	3.520	4.171	4.171	3.520
	2.042	2.042	2.042	2.190	2.190	2.042
	1.400	1.400	1.400	1.488	1.488	1.400
55	1.000	1.000	1.000	1.193	1.193	1.000
	0.716	0.716	0.716	1.000	1.000	0.716
	-	-	-	0.799	0.799	-
	3.224	3.224	3.224	3.607	3.607	3.224
	1.000/2.566	1.000/2.566	1.000/2.566	1.000/2.566	1.000/2.566	1.000/2.566
60	3.909/3.909	3.727/3.727	3.727/3.727	3.909/3.909	3.909/3.909	3.909/3.909
	8.0/8.0	8.0/8.0	8.0/8.0	8.0/8.0	8.0/8.0	8.0/8.0
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Drum , 210	Drum , 210	Drum , 210	Drum , 210	Drum , 210	Drum , 210
65	Single 10", Hydraulic*20	Single 10", Hydraulic*20	Single 10", Hydraulic*20	Single 10", Hydraulic*20	Single 10", Hydraulic*20	Single 10", Hydraulic*20
	-	-	-	-	-	-
	Double wishbone	Double wishbone	Double wishbone	Double wishbone	Double wishbone	Double wishbone
	4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod
	Standard	Standard	Standard	Standard	Standard	Standard
70	Standard	Standard	Standard	Standard	Standard	Standard
	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
	15.6	15.6	15.6	15.6	15.6	15.6
	Integral Type	Integral Type	Integral Type	Integral Type	Integral Type	Integral Type

Item / Area				Europe	Australia		
Body Type				5-Door Wagon			
Vehicle Grade				-	VX	GX	
Model Code				KDJ120L-GKAEYW	GRJ120R-GKAGKQ	GRJ120R-GKFEKQ	GRJ120R-GKAEKQ
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4810 (189.4), 4850 (190.9)*1, 4715 (185.6)*2	4810 (189.4), 4850 (190.9)*1, 4715 (185.6)*2	4810 (189.4), 4850 (190.9)*1, 4715 (185.6)*2	4810 (189.4), 4850 (190.9)*1, 4715 (185.6)*2
		Width	mm (in.)	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4
		Height	mm (in.)	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7
	Wheel Base		mm (in.)	2790 (109.8), 2785 (109.6)*8, 2790 (109.8)*9	2790 (109.8)	2790 (109.8)	2790 (109.8)
	Tread	Front	mm (in.)	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11
		Rear	mm (in.)	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11
	Room	Length	mm (in.)	2520 (99.2)	2520 (99.2)	2520 (99.2)	2520 (99.2)
		Width	mm (in.)	1530 (60.2)	1530 (60.2)	1530 (60.2)	1530 (60.2)
		Height	mm (in.)	1260 (49.6)	1260 (49.6)	1260 (49.6)	1260 (49.6)
	Cargo Space	Length	mm (in.)	-	-	-	-
		Width	mm (in.)	-	-	-	-
		Height	mm (in.)	-	-	-	-
	Overhang	Front	mm (in.)	855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)
		Rear	mm (in.)	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2
	Min. Running Ground Clearance		mm (in.)	207 (8.1)	207 (8.1)	207 (8.1)	207 (8.1)
	Angle of Approach		degrees	31°, 32° *4	31°, 32° *4	31°, 32° *4	31°, 32° *4
	Angle of Departure		degrees	26°, 27°*4, 25°*6, 26°*4, *6	26°, 27°*4, 25°*6, 26°*4, *6	26°, 27°*4, 25°*6, 26°*4, *6	26°, 27°*4, 25°*6, 26°*4, *6
	Curb Weight	Front	kg (lb)	1070 - 1180 (2359 - 2601)*15, *16	1000 - 1070 (2205 - 2359)*15,*16	970 - 1060 (2138 - 2337)*15,*16	980 - 1070 (2161 - 2359)*15,*16
		Rear	kg (lb)	890 - 960 (1962 - 2116)*15 930 - 1010 (2050 - 2227)*16	900 - 1000 (1984 - 2205)*15 940 - 1050 (2072 - 2315)*16	890 - 990 (1962 - 2183)*15 930 - 1040 (2050 - 2293)*16	890 - 990 (1962 - 2183)*15 930 - 1040 (2050 - 2293)*16
		Total	kg (lb)	1960 - 2140 (4321 - 4718)*15 2000 - 2190 (4409 - 4828)*16	1900 - 2070 (4189 - 4564)*15 1940 - 2120 (4277 - 4674)*16	1860 - 2050 (4100 - 4520)*15 1900 - 2100 (4188 - 4630)*16	1870 - 2060 (4123 - 4542)*15 1910 - 2110 (4211 - 4652)*16
	Gross Vehicle Weight	Front	kg (lb)	1250 (2756)*15, 1245 (2745)*16	1130 (2491)*15, 1125 (2480)*16	1115 (2458)*15, 1110 (2447)*16	1130 (2491)*15, 1120 (2469)*16
		Rear	kg (lb)	1600 (3527)*15, 1605 (3538)*16	1720 (3792)*15, 1725 (3803)*16	1735 (3825)*15, 1740 (3836)*16	1720(3792)*15, 1730 (3814)*16
		Total	kg (lb)	2850 (6283)*15, *16	2850 (6283)*15, *16	2850 (6283)*15, *16	2850 (6283)*15, *16
	Fuel Tank Capacity		ℓ (Imp. gal.)	87 (19.1)	87 (19.1), 180 (39.6)*12	87 (19.1), 180 (39.6)*12	87 (19.1), 180 (39.6)*12
	Luggage Compartment Capacity		m^3 (cu.ft.)	-	-	-	-
Performance	Max. Speed		km/h (mph)	175 (108.7)	180 (111.9)	180 (111.9)	180 (111.9)
	Max. Cruising Speed		km/h (mph)	175 (108.7)	180 (111.9)	180 (111.9)	180 (111.9)
	Max. Permissible Speed	1st Gear	km/h (mph)	17 (11)*13, 44 (27)*14	23 (14)*13, 58 (36)*14	19 (12)*13, 49 (30)*14	23 (14)*13, 58 (36)*14
		2nd Gear	km/h (mph)	30 (19)*13, 76 (47)*14	39 (24)*13, 100 (62)*14	36 (22)*13, 93 (58)*14	39 (24)*13, 100 (62)*14
		3rd Gear	km/h (mph)	43 (27)*13, 112 (70)*14	57 (35)*13, 146 (91)*14	54 (34)*13, 138 (86)*14	57 (35)*13, 146 (91)*14
		4th Gear	km/h (mph)	61 (38)*13, 156 (97)*14	80 (50)*13, 180 (112)*14	67 (42)*13, 172 (107)*14	80 (50)*13, 180 (112)*14
	Min. Turning Radius	Tire	m (ft.)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
		Body	m (ft.)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)
Engine	Engine Type			1KD-FTV	1GR-FE	1GR-FE	1GR-FE
	Valve Mechanism			16 - Valve, DOHC	24 - Valve, DOHC	24 - Valve, DOHC	24 - Valve, DOHC
	Bore × Stroke		mm (in.)	96.0 × 103.0 (3.78 × 4.06)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)
	Displacement		cm^3 (cu.in.)	2982 (182.0)	3956 (241.4)	3956 (241.4)	3956 (241.4)
	Compression Ratio			17.9:1	10.0:1	10.0:1	10.0:1
	Fuel System			Common-Rail Type	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			48 or higher	95 or higher	95 or higher	95 or higher
	Max. Output		kW/rpm	122/3400 (EEC)	179/5200 (SAE-NET)	179/5200 (SAE-NET)	179/5200 (SAE-NET)
	Max. Torque		N·m/rpm	410/1800 - 2600 (EEC)	376/3800 (SAE-NET)	376/3800 (SAE-NET)	376/3800 (SAE-NET)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 64, 12 - 64 × 2*19	12 - 55	12 - 55	12 - 55
	Alternator Output		Watts	960	960	960	960
	Starter Output		kW	2.7, 3.0*19	1.6	1.6	1.6
Chassis	Clutch Type			-	-	Dry, Single Plate, Diaphragm	-
	Transmission Type			A750F	A750F	RA61F	A750F
	Transmission Gear Ratio	In First		3.520	3.520	4.171	3.520
		In Second		2.042	2.042	2.190	2.042
		In Third		1.400	1.400	1.488	1.400
		In Fourth		1.000	1.000	1.193	1.000
		In Fifth		0.716	0.716	1.000	0.716
		In Sixth		-	-	0.799	-
		In Reverse		3.224	3.224	3.607	3.224
	Transfer Gear Ratio H4/L4			1.000/2.566	1.000/2.566	1.000/2.566	1.000/2.566
	Differential Gear Ratio (Front/Rear)			3.909/3.909	3.727/3.727	3.727/3.727	3.727/3.727
	Differential Gear Size (Front/Rear)		in.	8.0/8.0	8.0/8.0	8.0/8.0	8.0/8.0
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Drum , 210	Drum , 210	Drum , 210	Drum , 210
	Brake Booster Type and Size		in.	Single 10", Hydraulic*20	Single 10", Hydraulic*20	Single 10"	Single 10", Hydraulic*20
	Proportioning Valve Type			-	LSP & BV, -*21	LSP & BV, -*21	LSP & BV, -*21
	Suspension Type	Front		Double wishbone	Double wishbone	Double wishbone	Double wishbone
		Rear		4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
	Steering Gear Ratio (Overall)			15.6	15.6	15.6	15.6
	Power Steering Type			Integral Type	Integral Type	Integral Type	Integral Type

*1: With Back door - mounted Spare Tire
*2: With Underfloor - mounted Spare Tire
*3: With Grille Guard +75 mm (3.0 in.)
*4: With Over Fender
*5: With 265/65 R17 Tires +15 mm (0.6 in.)
*6: With Air Suspention
*7: With Roof Rail +40 mm (1.6 in.)
*8: With Coil Suspention and Gross Vehicle Weight
*9: With Air suspention on Rear and Gross Vehicle Weight
*10: With Grille Guard
*11: With 265/65 R17 Tires
*12: With Sub Fuel Tank System
*13: Transfer in Low
*14: Transfer in High
*15: 5 Seater

Australia		G.C.C. Countries			
5-Door Wagon		3-Door Wagon		5-Door Wagon	
GX		VX		GX	
KZJ120R-GKMETQ	KZJ120R-GKPETQ	TRJ125L-GJPEKV	GRJ125L-GJAGKV	TRJ120L-GKMEKV	TRJ120L-GKPEKV
4810 (189.4), 4850 (190.9)*1, 4715 (185.6)*2	4810 (189.4), 4850 (190.9)*1, 4715 (185.6)*2	4365 (171.9), 4405 (173.4)*1, *3	4365 (171.9), 4405 (173.4)*1, *3	4810 (189.4)*3, 4850 (190.9)*1, *3, 4715 (185.6)*2, *3	4810 (189.4)*3, 4850 (190.9)*1, *3, 4715 (185.6)*2, *3
1790(70.5), 1875 (73.8)*4	1790(70.5), 1875 (73.8)*4	1790(70.5), 1875 (73.8)*4	1790(70.5), 1875 (73.8)*4	1790(70.5), 1875 (73.8)*4	1790(70.5), 1875 (73.8)*4
1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7	1850 (72.8) *5, *7	1850 (72.8) *5, *7	1850 (72.8) *5	1850 (72.8) *5
2790 (109.8)	2790 (109.8)	2455 (96.7)	2455 (96.7)	2790 (109.8)	2790 (109.8)
1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11
1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11
2520 (99.2)	2520 (99.2)	1805 (71.1)	1805 (71.1)	2520 (99.2)	2520 (99.2)
1530 (60.2)	1530 (60.2)	1530 (60.2)	1530 (60.2)	1530 (60.2)	1530 (60.2)
1260 (49.6)	1260 (49.6)	1260 (49.6)	1260 (49.6)	1260 (49.6)	1260 (49.6)
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-
855 (33.7)	855 (33.7)	855 (33.7)*3	855 (33.7)*3	855 (33.7)*3	855 (33.7)*3
1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1055 (41.5), 1095 (43.1)*4	1055 (41.5), 1095 (43.1)*4	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2
207 (8.1)	207 (8.1)	207 (8.1)	207 (8.1)	207 (8.1)	207 (8.1)
31°, 32° *4	31°, 32° *4	31°, 32° *4, 26° *10, 27° *4, *10	31°, 32° *4, 26° *10, 27° *4, *10	31°, 32° *4, 26° *10, 27° *4, *10	31°, 32° *4, 26° *10, 27° *4, *10
26°, 27° *4, 25° *6, 26° *4, *6	26°, 27° *4, 25° *6, 26° *4, *6	29°, 30° *4	29°, 30° *4	26°, 27° *4	26°, 27° *4
1040 - 1130 (2293 - 2491)*15, *16	1050 - 1140 (2315 - 2513)*15, *16	890 - 950 (1962 - 2094)*15	910 - 980 (2006 - 2161)*15	970 - 1040 (2138 - 2293)*15 970 - 1020 (2138 - 2249)*16 970 - 1030 (2138 - 2271)*18	980 - 1040 (2161 - 2293)*15 980 - 1020 (2161 - 2249)*16 980 - 1030 (2161 - 2271)*17
890 - 990 (1962 - 2183)*15 930 - 1040 (2050 - 2293)*16	890 - 990 (1962 - 2183)*15 930 - 1030 (2050 - 2271)*16	890 - 970 (1962 - 2138)*15	890 - 970 (1962 - 2138)*15	890 - 960 (1962 - 2116)*15 930 - 980 (2050 - 2161)*16 910 - 970 (2006 - 2138)*18	890 - 960 (1962 - 2116)*15 930 - 980 (2050 - 2161)*16 910 - 970 (2006 - 2138)*17
1930 - 2120 (4255 - 4674)*15 1970 - 2170 (4343 - 4784)*16	1940 - 2130 (4277 - 4696)*15 1980 - 2170 (4365 - 4784)*16	1780 - 1920 (3924 - 4233)*15	1800 - 1950 (3968 - 4299)*15	1860 - 2000 (4101 - 4409)*15 1900 - 2000 (4189 - 4409)*16 1880 - 2000 (4145 - 4409)*18	1870 - 2000 (4123 - 4409)*15 1910 - 2000 (4211 - 4409)*16 1890 - 2000 (4167 - 4409)*17
1190 (2623)*15, 1185 (2612)*16	1200 (2646)*15, 1195 (2635)*16	980 (2161)*15	1015 (2238)*15	1105 (2436)*15 1055 (2326)*16 1135 (2502)*18	1105 (2436)*15 1055 (2326)*16 1090 (2403)*17
1710 (3770)*15, 1715 (3781)*16	1700 (3748)*15, 1705 (3759)*16	1620 (3571)*15	1585 (3494)*15	1695 (3737)*15 1745 (3847)*16 1665 (3671)*18	1695 (3737)*15 1745 (3847)*16 1710 (3770)*17
2900 (6393)*15, *16	2900 (6393)*15, *16	2600 (5732)*15	2600 (5732)*15	2800 (6173)*15, *16, *18	2800 (6173)*15, *16, *18
87 (19.1), 180 (39.6)*12	87 (19.1), 180 (39.6)*12	87 (19.1)	87 (19.1)	87 (19.1)	87 (19.1)
-	-	-	-	-	-
155 (96)	160 (99)	165 (102.5)	180 (111.9)	165 (102.5)	165 (102.5)
155 (96)	160 (99)	165 (102.5)	180 (111.9)	165 (102.5)	165 (102.5)
16 (9)*13, 40 (24)*14	21 (13)*13, 55 (34)*14	24 (15)*13, 61 (38)*14	23 (14)*13, 58 (36)*14	17 (11)*13, 45 (28)*14	24 (15)*13, 61 (38)*14
29 (18)*13, 75 (46)*14	39 (24)*13, 101 (62)*14	43 (27)*13, 111 (69)*14	39 (24)*13, 100 (62)*14	32 (20)*13, 83 (52)*14	43 (27)*13, 111 (69)*14
42 (26)*13, 107 (66)*14	-	66 (41)*13, 165 (103)*14	57 (35)*13, 146 (91)*14	46 (29)*13, 119 (74)*14	66 (41)*13, 165 (103)*14
-	-	-	80 (50)*13, 180 (112)*14	66 (41)*13, 165 (103)*14	-
5.7 (18.7)	5.7 (18.7)	5.2 (17.1)	5.2 (17.1)	5.7 (18.7)	5.7 (18.7)
6.2 (20.3)	6.2 (20.3)	5.6 (18.4)	5.6 (18.4)	6.2 (20.3)	6.2 (20.3)
1KZ-TE	1KZ-TE	2TR - FE	1GR-FE	2TR - FE	2TR - FE
8 - Valve, OHC	8 - Valve, OHC	16 - Valve, DOHC	24 - Valve, DOHC	16 - Valve, DOHC	16 - Valve, DOHC
96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	95.0 × 95.0 (3.74 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
2982 (181.9)	2982 (181.9)	2694 (164.3)	3956 (241.4)	2694 (164.3)	2694 (164.3)
21.0:1	21.0:1	9.6:1	10.0:1	9.6:1	9.6:1
Distributor Type	Distributor Type	EFI	EFI	EFI	EFI
50 or higher	50 or higher	91 or higher	95 or higher	91 or higher	91 or higher
96/3600 (SAE - NET)	96/3600 (SAE - NET)	120/5200 (SAE - NET)	179/5200 (SAE-NET)	120/5200 (SAE - NET)	120/5200 (SAE - NET)
343/2000 (SAE - NET)	343/2000 (SAE - NET)	246/3800 (SAE - NET)	376/3800 (SAE-NET)	246/3800 (SAE - NET)	246/3800 (SAE - NET)
12 - 64	12 - 64	12 - 48	12 - 55	12 - 48, 12 - 55*19	12 - 48, 12 - 55*19
960	960	960	960	960	960
2.2	2.7	1.6	1.6	1.6	1.6
Dry, Single Plate, Diaphragm	-	-	-	Dry, Single Plate, Diaphragm	-
R150F	A343F	A343F	A750F	R150F	A343F
3.830	2.804	2.804	3.520	3.830	2.804
2.062	1.531	1.531	2.042	2.062	1.531
1.436	1.000	1.000	1.400	1.436	1.000
1.000	0.753	0.753	1.000	1.000	0.753
0.838	-	-	0.716	0.838	-
-	-	-	-	-	-
4.220	2.393	2.393	3.224	4.220	2.393
1.000/2.566	1.000/2.566	1.000/2.566	1.000/2.566	1.000/2.566	1.000/2.566
4.100/4.100	4.100/4.100	4.555/4.555	3.727/3.727	4.555/4.555	4.555/4.555
8.0/8.0	8.0/8.0	8.0/8.0	8.0/8.0	8.0/8.0	8.0/8.0
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Drum , 210	Drum , 210	Drum , 210	Drum , 210	Drum , 210	Drum , 210
Single 10", Hydraulic*20	Single 10", Hydraulic*20	Single 10"	Single 10", Hydraulic*20	Single 10"	Single 10"
LSP & BV, -*21	LSP & BV, -*21	LSP & BV, -*21	LSP & BV, -*21	LSP & BV, -*21	LSP & BV, -*21
Double wishbone	Double wishbone	Double wishbone	Double wishbone	Double wishbone	Double wishbone
4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
15.6	15.6	15.6	15.6	15.6	15.6
Integral Type	Integral Type	Integral Type	Integral Type	Integral Type	Integral Type

*16: 8 Seater
*17: 9 Seater
*18: 10 Seater
*19: Option
*20: With VSC
*21: With ABS

Item / Area				G.C.C. Countries		General Countries	
Body Type				5-Door Wagon		3-Door Wagon	
Vehicle Grade				VX		GX	
Model Code				GRJ120L-GKFGKV	GRJ120L-GKAGKV	TRJ125L-GJMEK	LJ125L-GJMEE
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4810 (189.4)*3, 4850 (190.9)*1, *3, 4715 (185.6)*2, *3	4810 (189.4)*3, 4850 (190.9)*1, *3, 4715 (185.6)*2, *3	4365 (171.9)*3, 4405 (173.4)*1, *3	4365 (171.9)*3, 4405 (173.4)*1, *3
		Width	mm (in.)	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4
		Height	mm (in.)	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7	1850 (72.8) *5, *7	1850 (72.8)*5, *7
	Wheel Base		mm (in.)	2790 (109.8)	2790 (109.8)	2455 (96.7)	2455 (96.7)
	Tread	Front	mm (in.)	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11
		Rear	mm (in.)	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11
	Room	Length	mm (in.)	2520 (99.2)	2520 (99.2)	1805 (71.1)	1805 (71.1)
		Width	mm (in.)	1530 (60.2)	1530 (60.2)	1530 (60.2)	1530 (60.2)
		Height	mm (in.)	1260 (49.6)	1260 (49.6)	1260 (49.6)	1260 (49.6)
	Cargo Space	Length	mm (in.)	-	-	-	-
		Width	mm (in.)	-	-	-	-
		Height	mm (in.)	-	-	-	-
	Overhang	Front	mm (in.)	855 (33.7)*3	855 (33.7)*3	855 (33.7)*3	855 (33.7)*3
		Rear	mm (in.)	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1055 (41.5), 1095 (43.1)*4	1055 (41.9), 1095 (43.5)*4
	Min. Running Ground Clearance		mm (in.)	207 (8.1)	207 (8.1)	207 (8.1)	207 (8.1)
	Angle of Approach		degrees	31°, 32° *4, 26° *10, 27° *4, *10	31°, 32° *4, 26° *10, 27° *4, *10	31°, 32° *4, 26° *10, 27° *4, *10	31°, 32° *4, 26° *10, 27° *4, *10
	Angle of Departure		degrees	26°, 27° *4	26°, 27° *4	29°, 30° *4	29°, 30° *4
	Curb Weight	Front	kg (lb)	990 - 1070 (2183 - 2359)*15,*16,*17	1000 - 1080 (2205 - 2381)*15, *16, *17	860 - 950 (1896 - 2094)*15	910 - 1000 (2006 - 2205)*15
		Rear	kg (lb)	900 - 1000 (1984 - 2205)*15 940 - 1050 (2072 - 2315)*16 920 - 1020 (2028 - 2249)*17	900 - 1000 (1984 - 2205)*15 940 - 1050 (2072 - 2315)*16 920 - 1020 (2028 - 2249)*17	870 - 960 (1918 - 2116)*15	880 - 960 (1940 - 2116)*15
		Total	kg (lb)	1890 - 2070 (4167 - 4564)*15 1930 - 2120 (4255 - 4674)*16 1910 - 2090 (4211 - 4608)*17	1900 - 2080 (4189 - 4586)*15 1940 - 2130 (4277 - 4696)*16 1920 - 2100 (4233 - 4630)*17	1730 - 1910 (3814 - 4211)*15	1790 - 1960 (3946 - 4321)*15
	Gross Vehicle Weight	Front	kg (lb)	1135 (2502)*15 1125 (2480)*16 1130 (2491)*17	1145 (2524)*15 1140 (2513)*16, *17	975 (2150)*15	1035 (2282)*15
		Rear	kg (lb)	1715 (3781)*15 1725 (3803)*16 1720 (3792)*17	1705 (3759)*15 1710 (3770)*16, *17	1625 (3583)*15	1565 (3450)*15
		Total	kg (lb)	2850 (6283)*15, *16, *17	2850 (6283)*15, *16, *17	2600 (5732)*15	2600 (5732)*15
	Fuel Tank Capacity		ℓ (Imp. gal.)	87 (19.1), 180 (39.6)*12	87 (19.1), 180 (39.6)*12	87 (19.1)	87 (19.1)
	Luggage Compartment Capacity		m^3 (cu.ft.)	-	-	-	-
Performance	Max. Speed		km/h (mph)	180 (111.9)	180 (111.9)	165 (102.5)	145 (90)
	Max. Cruising Speed		km/h (mph)	180 (111.9)	180 (111.9)	165 (102.5)	-
	Max. Permissible Speed	1st Gear	km/h (mph)	19 (12)*13, 49 (30)*14	23 (14)*13, 58 (36)*14	17 (11)*13, 45 (28)*14	15 (9)*13, 38 (23)*14
		2nd Gear	km/h (mph)	36 (22)*13, 93 (58)*14	39 (24)*13, 100 (62)*14	32 (20)*13, 83 (52)*14	25 (15)*13, 63 (39)*14
		3rd Gear	km/h (mph)	54 (34)*13, 138 (86)*14	57 (35)*13, 146 (91)*14	46 (29)*13, 119 (74)*14	40 (24)*13, 102 (63)*14
		4th Gear	km/h (mph)	67 (42)*13, 172 (107)*14	80 (50)*13, 180 (112)*14	66 (41)*13, 165 (103)*14	-
	Min. Turning Radius	Tire	m (ft.)	5.7 (18.7)	5.7 (18.7)	5.2 (17.1)	5.2 (17.1)
		Body	m (ft.)	6.2 (20.3)	6.2 (20.3)	5.6 (18.4)	5.6 (18.4)
Engine	Engine Type			1GR-FE	1GR-FE	2TR - FE	5L-E
	Valve Mechanism			24 - Valve, DOHC	24 - Valve, DOHC	16 - Valve, DOHC	8 - Valve, OHC
	Bore × Stroke		mm (in.)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	99.5 × 96.0 (3.92 × 3.78)
	Displacement		cm^3 (cu.in.)	3956 (241.4)	3956 (241.4)	2694 (164.3)	2986 (182.2)
	Compression Ratio			10.0:1	10.0:1	9.6:1	22.2:1
	Fuel System			EFI	EFI	EFI	Distributor Type
	Research Octane No. or Cetane No. (Diesel)			95 or higher	95 or higher	91 or higher	50 or higher
	Max. Output		kW/rpm	179/5200 (SAE-NET)	179/5200 (SAE-NET)	120/5200 (SAE - NET)	70/4000 (SAE - NET)
	Max. Torque		N·m/rpm	376/3800 (SAE-NET)	376/3800 (SAE-NET)	246/3800 (SAE - NET)	197/2400 (SAE - NET)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55	12 - 55	12 - 48	12 - 64
	Alternator Output		Watts	960	960	960	1080
	Starter Output		kW	1.6	1.6, 2.0*19	1.6	2.2
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	-	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			RA61F	A750F	R150F	G52
	Transmission Gear Ratio	In First		4.171	3.520	3.830	3.928
		In Second		2.190	2.042	2.062	2.333
		In Third		1.488	1.400	1.436	1.451
		In Fourth		1.193	1.000	1.000	1.000
		In Fifth		1.000	0.716	0.838	0.851
		In Sixth		0.799	-	-	-
		In Reverse		3.607	3.224	4.220	4.743
	Transfer Gear Ratio H4/L4			1.000/2.566	1.000/2.566	1.000/2.566	1.000/2.566
	Differential Gear Ratio (Front/Rear)			3.727/3.727	3.727/3.727	4.555/4.555	4.555/4.555
	Differential Gear Size (Front/Rear)		in.	8.0/8.0	8.0/8.0	8.0/8.0	8.0/8.0
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Drum , 210	Drum , 210	Drum , 210	Drum , 210
	Brake Booster Type and Size		in.	Single 10"	Single 10", Hydraulic*20	Single 10"	Single 10"
	Proportioning Valve Type			LSP & BV, -*21	LSP & BV, -*21	LSP & BV, -*21	LSP & BV
	Suspension Type	Front		Double wishbone	Double wishbone	Double wishbone	Double wishbone
		Rear		4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
	Steering Gear Ratio (Overall)			15.6	15.6	15.6	15.6
	Power Steering Type			Integral Type	Integral Type	Integral Type	Integral Type

*1: With Back door - mounted Spare Tire
*2: With Underfloor - mounted Spare Tire
*3: With Grille Guard +75 mm (3.0 in.)
*4: With Over Fender
*5: With 265/65 R17 Tires +15 mm (0.6 in.)
*6: With Air Suspention
*7: With Roof Rail +40 mm (1.6 in.)
*10: With Grille Guard
*11: With 265/65 R17 Tires
*12: With Sub Fuel Tank System
*13: Transfer in Low
*14: Transfer in High
*15: 5 Seater
*16: 8 Seater
*17: 9 Seater
*18: 10 Seater
*19: Option
*20: With VSC
*21: With ABS

	General Countries					
	5-Door Wagon					
	GX			VX		GX
	TRJ120R-GKMEK	TRJ120L-GKMEK	TRJ120L-GKPEK	GRJ120L-GKFGK	GRJ120L-GKAGK	LJ120R-GKMEE
5	4810 (189.4)*3, 4850 (190.9)*1, *3, 4715 (185.6)*2, *3	4810 (189.4)*3, 4850 (190.9)*1, *3, 4715 (185.6)*2, *3	4810 (189.4), 4850 (190.9)*1	4810 (189.4)*3, 4850 (190.9)*1, *3, 4715 (185.6)*2, *3	4810 (189.4)*3, 4850 (190.9)*1, *3, 4715 (185.6)*2, *3	4810 (189.4)*3, 4850 (190.9)*1, *3, 4715 (185.6)*2, *3
	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4
	1850 (72.8) *5, *7	1850 (72.8) *5, *7	1850 (72.8)*5, *7	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7	1850 (72.8)*5, *7
	2790 (109.8)	2790 (109.8)	2790 (109.8)	2790 (109.8)	2790 (109.8)	2790 (109.8)
	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11
10	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11
	2520 (99.2)	2520 (99.2)	2520 (99.2)	2520 (99.2)	2520 (99.2)	2520 (99.2)
	1530 (60.2)	1530 (60.2)	1530 (60.2)	1530 (60.2)	1530 (60.2)	1530 (60.2)
	1260 (49.6)	1260 (49.6)	1260 (49.6)	1260 (49.6)	1260 (49.6)	1260 (49.6)
	-	-	-	-	-	-
15	-	-	-	-	-	-
	-	-	-	-	-	-
	855 (33.7)*3	855 (33.7)*3	855 (33.7)*3	855 (33.7)*3	855 (33.7)*3	855 (33.7)*3
	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2
	207 (8.1)	207 (8.1)	207 (8.1)	207 (8.1)	207 (8.1)	207 (8.1)
20	31°, 32° *4, 26° *10, 27° *4, *10	31°, 32° *4, 26° *10, 27° *4, *10	31°, 32° *4, 26° *10	31°, 32° *4, 26° *10, 27° *4, *10	31°, 32° *4, 26° *10, 27° *4, *10	31°, 32° *4, 26° *10, 27° *4, *10
	26°, 27° *4	26°, 27° *4	26°, 27° *4	26°, 27° *4	26°, 27° *4	26°, 27° *4
	950 - 1030 (2094 - 2271)*15 950 - 1010 (2094 - 2227)*16 950 - 1020 (2094 - 2249)*18	950 - 1030 (2094 - 2271)*15 950 - 1010 (2094 - 2227)*16 950 - 1020 (2094 - 2249)*18	960 - 1030 (2116 - 2271)*15 960 - 1010 (2116 - 2227)*16	970 - 1060 (2138 - 2337)*15,*16	980 - 1070 (2161 - 2359)*15,*16	1000 - 1090 (2205 - 2403)*15, *16 1000 - 1070 (2205 - 2359)*18
	880 - 970 (1940 - 2138)*15 920 - 990 (2028 - 2183)*16 900 - 980 (1984 - 2161)*18	880 - 970 (1940 - 2138)*15 920 - 990 (2028 - 2183)*16 900 - 980 (1984 - 2161)*18	890 - 970 (1962 - 2138)*15 930 - 990 (2050 - 2183)*16	900 - 1000 (1984 - 2205)*15 940 - 1050 (2072 - 2315)*16	900 - 1000 (1984 - 2205)*15 940 - 1050 (2072 - 2315)*16	890 - 990 (1962 - 2183)*15 930 - 1020 (2050 - 2249)*16 910 - 990 (2006 - 2183)*18
	1830 - 2000 (4034 - 4409)*15 1870 - 2000 (4123 - 4409)*16 1850 - 2000 (4079 - 4409)*18	1830 - 2000 (4034 - 4409)*15 1870 - 2000 (4123 - 4409)*16 1850 - 2000 (4079 - 4409)*18	1850 - 2000 (4079 - 4409)*15 1890 - 2000 (4167 - 4409)*16	1870 - 2060 (4123 - 4542)*15 1910 - 2110 (4211 - 4652)*16	1880 - 2070 (4145 - 4564)*15 1920 - 2120 (4233 - 4674)*16	1890 - 2080 (4167 - 4586)*15 1930 - 2110 (4255 - 4652)*16 1910 - 2060 (4211 - 4542)*18
25	1090 (2403)*15 1050 (2315)*16 1120 (2469)*18	1090 (2403)*15 1050 (2315)*16 1120 (2469)*18	1090 (2403)*15, 1050 (2315)*16	1130 (2491)*15,*16	1140 (2513)*15,*16	1160 (2557)*15, *16, 1170 (2579)*18
	1710 (3770)*15 1750 (3858)*16 1730 (3814)*18	1710 (3770)*15 1750 (3858)*16 1730 (3814)*18	1710 (3770)*15, 1750 (3858)*16	1670 (3682)*15,*16	1660 (3660)*15,*16	1640 (3616)*15, *16, 1730 (3814)*18
	2800 (6173)*15, *16, 2850 (6283)*18	2800 (6173)*15, *16, 2850 (6283)*18	2800 (6173)*15, *16	2800 (6173)*15, *16	2800 (6173)*15, *16	2800 (6173)*15, *16, 2900 (6393)*18
	87 (19.1), 180 (39.6)*12	87 (19.1), 180 (39.6)*12	87 (19.1), 180 (39.6)*12	87 (19.1), 180 (39.6)*12	87 (19.1), 180 (39.6)*12	87 (19.1), 180 (39.6)*12
	-	-	-	-	-	-
30	165 (102.5)	165 (102.5)	165 (102.5)	180 (111.9)	180 (111.9)	145 (90)
	165 (102.5)	165 (102.5)	165 (102.5)	180 (111.9)	180 (111.9)	-
	17 (11)*13, 45 (28)*14	17 (11)*13, 45 (28)*14	24 (15)*13, 61 (38)*14	19 (12)*13, 49 (30)*14	23 (14)*13, 58 (36)*14	15 (9)*13, 38 (23)*14
	32 (20)*13, 83 (52)*14	32 (20)*13, 83 (52)*14	43 (27)*13, 111 (69)*14	36 (22)*13, 93 (58)*14	39 (24)*13, 100 (62)*14	25 (15)*13, 63 (39)*14
	46 (29)*13, 119 (74)*14	46 (29)*13, 119 (74)*14	66 (41)*13, 165 (103)*14	54 (34)*13, 138 (86)*14	57 (35)*13, 146 (91)*14	40 (24)*13, 102 (63)*14
35	66 (41)*13, 165 (103)*14	66 (41)*13, 165 (103)*14	-	67 (42)*13, 172 (107)*14	80 (50)*13, 180 (112)*14	-
	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)
	2TR - FE	2TR - FE	2TR - FE	1GR-FE	1GR-FE	5L-E
	16 - Valve, DOHC	16 - Valve, DOHC	16 - Valve, DOHC	24 - Valve, DOHC	24 - Valve, DOHC	8 - Valve, OHC
40	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	99.5 × 96.0 (3.92 × 3.78)
	2694 (164.3)	2694 (164.3)	2694 (164.3)	3956 (241.4)	3956 (241.4)	2986 (182.2)
	9.6:1	9.6:1	9.6:1	10.0:1	10.0:1	22.2:1
	EFI	EFI	EFI	EFI	EFI	Distributor Type
	91 or higher	91 or higher	91 or higher	95 or higher	95 or higher	50 or higher
45	120/5200 (SAE - NET)	120/5200 (SAE - NET)	120/5200 (SAE - NET)	179/5200 (SAE-NET)	179/5200 (SAE-NET)	70/4000 (SAE - NET)
	246/3800 (SAE - NET)	246/3800 (SAE - NET)	246/3800 (SAE - NET)	376/3800 (SAE-NET)	376/3800 (SAE-NET)	197/2400 (SAE - NET)
	12 - 48	12 - 48	12 - 48	12 - 55	12 - 55	12 - 64
	960	960	960	960	960	1080
	1.6	1.6	1.6	1.6, 2.0*19	1.6, 2.0*19	2.2
50	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	-	Dry, Single Plate, Diaphragm	-	Dry, Single Plate, Diaphragm
	R150F	R150F	A343F	RA61F	A750F	G52
	3.830	3.830	2.804	4.171	3.520	3.928
	2.062	2.062	1.531	2.190	2.042	2.333
	1.436	1.436	1.000	1.488	1.400	1.451
55	1.000	1.000	0.753	1.193	1.000	1.000
	0.838	0.838	-	1.000	0.716	0.851
	-	-	-	0.799	-	-
	4.220	4.220	2.393	3.607	3.224	4.743
	1.000/2.566	1.000/2.566	1.000/2.566	1.000/2.566	1.000/2.566	1.000/2.566
60	4.555/4.555	4.555/4.555	4.555/4.555	3.727/3.727	3.727/3.727	4.555/4.555
	8.0/8.0	8.0/8.0	8.0/8.0	8.0/8.0	8.0/8.0	8.0/8.0
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Drum , 210	Drum , 210	Drum , 210	Drum , 210	Drum , 210	Drum , 210
65	Single 10”	Single 10”	Single 10”	Single 10”	Single 10”, Hydraulic*20	Single 10”
	LSP & BV, -*21	LSP & BV, -*21	LSP & BV, -*21	LSP & BV, -*21	LSP & BV, -*21	LSP & BV
	Double wishbone	Double wishbone	Double wishbone	Double wishbone	Double wishbone	Double wishbone
	4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod
	Standard	Standard	Standard	Standard	Standard	Standard
70	Standard	Standard	Standard	Standard	Standard	Standard
	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
	15.6	15.6	15.6	15.6	15.6	15.6
	Integral Type	Integral Type	Integral Type	Integral Type	Integral Type	Integral Type

Item / Area				General Countries		
Body Type				5-Door Wagon		
Vehicle Grade				GX	VX	
Model Code				LJ120L-GKMEE	KZ120L-GKMGT	KZJ120L-GKPGT
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4810 (189.4)*3, 4850 (190.9)*1, *3, 4715 (185.6)*2, *3	4810 (189.4)*3, 4850 (190.9)*1, *3, 4715 (185.6)*2, *3	4810 (189.4)*3, 4850 (190.9)*1, *3, 4715 (185.6)*2, *3
		Width	mm (in.)	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4	1790 (70.5), 1875 (73.8)*4
		Height	mm (in.)	1850 (72.8)*5, *7	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7	1850 (72.8)*5, *7, 1840 (72.4)*5, *6, *7
	Wheel Base		mm (in.)	2790 (109.8)	2790 (109.8)	2790 (109.8)
	Tread	Front	mm (in.)	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11
		Rear	mm (in.)	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11	1535 (60.4), 1575 (62.0)*11
	Room	Length	mm (in.)	2520 (99.2)	2520 (99.2)	2520 (99.2)
		Width	mm (in.)	1530 (60.2)	1530 (60.2)	1530 (60.2)
		Height	mm (in.)	1260 (49.6)	1260 (49.6)	1260 (49.6)
	Cargo Space	Length	mm (in.)	-	-	-
		Width	mm (in.)	-	-	-
		Height	mm (in.)	-	-	-
	Overhang	Front	mm (in.)	855 (33.7)*3	855 (33.7)*3	855 (33.7)*3
		Rear	mm (in.)	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2	1165 (45.9), 1205 (47.4)*4, 1070 (42.1)*2
	Min. Running Ground Clearance		mm (in.)	207 (8.1)	207 (8.1)	207 (8.1)
	Angle of Approach		degrees	31°, 32° *4, 26° *10, 27° *4, *10	31°, 32° *4, 26° *10, 27° *4, *10	31°, 32° *4, 26° *10, 27° *4, *10
	Angle of Departure		degrees	26°, 27° *4	26°, 27° *4, 25° *6, 26° *4, *6	26°, 27° *4, 25° *6, 26° *4, *6
	Curb Weight	Front	kg (lb)	1000 - 1090 (2205 - 2403)*15, *16 1000 - 1070 (2205 - 2359)*18	1040 - 1130 (2293 - 2491)*15, *16	1050 - 1140 (2315 - 2513)*15, *16
		Rear	kg (lb)	890 - 990 (1962 - 2183)*15 930 - 1020 (2050 - 2249)*16 910 - 990 (2006 - 2183)*18	900 - 990 (1984 - 2183)*15 940 - 1030 (2072 - 2271)*16	900 - 990 (1984 - 2183)*15 940 - 1030 (2072 - 2271)*16
		Total	kg (lb)	1890 - 2080 (4167 - 4586)*15 1930 - 2110 (4255 - 4652)*16 1910 - 2060 (4211 - 4542)*18	1940 - 2120 (4277 - 4674)*15 1980 - 2160 (4365 - 4762)*16	1950 - 2130 (4299 - 4696)*15 1990 - 2170 (4387 - 4784)*16
	Gross Vehicle Weight	Front	kg (lb)	1160 (2557)*15, *16, 1170 (2579)*18	1200 (2646)*15, *16	1210 (2668)*15, *16
		Rear	kg (lb)	1640 (3616)*15, *16, 1730 (3814)*18	1650 (3638)*15, *16	1640 (3616)*15, *16
		Total	kg (lb)	2800 (6173)*15, *16, 2900 (6393)*18	2850 (6283)*15, *16	2850 (6283)*15, *16
	Fuel Tank Capacity		ℓ (Imp. gal.)	87 (19.1), 180 (39.6)*12	87 (19.1), 180 (39.6)*12	87 (19.1), 180 (39.6)*12
	Luggage Compartment Capacity		m^3 (cu.ft.)	-	-	-
Performance	Max. Speed		km/h (mph)	145 (90)	155 (96)	160 (99)
	Max. Cruising Speed		km/h (mph)	-	155 (96)	160 (99)
	Max. Permissible Speed	1st Gear	km/h (mph)	15 (9)*13, 38 (23)*14	16 (9)*13, 40 (24)*14	21 (13)*13, 55 (34)*14
		2nd Gear	km/h (mph)	25 (15)*13, 63 (39)*14	29 (18)*13, 75 (46)*14	39 (24)*13, 101 (62)*14
		3rd Gear	km/h (mph)	40 (24)*13, 102 (63)*14	42 (26)*13, 107 (66)*14	-
		4th Gear	km/h (mph)	-	-	-
	Min. Turning Radius	Tire	m (ft.)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
		Body	m (ft.)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)
Engine	Engine Type			5L-E	1KZ-TE	1KZ-TE
	Valve Mechanism			8 - Valve, OHC	8 - Valve, OHC	8 - Valve, OHC
	Bore × Stroke		mm (in.)	99.5 × 96.0 (3.92 × 3.78)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
	Displacement		cm^3 (cu.in.)	2986 (182.2)	2982 (181.9)	2982 (181.9)
	Compression Ratio			22.2:1	21.0:1	21.0:1
	Fuel System			Distributor Type	Distributor Type	Distributor Type
	Research Octane No. or Cetane No. (Diesel)			50 or higher	50 or higher	50 or higher
	Max. Output		kW/rpm	70/4000 (SAE - NET)	96/3600 (SAE - NET)	96/3600 (SAE - NET)
	Max. Torque		N·m/rpm	197/2400 (SAE - NET)	343/2000 (SAE - NET)	343/2000 (SAE - NET)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 64	12 - 64	12 - 64
	Alternator Output		Watts	1080	960	960
	Starter Output		kW	2.2	2.2	2.7
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	-
	Transmission Type			G52	R150F	A343F
	Transmission Gear Ratio	In First		3.928	3.830	2.804
		In Second		2.333	2.062	1.531
		In Third		1.451	1.436	1.000
		In Fourth		1.000	1.000	0.753
		In Fifth		0.851	0.838	-
		In Sixth		-	-	-
		In Reverse		4.743	4.220	2.393
	Transfer Gear Ratio H4/L4			1.000/2.566	1.000/2.566	1.000/2.566
	Differential Gear Ratio (Front/Rear)			4.555/4.555	4.100/4.100	4.100/4.100
	Differential Gear Size (Front/Rear)		in.	8.0/8.0	8.0/8.0	8.0/8.0
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Drum , 210	Drum , 210	Drum , 210
	Brake Booster Type and Size		in.	Single 10"	Single 10"	Single 10"
	Proportioning Valve Type			LSP & BV	LSP & BV, -*21	LSP & BV, -*21
	Suspension Type	Front		Double wishbone	Double wishbone	Double wishbone
		Rear		4 Link with Lateral Rod	4 Link with Lateral Rod	4 Link with Lateral Rod
	Stabilizer Bar	Front		Standard	Standard	Standard
		Rear		Standard	Standard	Standard
	Steering Gear Type			Rack & Pinion	Rack & Pinion	Rack & Pinion
	Steering Gear Ratio (Overall)			15.6	15.6	15.6
	Power Steering Type			Integral Type	Integral Type	Integral Type

*1: With Back door - mounted Spare Tire
*2: With Underfloor - mounted Spare Tire
*3: With Grille Guard +75 mm (3.0 in.)
*4: With Over Fender
*5: With 265/65 R17 Tires +15 mm (0.6 in.)
*6: With Air Suspention
*7: With Roof Rail +40 mm (1.6 in.)
*10: With Grille Guard
*13: Transfer in Low
*14: Transfer in High
*15: 5 Seater
*16: 8 Seater
*18: 10 Seater
*21: With ABS