
CAMSHAFT (RH BANK) (1GR–FE)(From August, 2004)


1415X–04


COMPONENTS



Y N·m (kgf·cm, ft·lbf): Specified torque

A75642


VSV Connector
28 (286, 21)
Water By–pass Hose
Intake Air Surge Tank
VSV Connector
Fuel Vapor Feed Hose
Throttle Body w/
Motor Connector
Surge Tank Stay No.2
21 (214, 15)
21 (214, 15)
Surge Tank
Stay No.1
Ventilation Hose No.1
10 (102, 7)
Throttle Body Bracket
21 (214, 15)
◆ Gasket
9.0 (92, 80 in.·lbf)
Seal Washer
Oil Baffle Plate
Ignition
Coil Assy
9.0 (92, 80 in.·lbf)
10 (102, 7)
Cylinder Head Cover
Sub–assy RH
Cylinder Head Cover
Sub–assy LH
9.0 (92, 80 in.·lbf)
Cylinder Head Cover Gasket No.1
Cylinder Head Cover
Gasket No.2
Timing Chain Cover Plate
◆ Gasket
9.0 (92, 80 in.·lbf)
10 (102, 7)
Chain Tensioner Assy No.1
N·m (kgf·cm, ft·lbf): Specified torque
◆ Non–reusable part
G38095



Y N·m (kgf·cm, ft·lbf): Specified torque

G38093