# MULTIPLEX COMMUNICATION SYSTEM

## HOW TO PROCEED WITH TROUBLESHOOTING

05AEO–01

HINT:

Troubleshoot in accordance with the procedures on the following pages.

| | |
|---|---|
| 1 | VEHICLE BROUGHT TO WORKSHOP |

| | |
|---|---|
| 2 | CUSTOMER PROBLEM ANALYSIS CHECK AND SYMPTOM CHECK (See page 05–1830) |

| | |
|---|---|
| 3 | DIAGNOSTIC TROUBLE CODE CHECK (See page 05–1824) |

(a) Check for DTCs and make a note of the code that is output.
(b) Delete the DTC.
(c) Check if the DTC will be output once again, when the problem symptom is simulated based on the noted code.
  (1) When no code is output (symptom check and simulation is possible), proceed to A.
  (2) When a code is output, proceed to B.

| | |
|---|---|
| B | Go to step 6 |

A

| | |
|---|---|
| 4 | PROBLEM SYMPTOMS TABLE (See page 05–1830) |

(a) Without applicable symptoms, proceed to A.
(b) With applicable symptoms, proceed to B.

| | |
|---|---|
| B | Go to step 6 |

A

| | |
|---|---|
| 5 | PERFORM TROUBLESHOOTING IN FOLLOWING METHOD, DEPENDING ON MALFUNCTION SYMPTOM |

(a) Pre–check (See page 05–1823)
(b) Terminals of ECU (See page 05–1827)

| | |
|---|---|
| 6 | ADJUST, REPAIR OR REPLACE |

END