












SDS TOYOTA Land Cruiser RZJ120, 125 GRJ120, 125 Jan. '03

		3RZ–FE	1GR–FE
cm³ or CC *(cu. in.)*		2694 *(164.4)*	3956 *(241.4)*
 **mm** *(in.)* **N** *(kgf)*		7–8 *(0.28–0.31)* ※295–440 *(30–45)*	———
		10–13 *(0.39–0.51)* ※196–392 *(20–40)*	———
		6.5–7.5 *(0.26–0.30)* ※245–392 *(25–40)*	———
 A	**DENSO**	w/o TWC*3 K16R–U; w/ TWC*3 K16R–U11	K20HR–U11
	NGK	w/o TWC*3 BKR5EYA; w/ TWC*3 BKR5EYA–11	LFR6C11
	A **mm** *(in.)*	w/o TWC*3 0.8 *(0.031)*; w/ TWC*3 1.1 *(0.043)*	1.1 (0.043)
 **KΩ**		25 or more	———
 **BTDC**		3–7° (DLC3 Terminals 13 (TC) – 4 (CG) connected)	7–24° (DLC3 Terminals 13 (TC) – 4 (CG) connected)
 **mm** *(in.)*		0.15–0.25 *(0.006–0.010)*	0.15–0.25 *(0.006–0.010)*
		0.25–0.35 *(0.010–0.014)*	0.29–0.39 *(0.011–0.015)*
 **rpm**		*4 650–750 *5 750–850	650–750
			
 *1 **CO%**		Saudi Arabia, China, Europe: 0.5 or more Others: 1.0–2.0 (Check Connector TE_1–E_1 Connected)	0–0.5

 **kPa** *(kgf/cm², psi)*		1230 *(12.5, 178)*	1300 *(13.3, 189)*
		880 *(9.0, 127)* or more	1000 *(10.2, 145)* or more
		98 *(1.0, 14)* or more	100 *(1.0, 15)* or more
 **kPa** *(kgf/cm², psi)*		29 *(0.3, 4.2)* or more	
	3,000 rpm 	245–490 *(2.5–5.0, 36–71)*	294–588 *(3.0–6.0, 43–85)*
 **N·m** *(kgf·cm, ft·lbf)*	**A**	① 39 *(400, 29)* ② 90° ③ 90°	① 36 *(367, 27)* ② 90° ③ 90°
	B	29 *(300, 22)*	28 *(286, 21)*
	C	49 *(500, 36)*	30 *(306, 22)*

	3RZ–FE	1GR–FE
 **liter** *(US qts, Imp. qts)*	4.4 *(4.7, 3.9)*	4.9 *(5.2, 4.3)*
	5.1 *(5.4, 4.5)*	5.2 *(5.5, 4.6)*
	API grade SJ "Energy-Conserving" SL "Energy-Conserving" or ILSAC multigrade engine oil	
 **liter** *(US qts, Imp. qts)*	M/T 7.3 *(7.7, 6.4)* A/T *7.1 (7.5, 6.2)*	M/T 9.4 *(9.9, 8.3)* A/T *9.8 (10.4, 8.6)*

Printed in Japan


*1 In the 2 mode (2,500 rpm and idle) test, follow the measurement order prescribed by the applicable local regulations.
*2 ILSAC: International Lubricant Standarzation and Approval Committer
*3 TWC: Three–way Catalytic Converter *4 Unled gasoline *5 Lead gasoline







TOYOTA MOTOR CORPORATION Pub. No. SDS468E



Land Cruiser





RZJ120 RZJ125
GRJ120 GRJ125


TOYOTA QUALITY SERVICE




	A	197.9–207.9 *(7.791–8.185)*	193.9–203.9 *(7.634–8.028)*
	B	5–15 *(0.20–0.59)*	
	C	⬆ 25 *(0.98)*	
mm *(in.)*		SAE J1703 or FMVSS No. 116 DOT3	


		RZJ	GRJ
	A	LHD: 181.6–191.6 *(7.15–7.54)* RHD: 180.6–190.6 *(7.11–7.50)*	
	B	1–6 *(0.04–0.24)*	
	C	※1 ⬆ 52 *(2.05)* ※2 ⬆ 55 *(2.17)* ※3 ⬆ 55 *(2.17)*	※6 ⬆ 55 *(2.17)* ※7 ⬆ 44 *(2.73)*
mm *(in.)*		SAE J1703 or FMVSS No. 116 DOT3	
 196 N *(20 kgf, 44 lbf)*		5–7	
			
mm *(in.)*	A	⬆ 1.0 *(0.039)*	
	B	⬆ 26 *(1.02)*	⬆ 16 *(0.63)*
 mm *(in.)*		⬆ 1.0 *(0.039)*	
 mm *(in.)*		⬇ 211 *(8.307)*	

			
 N·m *(kgf·cm, ft·lbf)*		113 *(1150, 83)*	

			RZJ	GRJ
			2.5 *(2.6, 2.2)*	2.2 *(2.3, 1.9)*
liter *(US qts, Imp. qts)*			API GL–4 or GL–5 SAE 75W–90	
			2.0 *(2.1, 1.8)*	
liter *(US qts, Imp. qts)*			ATF TYPE T–IV	
			Full–time type 1.4 *(1.5, 1.2)* Part–time type 1.0 *(1.1, 0.9)*	1.4 *(1.5, 1.2)*
liter *(US qts, Imp. qts)*			Full–time type API GL-5 SAE 75W-90 Part–time type API GL-3 SAE 75W-90	API GL–5 SAE 75W–90
				
	Australia			2.95 *(3.1, 2.6)* (w/ Rr Differential lock) 3.05 *(3.2, 2.7)* (w/ o Rr Differential lock)
	Others	3-door model	1.4 *(1.5, 1.2)*	2.4 *(2.6, 2.2)* (w/ Rr Differential lock) 2.5 *(2.6, 2.2)* (w/ o Rr Differential lock)
		5-door model		2.95 *(3.1, 2.6)* (w/ Rr Differential lock) 3.05 *(3.2, 2.7)* (w/ o Rr Differential lock)
liter *(US qts, Imp. qts)*			Hypoid gear oil API GL–5 With LSD use LSD oil only SAE 90 (⬆ –18° C (0° F)) SAE 80W, 80W–90 (⬇ –18° C (0° F))	

	RZJ•GRJ
 mm *(in.)*	⬇ 30 (1.18)

		3–door model	5–door model
	A	0°16′±45′ *(0.27°±0.75°)*	0°19′±45′ *(0.32°±0.75°)*
	B	12°14′±45′ *(12.23°±0.75°)*	12°11′±45′ *(12.18°±0.75°)*
	C	2°41′±45′ *(2.68°±0.75°)*	Normal suspension 2°40′±45′ *(2.67°±0.75°)* Air suspension 2°56′±45′ *(2.93°±0.75°)*
	D	36°20′ $^{+1°}_{-2°}$ *(36.33° $^{+1°}_{-2°}$)*	
	E+F	0°05′±0°10′ *(0.08°±0.16°)*	0°10′±0°10′ *(0.16°±0.16°)*
	G–H mm *(in.)*	1±2 *(0.04+0.08)*	2±2 *(0.08+0.08)*

			
 kPa *(kgf/cm², psi)*	225/70R17 108S	200 *(2.0, 29)*	200 *(2.0, 29)* 260 *(2.7, 38)**1
	225/70R17C 108S	200 *(2.0, 29)*	200 *(2.0, 29)* 290 *(3.0, 42)**1
	P265/65R17 110S	200 *(2.0, 29)*	200 *(2.0, 29)*
	265/65R17 112S	200 *(2.0, 29)* 190 *(1.9, 28)**2	200 *(2.0, 29)* 190 *(1.9, 28)**2

*1: Standard inflation for all loads including full rated loads
*2: Australia

© 2003 TOYOTA MOTOR CORPORATION

※1: w/ ABS
※2: w/o ABS
※3: w / ABS and VSC
※4: w/ Limited slip differential
※5: w/o Limited slip differential
※6: w/ VSC and TRC
※7: w/o VSC and TRC