MAJOR TECHNICAL SPECIFICATIONS

Item / Area				General Countries			
Body Type				Station Wagon (Lift-up/8-seater)		Station Wagon (Lift-up/5-seater)	Station Wagon (Lift-up/8-seater)
Vehicle Grade				GX			
Model Code				VDJ200R-GNTNZ	VDJ200L-GNTNZ	VDJ200R-GMMNZ	VDJ200R-GNMNZ
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)
		Width	mm (in.)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
		Height	mm (in.)	1905 (74.9)	1905 (74.9)	1905 (74.9)	1905 (74.9)
	Wheel Base		mm (in.)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
	Tread	Front	mm (in.)	1680 (66.1)	1680 (66.1)	1680 (66.1)	1680 (66.1)
		Rear	mm (in.)	1675 (65.9)	1675 (65.9)	1675 (65.9)	1675 (65.9)
	Room	Length	mm (in.)	2715 (106.8)	2715 (106.8)	2715 (106.8)	2715 (106.8)
		Width	mm (in.)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)
		Height	mm (in.)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
	Overhang	Front	mm (in.)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
		Rear	mm (in.)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)
	Min. Running Ground Clearance		mm (in.)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)
	Angle of Approach		degrees	30	30	30	30
	Angle of Departure		degrees	20	20	20	20
	Curb Weight	Front	kg (lb)	1430 - 1515 (3153 - 3340), 1420 - 1505 (3131 - 3318)*3	1430 - 1515 (3153 - 3340), 1420 - 1505 (3131 - 3318)*3	1410 - 1480 (3108 - 3263)	1410 - 1495 (3109 - 3296), 1400 - 1485 (3086 - 3274)*3
		Rear	kg (lb)	1200 - 1240 (2646 - 2734), 1255 - 1295 (2767 - 2855)*3	1200 - 1240 (2646 - 2734), 1255 - 1295 (2767 - 2855)*3	1140 - 1255 (2514 - 2767)	1190 - 1210 (2623 - 2668), 1245 - 1265 (2745 - 2789)*3
		Total	kg (lb)	2630 - 2755 (5798 - 6074), 2675 - 2800 (5897 - 6173)*3	2630 - 2755 (5798 - 6074), 2675 - 2800 (5897 - 6173)*3	2550 - 2735 (5622 - 6030)	2600 - 2705 (5732 - 5963), 2645 - 2750 (5831 - 6063)*3
	Gross Vehicle Weight	Front	kg (lb)	1600 (3527)	1600 (3527)	1520 (3351)	1565 (3450), 1570 (3461)*3
		Rear	kg (lb)	1750 (3858)	1750 (3858)	1780 (3924)	1785 (3935), 1780 (3924)*3
		Total	kg (lb)	3350 (7385)	3350 (7385)	3300 (7275)	3350 (7385)
	Fuel Tank Capacity		L (US.gal, Imp.gal)	93 (24.6, 20.5), 138 (36.5, 30.4)*1	93 (24.6, 20.5), 138 (36.5, 30.4)*1	93 (24.6, 20.5), 138 (36.5, 30.4)*1	93 (24.6, 20.5), 138 (36.5, 30.4)*1
	Luggage Capacity (VDA)		m^3 (cu.ft.)	0.259 (9.1)	0.259 (9.1)	0.909 (32.1)	0.259 (9.1)
Performance	Max. Speed		km/h	210	210	170	170
	Max. Cruising Speed		km/h	210	210	170	170
	Acceleration	0 to 100 km/h	sec.	8.6	8.6	12.0	12.0
		0 to 400 m	sec.	16.2	16.2	18.2	18.2
	Max. Permissible Speed	1st Gear	km/h	51	51	35	35
		2nd Gear	km/h	86	86	64	64
		3rd Gear	km/h	125	125	106	106
		4th Gear	km/h	169	169	158	158
		5th Gear	km/h	210	210	170	170
		6th Gear	km/h	210	210	—	—
	Min. Turning Radius	Tire	m (ft.)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)
		Body	m (ft.)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)
Engine	Engine Type			1VD-FTV	1VD-FTV	1VD-FTV	1VD-FTV
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve, DOHC	32-valve, DOHC	32-valve, DOHC	32-valve, DOHC
	Bore × Stroke		mm (in.)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)
	Displacement		cm^3 (cu.in.)	4461 (272.2)	4461 (272.2)	4461 (272.2)	4461 (272.2)
	Compression Ratio			16.8 : 1	16.8 : 1	16.8 : 1	16.8 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Cetane Number			50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher
	Max. Output (SAE)		kW@rpm	173@3200*2	173@3200*2	162@3600*2	162@3600*2
	Max. Torque (SAE)		N·m@rpm	615@1800 - 2200*2	615@1800 - 2200*2	430@1200 - 3600*2	430@1200 - 3600*2
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 110	12 - 110	12 - 110	12 - 110
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	2.7	2.7	2.7	2.7
Chassis	Clutch Type			—	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			AB60F	AB60F	H150F	H150F
	Gear Ratio	In 1st		3.333	3.333	4.529	4.529
		In 2nd		1.960	1.960	2.464	2.464
		In 3rd		1.353	1.353	1.490	1.490
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.728	0.728	0.881	0.881
		In 6th		0.588	0.588	—	—
		In Reverse		3.061	3.061	4.313	4.313
	Transfer Gear Ratio		H4/L4	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
	Differential Gear Ratio (Front/Rear)			3.909/3.909	3.909/3.909	3.909/3.909	3.909/3.909
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio			16.7	16.7	16.7	16.7
	Power Steering Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic

*1: Option
*2: ECE
*3: Models with sub fuel tank

General Countries					
Station Wagon (Lift-up/9-seater)	Station Wagon (Lift-up/5-seater)	Station Wagon (Lift-up/8-seater)	Station Wagon (Lift-up/9-seater)	Station Wagon (Lift-up/8-seater)	
GX				VX	
VDJ200R-GPMNZ	VDJ200L-GMMNZ	VDJ200L-GNMNZ	VDJ200L-GPMNZ	VDJ200R-GNTEZ	VDJ200L-GNTEZ
4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)
1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
1905 (74.9)	1905 (74.9)	1905 (74.9)	1905 (74.9)	1905 (74.9)	1905 (74.9)
2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
1680 (66.1)	1680 (66.1)	1680 (66.1)	1680 (66.1)	1640 (64.5)	1640 (64.5)
1675 (65.9)	1675 (65.9)	1675 (65.9)	1675 (65.9)	1635 (64.3)	1635 (64.3)
2715 (106.8)	1965 (77.4)	2715 (106.8)	2715 (106.8)	2715 (106.8)	2715 (106.8)
1640 (64.5)	1615 (63.6)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)
1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)
225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)
30	30	30	30	30	30
20	20	20	20	20	20
1410 - 1475 (3108 - 3252)	1410 - 1500 (3109 - 3307)	1400 - 1500 (3086 - 3307), 1390 - 1490 (3064 - 3285)*3	1410 - 1480 (3108 - 3263)	1425 - 1460 (3142 - 3219), 1415 - 1450 (3120 - 3197)*3	1425 - 1460 (3142 - 3219), 1415 - 1450 (3120 - 3197)*3
1160 - 1250 (2558 - 2756)	1140 - 1215 (2513 - 2679)	1175 - 1205 (2590 - 2657), 1230 - 1260 (2712 - 2778)*3	1160 - 1250 (2558 - 2756)	1195 - 1295 (2635 - 2855), 1250 - 1350 (2756 - 2976)*3	1195 - 1295 (2635 - 2855), 1250 - 1350 (2756 - 2976)*3
2570 - 2725 (5666 - 6008)	2550 - 2715 (5622 - 5986)	2575 - 2705 (5677 - 5963), 2620 - 2750 (5776 - 6063)*3	2570 - 2730 (5666 - 6019)	2620 - 2755 (5776 - 6074), 2665 - 2800 (5875 - 6173)*3	2620 - 2755 (5776 - 6074), 2665 - 2800 (5875 - 6173)*3
1520 (3351)	1575 (3472)	1570 (3461), 1575 (3472)*3	1520 (3351)	1545 (3406)	1545 (3406)
1780 (3924)	1775 (3913)	1780 (3924), 1775 (3913)*3	1780 (3924)	1805 (3979)	1805 (3979)
3300 (7275)	3350 (7385)	3350 (7385)	3300 (7275)	3350 (7385)	3350 (7385)
93 (24.6, 20.5), 138 (36.5, 30.4)*1	138 (36.5, 30.4)	93 (24.6, 20.5), 138 (36.5, 30.4)*1	138 (36.5, 30.4)	93 (24.6, 20.5), 138 (36.5, 30.4)*1	93 (24.6, 20.5), 138 (36.5, 30.4)*1
0.060 (2.1)	0.909 (32.1)	0.259 (9.1)	0.060 (2.1)	0.259 (9.1)	0.259 (9.1)
170	170	170	170	210	210
170	170	170	170	210	210
12.0	12.0	12.0	12.0	8.6	8.6
18.2	18.2	18.2	18.2	16.2	16.2
35	35	35	35	51	51
64	64	64	64	86	86
106	106	106	106	125	125
158	158	158	158	169	169
170	170	170	170	210	210
—	—	—	—	210	210
5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)
6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)
1VD-FTV	1VD-FTV	1VD-FTV	1VD-FTV	1VD-FTV	1VD-FTV
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
32-valve, DOHC	32-valve, DOHC	32-valve, DOHC	32-valve, DOHC	32-valve, DOHC	32-valve, DOHC
86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)
4461 (272.2)	4461 (272.2)	4461 (272.2)	4461 (272.2)	4461 (272.2)	4461 (272.2)
16.8 : 1	16.8 : 1	16.8 : 1	16.8 : 1	16.8 : 1	16.8 : 1
Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher
162@3600*2	162@3600*2	162@3600*2	162@3600*2	173@3200*2	173@3200*2
430@1200 - 3600*2	430@1200 - 3600*2	430@1200 - 3600*2	430@1200 - 3600*2	615@1800 - 2200*2	615@1800 - 2200*2
12 - 110	12 - 110	12 - 110	12 - 110	12 - 110	12 - 110
1560	1560	1560	1560	1800	1800
2.7	2.7	2.7	2.7	2.7	2.7
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—	—
H150F	H150F	H150F	H150F	AB60F	AB60F
4.529	4.529	4.529	4.529	3.333	3.333
2.464	2.464	2.464	2.464	1.960	1.960
1.490	1.490	1.490	1.490	1.353	1.353
1.000	1.000	1.000	1.000	1.000	1.000
0.881	0.881	0.881	0.881	0.728	0.728
—	—	—	—	0.588	0.588
4.313	4.313	4.313	4.313	3.061	3.061
1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
3.909/3.909	3.909/3.909	3.909/3.909	3.909/3.909	3.909/3.909	3.909/3.909
220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
16.7	16.7	16.7	16.7	16.7	16.7
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic

Item \ Area				General Countries			
Body Type				Station Wagon (Swing/5-seater)	Station Wagon (Swing/9-seater, 10-seater*5)	Station Wagon (Swing/5-seater)	Station Wagon (Swing/9-seater, 10-seater*5)
Vehicle Grade				Standard			
Model Code				VDJ200R-GCMRZ	VDJ200R-GDMRZ	VDJ200R-KCMRZ	VDJ200R-KDMRZ
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Wheel Base		mm (in.)	—	—	—	—
	Tread	Front	mm (in.)	—	—	—	—
		Rear	mm (in.)	—	—	—	—
	Room	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	—	—	—	—
		Rear	mm (in.)	—	—	—	—
	Min. Running Ground Clearance		mm (in.)	—	—	—	—
	Angle of Approach		degrees	—	—	—	—
	Angle of Departure		degrees	—	—	—	—
	Curb Weight	Front	kg (lb)	1395 - 1470 (3075 - 3241), 1385 - 1460 (3053 - 3219)*3	1395 - 1480 (3075 - 3263), 1385 - 1470 (3053 - 3241)*3	1395 - 1460 (3075 - 3219)	1395 - 1465 (3075 - 3230), 1400 - 1470 (3086 - 3241)*5
		Rear	kg (lb)	1125 - 1205 (2480 - 2657), 1180 - 1260 (2601 - 2778)*3	1150 - 1220 (2535 - 2690), 1205 - 1265 (2657 - 2789)*3	1125 - 1260 (2480 - 2778)	1150 - 1245 (2535 - 2745)
		Total	kg (lb)	2520 - 2675 (5556 - 5897), 2565 - 2720 (5655 - 5997)*3	2545 - 2700 (5611 - 5952), 2590 - 2735 (5710 - 6030)*3	2520 - 2720 (5556 - 5997)	2545 - 2710 (5611 - 5975), 2550 - 2715 (5622 - 5986)*5
	Gross Vehicle Weight	Front	kg (lb)	1500 (3307)	1610 (3549)	1540 (3395)	1515 (3340), 1585 (3494)*5
		Rear	kg (lb)	1850 (4079)	1740 (3836)	1810 (3990)	1835 (4045), 1765 (3891)*5
		Total	kg (lb)	3350 (7385)	3350 (7385)	3350 (7385)	3350 (7385)
	Fuel Tank Capacity		L (US.gal, Imp.gal)	138 (36.5, 30.4)	93 (24.6, 20.5), 138 (36.5, 30.4)*1	138 (36.5, 30.4)	93 (24.6, 20.5), 138 (36.5, 30.4)*1
	Luggage Capacity (VDA)		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h	—	—	—	—
	Max. Cruising Speed		km/h	—	—	—	—
	Acceleration	0 to 100 km/h	sec.	—	—	—	—
		0 to 400 m	sec.	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h	—	—	—	—
		2nd Gear	km/h	—	—	—	—
		3rd Gear	km/h	—	—	—	—
		4th Gear	km/h	—	—	—	—
		5th Gear	km/h	—	—	—	—
		6th Gear	km/h	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	—	—	—	—
		Body	m (ft.)	—	—	—	—
Engine	Engine Type			1VD-FTV	1VD-FTV	1VD-FTV	1VD-FTV
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve, DOHC	32-valve, DOHC	32-valve, DOHC	32-valve, DOHC
	Bore × Stroke		mm (in.)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)
	Displacement		cm^3 (cu.in.)	4461 (272.2)	4461 (272.2)	4461 (272.2)	4461 (272.2)
	Compression Ratio			16.8 : 1	16.8 : 1	16.8 : 1	16.8 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Octane Rating or Cetane Number (Diesel)			50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher
	Max. Output (SAE)		kW@rpm	136@3200	136@3200	136@3200	136@3200
	Max. Torque (SAE)		N·m@rpm	430@1600 - 3000	430@1600 - 3000	430@1600 - 3000	430@1600 - 3000
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 110	12 - 110	12 - 110	12 - 110
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	2.7	2.7	2.7	2.7
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			H150F	H150F	H150F	H150F
	Gear Ratio	In 1st		4.529	4.529	4.529	4.529
		In 2nd		2.464	2.464	2.464	2.464
		In 3rd		1.490	1.490	1.490	1.490
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.881	0.881	0.881	0.881
		In 6th		—	—	—	—
		In Reverse		4.313	4.313	4.313	4.313
	Transfer Gear Ratio		H4/L4	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
	Differential Gear Ratio (Front/Rear)			3.909/3.909	3.909/3.909	3.909/3.909	3.909/3.909
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio			16.7	16.7	16.7	16.7
	Power Steering Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic

*1: Option
*2: ECE
*3: Models with sub fuel tank
*4: Cold area specification models
*5: Models with bench type front passenger seat

General Countries					
Station Wagon (Swing/5-seater)	Station Wagon (Swing/9-seater, 10-seater*5)	Station Wagon (Swing/5-seater)	Station Wagon (Swing/9-seater, 10-seater*5)	Station Wagon (Lift-up/8-seater)	Station Wagon (Lift-up/5-seater)
Standard				GX	
VDJ200L-GCMRZ	VDJ200L-GDMRZ	VDJ200L-KCMRZ	VDJ200L-KDMRZ	GRJ200R-GNMNK	GRJ200L-GMMNK
—	—	—	—	4950 (194.9)	4950 (194.9)
—	—	—	—	1970 (77.6)	1970 (77.6)
—	—	—	—	1905 (74.9)	1905 (74.9)
—	—	—	—	2850 (112.2)	2850 (112.2)
—	—	—	—	1680 (66.1)	1680 (66.1)
—	—	—	—	1675 (65.9)	1675 (65.9)
—	—	—	—	2715 (106.8)	1965 (77.4)
—	—	—	—	1640 (64.5)	1615 (63.6)
—	—	—	—	1200 (47.2)	1200 (47.2)
—	—	—	—	930 (36.6)	930 (36.6)
—	—	—	—	1175 (46.2)	1175 (46.2)
—	—	—	—	225 (8.9)	225 (8.9)
—	—	—	—	30	30
—	—	—	—	20	20
1395 - 1470 (3075 - 3241)	1395 - 1465 (3075 - 3230)	1395 - 1460 (3075 - 3219)	1395 - 1465 (3075 - 3230), 1400 - 1470 (3086 - 3241)*5	1220 - 1300 (2690 - 2866)	1230 - 1300 (2711 - 2866)
1125 - 1250 (2480 - 2756)	1145 - 1245 (2524 - 2745)	1125 - 1245 (2480 - 2745)	1145 - 1245 (2524 - 2745)	1155 - 1285 (2546 - 2833)	1120 - 1215 (2469 - 2678)
2520 - 2720 (5556 - 5997)	2540 - 2710 (5600 - 5975)	2520 - 2705 (5556 - 5963)	2540 - 2710 (5600 - 5975), 2545 - 2715 (5611 - 5986)*5	2375 - 2585 (5236 - 5699)	2350 - 2515 (5180 - 5544)
1540 (3395)	1590 (3505)	1535 (3384)	1515 (3340), 1585 (3494)*5	1340 (2954)	1340 (2954)
1810 (3990)	1760 (3880)	1815 (4001)	1835 (4045), 1765 (3891)*5	1920 (4233)	1920 (4233)
3350 (7385)	3350 (7385)	3350 (7385)	3350 (7385)	3260 (7187)	3260 (7187)
138 (36.5, 30.4)	93 (24.6, 20.5), 138 (36.5, 30.4)*1	138 (36.5, 30.4)	93 (24.6, 20.5), 138 (36.5, 30.4)*1	138 (36.5, 30.4)	138 (36.5, 30.4)
—	—	—	—	0.259 (9.1)	0.909 (32.1)
—	—	—	—	200	200
—	—	—	—	200	200
—	—	—	—	11.0	11.0
—	—	—	—	17.8	17.8
—	—	—	—	43	43
—	—	—	—	78	78
—	—	—	—	130	130
—	—	—	—	193	193
—	—	—	—	200	200
—	—	—	—	—	—
—	—	—	—	5.9 (19.4)	5.9 (19.4)
—	—	—	—	6.3 (20.7)	6.3 (20.7)
1VD-FTV	1VD-FTV	1VD-FTV	1VD-FTV	1GR-FE	1GR-FE
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	6-cylinder, V Type	6-cylinder, V Type
32-valve, DOHC	32-valve, DOHC	32-valve, DOHC	32-valve, DOHC	24-valve, DOHC with VVT-i	24-valve, DOHC with VVT-i
86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)
4461 (272.2)	4461 (272.2)	4461 (272.2)	4461 (272.2)	3956 (241.4)	3956 (241.4)
16.8 : 1	16.8 : 1	16.8 : 1	16.8 : 1	10.0 : 1	10.0 : 1
Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	SFI	SFI
50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	95 or higher	95 or higher
136@3200	136@3200	136@3200	136@3200	179@5200*2	179@5200*2
430@1600 - 3000	430@1600 - 3000	430@1600 - 3000	430@1600 - 3000	376@3800*2	376@3800*2
12 - 110	12 - 110	12 - 110	12 - 110	12 - 55	12 - 55
1560	1560	1560	1560	1200	1200
2.7	2.7	2.7	2.7	1.4, 2.0*1	1.4, 2.0*4
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
H150F	H150F	H150F	H150F	H150F	H150F
4.529	4.529	4.529	4.529	4.529	4.529
2.464	2.464	2.464	2.464	2.464	2.464
1.490	1.490	1.490	1.490	1.490	1.490
1.000	1.000	1.000	1.000	1.000	1.000
0.881	0.881	0.881	0.881	0.881	0.881
—	—	—	—	—	—
4.313	4.313	4.313	4.313	4.313	4.313
1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
3.909/3.909	3.909/3.909	3.909/3.909	3.909/3.909	4.100/4.100	4.100/4.100
220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
16.7	16.7	16.7	16.7	16.7	16.7
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic

Item / Area				General Countries			
Body Type				Station Wagon (Lift-up/8-seater)	Station Wagon (Lift-up/9-seater)	Station Wagon (Swing/9-seater, 10-seater*5)	Station Wagon (Swing/5-seater)
Vehicle Grade				GX		Standard	
Model Code				GRJ200L-GNMNK	GRJ200L-GPMNK	GRJ200R-KDMRK	GRJ200L-KCMRK
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4950 (194.9)	4950 (194.9)	—	—
		Width	mm (in.)	1970 (77.6)	1970 (77.6)	—	—
		Height	mm (in.)	1905 (74.9)	1905 (74.9)	—	—
	Wheel Base		mm (in.)	2850 (112.2)	2850 (112.2)	—	—
	Tread	Front	mm (in.)	1680 (66.1)	1680 (66.1)	—	—
		Rear	mm (in.)	1675 (65.9)	1675 (65.9)	—	—
	Room	Length	mm (in.)	2715 (106.8)	2715 (106.8)	—	—
		Width	mm (in.)	1640 (64.5)	1640 (64.5)	—	—
		Height	mm (in.)	1200 (47.2)	1200 (47.2)	—	—
	Overhang	Front	mm (in.)	930 (36.6)	930 (36.6)	—	—
		Rear	mm (in.)	1175 (46.2)	1170 (46.1)	—	—
	Min. Running Ground Clearance		mm (in.)	225 (8.9)	225 (8.9)	—	—
	Angle of Approach		degrees	30	30	—	—
	Angle of Departure		degrees	20	20	—	—
	Curb Weight	Front	kg (lb)	1240 - 1335 (2734 - 2943)	1230 - 1290 (2711 - 2844)	1215 - 1290 (2679 - 2844), 1220 - 1295 (2690 - 2855)*5	1220 - 1285 (2690 - 2833)
		Rear	kg (lb)	1165 - 1260 (2568 - 2778)	1140 - 1230 (2513 - 2711)	1125 - 1250 (2480 - 2756)	1105 - 1225 (2436 - 2701)
		Total	kg (lb)	2405 - 2595 (5302 - 5721)	2370 - 2520 (5224 - 5555)	2340 - 2540 (5159 - 5600), 2345 - 2545 (5170 - 5611)*5	2325 - 2510 (5126 - 5534)
	Gross Vehicle Weight	Front	kg (lb)	1390 (3064)	1340 (2954)	1320 (2910), 1380 (3042)*5	1340 (2954)
		Rear	kg (lb)	1910 (4211)	1920 (4233)	1940 (4277), 1920 (4233)*5	1920 (4233)
		Total	kg (lb)	3300 (7275)	3260 (7187)	3260 (7187), 3300 (7275)*5	3260 (7187)
	Fuel Tank Capacity		L (US.gal, Imp.gal)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)
	Luggage Capacity (VDA)		m^3 (cu.ft.)	0.259 (9.1)	0.060 (2.1)	—	—
Performance	Max. Speed		km/h	200	200	—	—
	Max. Cruising Speed		km/h	200	200	—	—
	Acceleration	0 to 100 km/h	sec.	11.0	11.0	—	—
		0 to 400 m	sec.	17.8	17.8	—	—
	Max. Permissible Speed	1st Gear	km/h	43	43	—	—
		2nd Gear	km/h	78	78	—	—
		3rd Gear	km/h	130	130	—	—
		4th Gear	km/h	193	193	—	—
		5th Gear	km/h	200	200	—	—
		6th Gear	km/h	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	5.9 (19.4)	5.9 (19.4)	—	—
		Body	m (ft.)	6.3 (20.7)	6.3 (20.7)	—	—
Engine	Engine Type			1GR-FE	1GR-FE	1GR-FE	1GR-FE
	No. of Cyls. & Arrangement			6-cylinder, V Type	6-cylinder, V Type	6-cylinder, V Type	6-cylinder, V Type
	Valve Mechanism			24-valve, DOHC with VVT-i	24-valve, DOHC with VVT-i	24-valve, DOHC with VVT-i	24-valve, DOHC with VVT-i
	Bore × Stroke		mm (in.)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)
	Displacement		cm^3 (cu.in.)	3956 (241.4)	3956 (241.4)	3956 (241.4)	3956 (241.4)
	Compression Ratio			10.0 : 1	10.0 : 1	10.0 : 1	10.0 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating or Cetane Number (Diesel)			95 or higher	95 or higher	95 or higher	95 or higher
	Max. Output (SAE)		kW@rpm	179@5200*2	179@5200*2	179@5200*2	179@5200*2
	Max. Torque (SAE)		N·m@rpm	376@3800*2	376@3800*2	376@3800*2	376@3800*2
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 55	12 - 55	12 - 55	12 - 55
	Alternator Output		Watts	1200	1200	1200	1200
	Starter Output		kW	1.4, 2.0*4	1.4	1.4	1.4
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			H150F	H150F	H150F	H150F
	Gear Ratio	In 1st		4.529	4.529	4.529	4.529
		In 2nd		2.464	2.464	2.464	2.464
		In 3rd		1.490	1.490	1.490	1.490
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.881	0.881	0.881	0.881
		In 6th		—	—	—	—
		In Reverse		4.313	4.313	4.313	4.313
	Transfer Gear Ratio		H4/L4	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
	Differential Gear Ratio (Front/Rear)			4.100/4.100	4.100/4.100	4.100/4.100	4.100/4.100
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio			16.7	16.7	16.7	16.7
	Power Steering Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic

*1: Models with bench type front passenger seat
*2: ECE
*3: Models with towing package
*4: Cold area specification models
*5: Models with bench type front passenger seat
*6: Either is selectable

General Countries		G.C.C. Countries			
Station Wagon (Swing/9-seater, 10-seater*1)	Station Wagon (Lift-up/8-seater)	Station Wagon (Lift-up/9-seater)	Station Wagon (Lift-up/8-seater)	Station Wagon (Lift-up/9-seater)	
Standard	VX	GX			
GRJ200L-KDMRK	UZJ200L-GNAEK	GRJ200L-GNANKV	GRJ200L-GPANKV	GRJ200L-GNMNKV	GRJ200L-GPMNKV
—	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)
—	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
—	1905 (74.9)	1890 (74.3)	1890 (74.3)	1890 (74.3)	1890 (74.3)
—	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
—	1640 (64.5)	1680 (66.1)	1680 (66.1)	1680 (66.1)	1680 (66.1)
—	1635 (64.3)	1675 (65.9)	1675 (65.9)	1675 (65.9)	1675 (65.9)
—	2715 (106.8)	2715 (106.8)	2905 (114.4)	2715 (106.8)	2905 (114.4)
—	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)
—	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
—	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
—	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)
—	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)
—	30	30	30	30	30
—	20	20	20	20	20
1220 - 1290 (2690 - 2844), 1225 - 1295 (2701 - 2855)*1	1310 - 1335 (2888 - 2944)	1230 - 1360 (2712 - 2998)	1225 - 1300 (2701 - 2866)	1225 - 1320 (2701 - 2910)	1220 - 1300 (2690 - 2866)
1125 - 1250 (2480 - 2756)	1290 - 1415 (2844 - 3119)	1220 - 1305 (2690 - 2877)	1200 - 1270 (2646 - 2800)	1215 - 1280 (2679 - 2822)	1195 - 1280 (2634 - 2822)
2345 - 2540 (5170 - 5600), 2350 - 2545 (5181 - 5611)*1	2600 - 2750 (5732 - 6023)	2450 - 2665 (5401 - 5875)	2425 - 2570 (5346 - 5666)	2440 - 2600 (5379 - 5732)	2415 - 2580 (5324 - 5688)
1320 (2910), 1380 (3042)*1	1415 (3119)	1435 (3164)	1360 (2998)	1380 (3042)	1350 (2976)
1940 (4277), 1920 (4233)*1	1885 (4156)	1865 (4112)	1900 (4189)	1920 (4233)	1910 (4211)
3260 (7187), 3300 (7275)*1	3300 (7275)	3300 (7275)	3260 (7187)	3300 (7275)	3260 (7187)
138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)
—	0.259 (9.1)	0.259 (9.1)	0.060 (2.1)	0.259 (9.1)	0.060 (2.1)
—	200	190	190	200	200
—	200	190	190	200	200
—	9.5	10.7	10.7	11.0	11.0
—	16.9	17.6	17.6	17.6	17.8
—	57	56	56	56	43
—	98	96	96	96	78
—	143	140	140	140	130
—	200	190	190	200	193
—	200	190	190	200	200
—	—	—	—	—	—
—	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)
—	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)
1GR-FE	2UZ-FE	1GR-FE	1GR-FE	1GR-FE	1GR-FE
6-cylinder, V Type	8-cylinder, V Type	6-cylinder, V Type	6-cylinder, V Type	6-cylinder, V Type	6-cylinder, V Type
24-valve, DOHC with VVT-i	32-valve, DOHC with VVT-i	24-valve, DOHC with VVT-i	24-valve, DOHC with VVT-i	24-valve, DOHC with VVT-i	24-valve, DOHC with VVT-i
94.0 × 95.0 (3.70 × 3.74)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)
3956 (241.4)	4664 (284.5)	3956 (241.4)	3956 (241.4)	3956 (241.4)	3956 (241.4)
10.0 : 1	10.0 : 1	10.0 : 1	10.0 : 1	10.0 : 1	10.0 : 1
SFI	SFI	SFI	SFI	SFI	SFI
95 or higher	91 or higher	95 or higher	95 or higher	95 or higher	95 or higher
179@5200*2	202@5400	179@5200*2	179@5200*2	179@5200*2	179@5200*2
376@3800*2	410@3400	376@3800*2	376@3800*2	376@3800*2	376@3800*2
12 - 55	12 - 55	12 - 58*6, 12 - 59*6	12 - 58*6, 12 - 59*6	12 - 58*6, 12 - 59*6	12 - 58*6, 12 - 59*6
1200	1560, 1800*3	1200	1200	1200	1200
1.4	1.4	1.4	1.4	1.4	1.4
Dry, Single Plate, Diaphragm	—	—	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
H150F	A750F	A750F	A750F	H150F	H150F
4.529	3.520	3.520	3.520	4.529	4.529
2.464	2.042	2.042	2.042	2.464	2.464
1.490	1.400	1.400	1.400	1.490	1.490
1.000	1.000	1.000	1.000	1.000	1.000
0.881	0.716	0.716	0.716	0.881	0.881
—	—	—	—	—	—
4.313	3.224	3.224	3.224	4.313	4.313
1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
4.100/4.100	4.100/4.100	4.100/4.100	4.100/4.100	4.100/4.100	4.100/4.100
220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
16.7	16.7	16.7	16.7	16.7	16.7
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic

Item \ Area				G.C.C. Countries			
Body Type				Station Wagon (Lift-up/8-seater)	Station Wagon (Lift-up/9-seater)	Station Wagon (Lift-up/8-seater)	Station Wagon (Swing/9-seater, 10-seater*1)
Vehicle Grade				GX			Standard
Model Code				VDJ200L-GNMNZV	VDJ200L-GPMNZV	VDJ200L-GNTNZV	VDJ200L-GDMRZV
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4950 (194.9)	4950 (194.9)	4950 (194.9)	—
		Width	mm (in.)	1970 (77.6)	1970 (77.6)	1970 (77.6)	—
		Height	mm (in.)	1890 (74.3)	1890 (74.3)	1890 (74.3)	—
	Wheel Base		mm (in.)	2850 (112.2)	2850 (112.2)	2850 (112.2)	—
	Tread	Front	mm (in.)	1680 (66.1)	1680 (66.1)	1680 (66.1)	—
		Rear	mm (in.)	1675 (65.9)	1675 (65.9)	1675 (65.9)	—
	Room	Length	mm (in.)	2715 (106.8)	2905 (114.4)	2715 (106.8)	—
		Width	mm (in.)	1640 (64.5)	1640 (64.5)	1640 (64.5)	—
		Height	mm (in.)	1200 (47.2)	1200 (47.2)	1200 (47.2)	—
	Overhang	Front	mm (in.)	930 (36.6)	930 (36.6)	930 (36.6)	—
		Rear	mm (in.)	1170 (46.1)	1170 (46.1)	1170 (46.1)	—
	Min. Running Ground Clearance		mm (in.)	225 (8.9)	225 (8.9)	225 (8.9)	—
	Angle of Approach		degrees	30	30	30	—
	Angle of Departure		degrees	20	20	20	—
	Curb Weight	Front	kg (lb)	1390 - 1480 (3064 - 3263)	1400 - 1405 (3087 - 3097)	1400 - 1490 (3086 - 3285)	1420 - 1430 (3131 - 3153)
		Rear	kg (lb)	1215 - 1270 (2679 - 2800)	1200 - 1255 (2645 - 2767)	1215 - 1260 (2679 - 2778)	1190 - 1260 (2623 - 2778)
		Total	kg (lb)	2605 - 2750 (5743 - 6063)	2600 - 2660 (5732 - 5864)	2615 - 2750 (5765 - 6063)	2610 - 2690 (5754 - 5930)
	Gross Vehicle Weight	Front	kg (lb)	1565 (3450)	1460 (3219)	1575 (3472)	1550 (3417)
		Rear	kg (lb)	1785 (3935)	1840 (4056)	1775 (3913)	1800 (3968)
		Total	kg (lb)	3350 (7385)	3300 (7275)	3350 (7385)	3350 (7385)
	Fuel Tank Capacity		L (US.gal, Imp.gal)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)
	Luggage Capacity (VDA)		m^3 (cu.ft.)	0.259 (9.1)	0.060 (2.1)	0.259 (9.1)	—
Performance	Max. Speed		km/h	170	170	210	—
	Max. Cruising Speed		km/h	170	170	210	—
	Acceleration	0 to 100 km/h	sec.	12.0	12.0	8.6	—
		0 to 400 m	sec.	18.2	18.2	16.2	—
	Max. Permissible Speed	1st Gear	km/h	35	35	51	—
		2nd Gear	km/h	64	64	86	—
		3rd Gear	km/h	106	106	125	—
		4th Gear	km/h	158	158	169	—
		5th Gear	km/h	170	170	210	—
		6th Gear	km/h	—	—	210	—
	Min. Turning Radius	Tire	m (ft.)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	—
		Body	m (ft.)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	—
Engine	Engine Type			1VD-FTV	1VD-FTV	1VD-FTV	1VD-FTV
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve, DOHC	32-valve, DOHC	32-valve, DOHC	32-valve, DOHC
	Bore × Stroke		mm (in.)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)
	Displacement		cm^3 (cu.in.)	4461 (272.2)	4461 (272.2)	4461 (272.2)	4461 (272.2)
	Compression Ratio			16.8 : 1	16.8 : 1	16.8 : 1	16.8 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Octane Rating or Cetane Number (Diesel)			50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher
	Max. Output (SAE)		kW@rpm	162@3600*2	162@3600*2	173@3200*2	162@3600*2
	Max. Torque (SAE)		N·m@rpm	430@1200 - 3600*2	430@1200 - 3600*2	615@1800 - 2200*2	430@1200 - 3600*2
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 116*3, 12 - 118*3	12 - 116*3, 12 - 118*3	12 - 116*3, 12 - 118*3	12 - 116*3, 12 - 118*3
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	2.7	2.7	2.7	2.7
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm
	Transmission Type			H150F	H150F	AB60F	H150F
	Gear Ratio	In 1st		4.529	4.529	3.333	4.529
		In 2nd		2.464	2.464	1.960	2.464
		In 3rd		1.490	1.490	1.353	1.490
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.881	0.881	0.728	0.881
		In 6th		—	—	0.588	—
		In Reverse		4.313	4.313	3.061	4.313
	Transfer Gear Ratio		H4/L4	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
	Differential Gear Ratio (Front/Rear)			3.909/3.909	3.909/3.909	3.909/3.909	3.909/3.909
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio			16.7	16.7	16.7	16.7
	Power Steering Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic

*1: Models with bench type front passenger seat
*2: ECE
*3: Either is selectable

G.C.C. Countries					
Station Wagon (Lift-up/8-seater)			Station Wagon (Swing/9-seater)	Station Wagon (Swing/9-seater, 10-seater*1)	Station Wagon (Swing/9-seater)
GX	VX		GX	Standard	GX
UZJ200L-GNANKV	UZJ200L-GNAEKV	URJ200L-GNTEKV	GRJ200L-KDMNKV	GRJ200L-KDMRKV	VDJ200L-KDMNZV
4950 (194.9)	4950 (194.9)	4950 (194.9)	—	—	—
1970 (77.6)	1970 (77.6)	1970 (77.6)	—	—	—
1890 (74.3)	1890 (74.3)	1890 (74.3)	—	—	—
2850 (112.2)	2850 (112.2)	2850 (112.2)	—	—	—
1680 (66.1)	1640 (64.5)	1640 (64.5)	—	—	—
1675 (65.9)	1635 (64.3)	1635 (64.3)	—	—	—
2715 (106.8)	2715 (106.8)	2715 (106.8)	—	—	—
1640 (64.5)	1640 (64.5)	1640 (64.5)	—	—	—
1200 (47.2)	1200 (47.2)	1200 (47.2)	—	—	—
930 (36.6)	930 (36.6)	930 (36.6)	—	—	—
1170 (46.1)	1170 (46.1)	1170 (46.1)	—	—	—
225 (8.9)	225 (8.9)	225 (8.9)	—	—	—
30	30	30	—	—	—
20	20	20	—	—	—
1285 - 1370 (2833 - 3020)	1295 - 1320 (2855 - 2910)	1310 - 1360 (2888 - 2998)	1210 - 1310 (2668 - 2888)	1210 - 1290 (2668 - 2844), 1215 - 1295 (2679 - 2855)*1	1420 - 1445 (3131 - 3186)
1245 - 1345 (2745 - 2965)	1270 - 1390 (2800- 3064)	1280 - 1380 (2822 - 3042)	1170 - 1260 (2579 - 2778)	1180 - 1230 (2601 - 2712)	1175 - 1285 (2590 - 2833)
2530 - 2715 (5578 - 5985)	2565 - 2710 (5655 - 5974)	2590 - 2740 (5710 - 6041)	2380 - 2570 (5247 - 5666)	2390 - 2520 (5269 - 5556), 2395 - 2525 (5280 - 5567)*1	2595 - 2730 (5721 - 6019)
1440 (3175)	1390 (3064)	1440 (3175)	1350 (2976)	1315 (2899), 1375 (3031)*1	1500 (3307)
1860 (4100)	1910 (4211)	1910 (4211)	1910 (4211)	1945 (4288), 1925 (4244)*1	1850 (4079)
3300 (7275)	3300 (7275)	3350 (7385)	3260 (7187)	3260 (7187), 3300 (7275)*1	3350 (7385)
138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)
0.259 (9.1)	0.259 (9.1)	0.259 (9.1)	—	—	—
200	200	210	—	—	—
200	200	210	—	—	—
9.5	9.5	7.8	—	—	—
16.9	16.9	15.8	—	—	—
57	57	66	—	—	—
98	98	113	—	—	—
143	143	164	—	—	—
200	200	210	—	—	—
200	200	210	—	—	—
—	—	210	—	—	—
5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	—	—	—
6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	—	—	—
2UZ-FE	2UZ-FE	3UR-FE	1GR-FE	1GR-FE	1VD-FTV
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	6-cylinder, V Type	6-cylinder, V Type	8-cylinder, V Type
32-valve, DOHC with VVT-i	32-valve, DOHC with VVT-i	32-valve, DOHC with Dual VVT-i	24-valve, DOHC with VVT-i	24-valve, DOHC with VVT-i	32-valve, DOHC
94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	86.0 × 96.0 (3.39 × 3.78)
4664 (284.5)	4664 (284.5)	5663 (345.6)	3956 (241.4)	3956 (241.4)	4461 (272.2)
10.0 : 1	10.0 : 1	10.2 : 1	10.0 : 1	10.0 : 1	16.8 : 1
SFI	SFI	SFI	SFI	SFI	Common-rail Type
91 or higher	91 or higher	91 or higher	95 or higher	95 or higher	50 (Cetane Index 45) or higher
202@5400	202@5400	270@5600	179@5200*2	179@5200*2	136@3200
410@3400	410@3400	530@3200	376@3800*2	376@3800*2	430@1600 - 3000
12 - 58*3, 12 - 59*3	12 - 58*3, 12 - 59*3	12 - 58*3, 12 - 59*3	12 - 58*3, 12 - 59*3	12 - 58*3, 12 - 59*3	12 - 116*3, 12 - 118*3
1800	1800	2160	1200	1200	1560
1.4	1.4	2.0	1.4	1.4	2.7
—	—	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
A750F	A750F	AB60F	H150F	H150F	H150F
3.520	3.520	3.333	4.529	4.529	4.529
2.042	2.042	1.960	2.464	2.464	2.464
1.400	1.400	1.353	1.490	1.490	1.490
1.000	1.000	1.000	1.000	1.000	1.000
0.716	0.716	0.728	0.881	0.881	0.881
—	—	0.588	—	—	—
3.224	3.224	3.061	4.313	4.313	4.313
1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
4.100/4.100	4.100/4.100	3.909/3.909	4.100/4.100	4.100/4.100	4.100/4.100
220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
16.7	16.7	16.7	16.7	16.7	16.7
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic

Item / Area				G.C.C. Countries	Australia		
Body Type				Station Wagon (Swing/9-seater, 10-seater*3)	Station Wagon (Lift-up/8-seater)	Station Wagon (Lift-up/7-seater*6, 8-seater)	Station Wagon (Lift-up/8-seater)
Vehicle Grade				Standard	GX	VX	GX
Model Code				VDJ200L-KDMRZV	VDJ200R-GNTNZQ	VDJ200R-GNTEZQ	UZJ200R-GNANKQ
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	—	4950 (194.9)	4950 (194.9)	4950 (194.9)
		Width	mm (in.)	—	1970 (77.6)	1970 (77.6)	1970 (77.6)
		Height	mm (in.)	—	1965 (77.3)	1905 (74.9)	1905 (74.9)
	Wheel Base		mm (in.)	—	2850 (112.2)	2850 (112.2)	2850 (112.2)
	Tread	Front	mm (in.)	—	1680 (66.1)	1640 (64.5)	1680 (66.1)
		Rear	mm (in.)	—	1675 (65.9)	1635 (64.3)	1675 (65.9)
	Room	Length	mm (in.)	—	2715 (106.8)	2715 (106.8)	2715 (106.8)
		Width	mm (in.)	—	1640 (64.5)	1640 (64.5)	1640 (64.5)
		Height	mm (in.)	—	1200 (47.2)	1200 (47.2)	1200 (47.2)
	Overhang	Front	mm (in.)	—	930 (36.6)	930 (36.6)	930 (36.6)
		Rear	mm (in.)	—	1170 (46.1)	1170 (46.1)	1170 (46.1)
	Min. Running Ground Clearance		mm (in.)	—	225 (8.9)	225 (8.9)	225 (8.9)
	Angle of Approach		degrees	—	30	30	30
	Angle of Departure		degrees	—	20	20	20
	Curb Weight	Front	kg (lb)	1420 (3131), 1425 (3142)*3	1410 - 1480 (3109 - 3263)	1460 - 1510 (3219 - 3329)	1300 - 1340 (2866 - 2954)
		Rear	kg (lb)	1190 - 1255 (2623 - 2767)	1220 - 1250 (2690 - 2756)	1245 - 1240 (2745 - 2734)	1255 - 1295 (2767 - 2855)
		Total	kg (lb)	2610 - 2675 (5754 - 5897), 2615 - 2680 (5765 - 5908)*3	2630 - 2730 (5798 - 6019)	2705 - 2750 (5963 - 6063)	2555 - 2635 (5633 - 5809)
	Gross Vehicle Weight	Front	kg (lb)	1465 (3230), 1530 (3373)*3	1560 (3439)	1580 (3483)*6, 1595 (3516)	1390 (3064)
		Rear	kg (lb)	1885 (4156), 1820 (4012)*3	1790 (3946)	1770 (3902)*6, 1755 (3869)	1910 (4211)
		Total	kg (lb)	3350 (7385)	3350 (7385)	3350 (7385)	3300 (7275)
	Fuel Tank Capacity		L (US.gal, Imp.gal)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4), 93 (24.6, 20.5)*1	138 (36.5, 30.4)
	Luggage Capacity (VDA)		m^3 (cu.ft.)	—	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)
Performance	Max. Speed		km/h	—	210	210	200
	Max. Cruising Speed		km/h	—	210	210	200
	Acceleration	0 to 100 km/h	sec.	—	8.6	8.6	9.5
		0 to 400 m	sec.	—	16.2	16.2	16.9
	Max. Permissible Speed	1st Gear	km/h	—	51	51	57
		2nd Gear	km/h	—	86	86	98
		3rd Gear	km/h	—	125	125	143
		4th Gear	km/h	—	169	169	200
		5th Gear	km/h	—	210	210	200
		6th Gear	km/h	—	210	210	—
	Min. Turning Radius	Tire	m (ft.)	—	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)
		Body	m (ft.)	—	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)
Engine	Engine Type			1VD-FTV	1VD-FTV	1VD-FTV	2UZ-FE
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve, DOHC	32-valve, DOHC	32-valve, DOHC	32-valve, DOHC with VVT-i
	Bore × Stroke		mm (in.)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	94.0 × 84.0 (3.70 × 3.31)
	Displacement		cm^3 (cu.in.)	4461 (272.2)	4461 (272.2)	4461 (272.2)	4664 (284.5)
	Compression Ratio			16.8 : 1	16.8 : 1	16.8 : 1	10.0 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	SFI
	Octane Rating or Cetane Number (Diesel)			50 (Cetane Index 45) or higher	50 (Cetane Index 45) or higher	50 or higher	91 or higher
	Max. Output (SAE)		kW@rpm	136@3200	195@3400*2	195@3400*2	202@5400
	Max. Torque (SAE)		N·m@rpm	430@1600 - 3000	650@1600 - 2600*2	650@1600 - 2600*2	410@3400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 116*8, 12 - 118*8	12 - 110	12 - 110	12 - 55
	Alternator Output		Watts	1560	1800	1800	1560
	Starter Output		kW	2.7	2.7	2.7	1.4
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	—	—	—
	Transmission Type			H150F	AB60F	AB60F	A750F
	Gear Ratio	In 1st		4.529	3.333	3.333	3.520
		In 2nd		2.464	1.960	1.960	2.042
		In 3rd		1.490	1.353	1.353	1.400
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.881	0.728	0.728	0.716
		In 6th		—	0.588	0.588	—
		In Reverse		4.313	3.061	3.061	3.224
	Transfer Gear Ratio		H4/L4	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
	Differential Gear Ratio (Front/Rear)			4.100/4.100	3.909/3.909	3.909/3.909	4.100/4.100
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio			16.7	16.7	16.7	16.7
	Power Steering Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic

*1: Option
*2: ECE
*3: 9-passenger model
*4: Cold area specification models
*5: Models with towing package
*6: Models with rear No. 2 seat for 2 passengers
*7: Models with VGRS
*8: Either is selectable
*9: Cold area specification models or models with inclination sensor

Australia		Europe			
Station Wagon (Lift-up/8-seater)	Station Wagon (Swing/5-seater)	Station Wagon (Lift-up/7-seater)	Station Wagon (Lift-up/5-seater)	Station Wagon (Lift-up/7-seater)	
VX	Standard	VX			
UZJ200R-GNAEKQ	VDJ200R-KCTRZQ	UZJ200R-GNAEKW	UZJ200L-GMAEKW	UZJ200L-GNAEKW	VDJ200R-GNTEZW
4950 (194.9)	—	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)
1970 (77.6)	—	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
1905 (74.9)	—	1910 (75.2)	1910 (75.2)	1910 (75.2)	1910 (75.2)
2850 (112.2)	—	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
1640 (64.5)	—	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)
1635 (64.3)	—	1635 (64.3)	1635 (64.3)	1635 (64.3)	1635 (64.3)
2715 (106.8)	—	2715 (106.8)	1965 (77.4)	2715 (106.8)	2715 (106.8)
1640 (64.5)	—	1640 (64.5)	1615 (63.6)	1640 (64.5)	1640 (64.5)
1200 (47.2)	—	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
930 (36.6)	—	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
1170 (46.1)	—	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)
225 (8.9)	—	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)
30	—	30	30	30	30
20	—	20	20	20	20
1320 - 1340 (2910 - 2954)	1430 - 1435 (3153 - 3164)	1320 - 1380 (2911 - 3042)	1320 - 1380 (2909 - 3042)	1320 - 1380 (2911 - 3042)	1425 - 1480 (3142 - 3263)
1290 - 1325 (2844 - 2921)	1205 (2657)	1230 - 1310 (2711 - 2888)	1190 - 1270 (2623 - 2800)	1230 - 1310 (2711 - 2888)	1215 - 1270 (2679 - 2800)
2610 - 2665 (5754 - 5875)	2635 - 2640 (5809 - 5820)	2550 - 2690 (5622 - 5930)	2510 - 2650 (5533 - 5842)	2550 - 2690 (5622 - 5930)	2640 - 2750 (5820 - 6063)
1390 (3064)	1500 (3307)	1435 (3163)	1435 (3163)	1435 (3163)	1550 (3417)
1910 (4211)	1850 (4079)	1865 (4110)	1865 (4110)	1865 (4110)	1800 (3968)
3300 (7275)	3350 (7385)	3300 (7275)	3300 (7275)	3300 (7275)	3350 (7385)
138 (36.5, 30.4)	138 (36.5, 30.4)	93 (24.6, 20.5)	93 (24.6, 20.5)	93 (24.6, 20.5)	93 (24.6, 20.5)
0.259 (9.1)	—	0.259 (9.1)	0.909 (32.1)	0.259 (9.1)	0.259 (9.1)
200	—	200	200	200	210
200	—	200	200	200	210
9.5	—	9.5	9.5	9.5	8.6
16.9	—	16.9	16.9	16.9	16.2
57	—	57	57	57	51
98	—	98	98	98	86
143	—	143	143	143	125
200	—	200	200	200	169
200	—	200	200	200	210
—	—	—	—	—	210
5.9 (19.4)	—	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)
6.3 (20.7)	—	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)
2UZ-FE	1VD-FTV	2UZ-FE	2UZ-FE	2UZ-FE	1VD-FTV
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
32-valve, DOHC with VVT-i	32-valve, DOHC	32-valve, DOHC with VVT-i	32-valve, DOHC with VVT-i	32-valve, DOHC with VVT-i	32-valve, DOHC
94.0 × 84.0 (3.70 × 3.31)	86.0 × 96.0 (3.39 × 3.78)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)	86.0 × 96.0 (3.39 × 3.78)
4664 (284.5)	4461 (272.2)	4664 (284.5)	4664 (284.5)	4664 (284.5)	4461 (272.2)
10.0 : 1	16.8 : 1	10.0 : 1	10.0 : 1	10.0 : 1	16.8 : 1
SFI	Common-rail Type	SFI	SFI	SFI	Common-rail Type
91 or higher	50 (Cetane Index 45) or higher	95 or higher	95 or higher	95 or higher	48 or higher
202@5400	136@3200	212@5400	212@5400	212@5400	210@3600*2
410@3400	430@1600 - 3000	445@3400	445@3400	445@3400	650@1600 - 2800*2
12 - 55	12 - 110	12 - 64	12 - 55, 12 - 64*9	12 - 55, 12 - 64*9	12 - 110, 12 - 128*4
1560, 1800*1	1800	1800, 1560*5	1800, 1560*5	1800, 1560*5	2160
1.4	2.7	2.0	2.0	2.0	2.7
—	—	—	—	—	—
A750F	AB60F	A750F	A750F	A750F	AB60F
3.520	3.333	3.520	3.520	3.520	3.333
2.042	1.960	2.042	2.042	2.042	1.960
1.400	1.353	1.400	1.400	1.400	1.353
1.000	1.000	1.000	1.000	1.000	1.000
0.716	0.728	0.716	0.716	0.716	0.728
—	0.588	—	—	—	0.588
3.224	3.061	3.224	3.224	3.224	3.061
1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
4.100/4.100	3.909/3.909	4.100/4.100	4.100/4.100	4.100/4.100	3.909/3.909
220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
16.7	16.7	16.7, 14.2 - 17.6*7	16.7, 14.2 - 17.6*7	16.7, 14.2 - 17.6*7	16.7, 14.2 - 17.6*7
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic

Item \ Area				Europe		China	
Body Type				Station Wagon (Lift-up/5-seater)	Station Wagon (Lift-up/7-seater)	Station Wagon (Lift-up/8-seater)	
Vehicle Grade				VX		GX	
Model Code				VDJ200L-GMTEZW	VDJ200L-GNTEZW	GRJ200L-GNANKC	UZJ200L-GNANKC
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4950 (194.9)	4950 (194.9)	5100 (200.6)	4950 (194.9)
		Width	mm (in.)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
		Height	mm (in.)	1910 (75.2)	1910 (75.2)	1945 (76.5)	1840 (72.4)
	Wheel Base		mm (in.)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
	Tread	Front	mm (in.)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)
		Rear	mm (in.)	1635 (64.3)	1635 (64.3)	1635 (64.3)	1635 (64.3)
	Room	Length	mm (in.)	1965 (77.4)	2715 (106.8)	2715 (106.8)	2715 (106.8)
		Width	mm (in.)	1615 (63.6)	1640 (64.5)	1640 (64.5)	1640 (64.5)
		Height	mm (in.)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
	Overhang	Front	mm (in.)	930 (36.6)	930 (36.6)	920 (36.2)	920 (36.2)
		Rear	mm (in.)	1170 (46.1)	1170 (46.1)	1180 (46.5)	1180 (46.5)
	Min. Running Ground Clearance		mm (in.)	225 (8.9)	225 (8.9)	225 (8.9)	225 (8.9)
	Angle of Approach		degrees	30	30	30	30
	Angle of Departure		degrees	20	20	20	20
	Curb Weight	Front	kg (lb)	1430 - 1500 (3153 - 3307)	1425 - 1475 (3142 - 3252)	1255 - 1360 (2767 - 2998)	1340 - 1430 (2954 - 3153)
		Rear	kg (lb)	1175 - 1245 (2590 - 2745)	1215 - 1270 (2679 - 2800)	1285 (2833)	1280 - 1265 (2821 - 2788)
		Total	kg (lb)	2605 - 2745 (5743 - 6052)	2640 - 2745 (5820 - 6052)	2540 - 2645 (5600 - 5831)	2620 - 2695 (5775 - 5941)
	Gross Vehicle Weight	Front	kg (lb)	1580 (3483)	1545 (3406)	1430 (3153)	1495 (3296)
		Rear	kg (lb)	1770 (3902)	1805 (3979)	1870 (4123)	1805 (3979)
		Total	kg (lb)	3350 (7385)	3350 (7385)	3300 (7275)	3300 (7275)
	Fuel Tank Capacity		L (US.gal, Imp.gal)	93 (24.6, 20.5)	93 (24.6, 20.5)	138 (36.5, 30.4)	138 (36.5, 30.4)
	Luggage Capacity (VDA)		m^3 (cu.ft.)	0.909 (32.1)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)
Performance	Max. Speed		km/h	210	210	190	200
	Max. Cruising Speed		km/h	210	210	190	200
	Acceleration	0 to 100 km/h	sec.	8.6	8.6	10.7	9.5
		0 to 400 m	sec.	16.2	16.2	17.6	16.9
	Max. Permissible Speed	1st Gear	km/h	51	51	56	57
		2nd Gear	km/h	86	86	96	98
		3rd Gear	km/h	125	125	140	143
		4th Gear	km/h	169	169	190	200
		5th Gear	km/h	210	210	190	200
		6th Gear	km/h	210	210	—	—
	Min. Turning Radius	Tire	m (ft.)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)
		Body	m (ft.)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)
Engine	Engine Type			1VD-FTV	1VD-FTV	1GR-FE	2UZ-FE
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	6-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve, DOHC	32-valve, DOHC	24-valve, DOHC with VVT-i	32-valve, DOHC with VVT-i
	Bore × Stroke		mm (in.)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 84.0 (3.70 × 3.31)
	Displacement		cm^3 (cu.in.)	4461 (272.2)	4461 (272.2)	3956 (241.4)	4664 (284.5)
	Compression Ratio			16.8 : 1	16.8 : 1	10.0 : 1	10.0 : 1
	Fuel System			Common-rail Type	Common-rail Type	SFI	SFI
	Octane Rating or Cetane Number (Diesel)			48 or higher	48 or higher	95 or higher	91 or higher
	Max. Output (SAE)		kW@rpm	210@3600*1	210@3600*1	179@5200*1	202@5400
	Max. Torque (SAE)		N·m@rpm	650@1600 - 2800*1	650@1600 - 2800*1	376@3800*1	410@3400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 110, 12 - 128*2	12 - 110, 12 - 128*2	12 - 64	12 - 64
	Alternator Output		Watts	2160	2160	1200	1800
	Starter Output		kW	2.7	2.7	2.0	2.0
Chassis	Clutch Type			—	—	—	—
	Transmission Type			AB60F	AB60F	A750F	A750F
	Gear Ratio	In 1st		3.333	3.333	3.520	3.520
		In 2nd		1.960	1.960	2.042	2.042
		In 3rd		1.353	1.353	1.400	1.400
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.728	0.728	0.716	0.716
		In 6th		0.588	0.588	—	—
		In Reverse		3.061	3.061	3.224	3.224
	Transfer Gear Ratio		H4/L4	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
	Differential Gear Ratio (Front/Rear)			3.909/3.909	3.909/3.909	4.100/4.100	4.100/4.100
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)	220 (8.7)/240 (9.4)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio			16.7, 14.2 - 17.6*3	16.7, 14.2 - 17.6*3	16.7	16.7
	Power Steering Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic

*1: ECE
*2: Cold area specification models
*3: Models with VGRS

	China
	Station Wagon (Lift-up/8-seater)
	VX
	UZJ200L-GNAEKC
5	5100 (200.6)
	1970 (77.6)
	1945 (76.5)
	2850 (112.2)
	1640 (64.5)
10	1635 (64.3)
	2715 (106.8)
	1640 (64.5)
	1200 (47.2)
	920 (36.2)
15	1180 (46.5)
	225 (8.9)
	30
	20
	1355 - 1370 (2987 - 3020)
20	1295 (2855)
	2650 - 2665 (5842 - 5876)
	1425 (3141)
	1875 (4134)
	3300 (7275)
25	138 (36.5, 30.4)
	0.259 (9.1)
	200
	200
	9.5
30	16.9
	57
	98
	143
	200
35	200
	—
	5.9 (19.4)
	6.3 (20.7)
	2UZ-FE
40	8-cylinder, V Type
	32-valve, DOHC with VVT-i
	94.0 × 84.0 (3.70 × 3.31)
	4664 (284.5)
	10.0 : 1
45	SFI
	91 or higher
	202@5400
	410@3400
	12 - 64
50	1800
	2.0
	—
	A750F
	3.520
55	2.042
	1.400
	1.000
	0.716
	—
60	3.224
	1.000/2.618
	4.100/4.100
	220 (8.7)/240 (9.4)
	Ventilated Disc
65	Ventilated Disc
	Duo-servo Drum
	Hydraulic
	—
	Double-wishbone
70	4-link with Lateral Rod
	Standard
	Standard
	Rack and Pinion
	16.7
75	Hydraulic