MAJOR TECHNICAL SPECIFICATIONS

Item \ Area				General Countries			
Body Type				Station Wagon (Lift-up/8-seater)			Station Wagon (Swing/5-seater)
Vehicle Grade				GX			Standard
Model Code				VDJ200R-GNTNZ	VDJ200L-GNTNZ	VDJ200R-GNMNZ	VDJ200R-GCMRZ
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4950 (194.9)*7	4950 (194.9)*6, *7	4950 (194.9)*6, *7	4950 (194.9)*6, *7
		Width	mm (in.)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
		Height	mm (in.)	1905 (74.9)*8, *10	1905 (74.9)*8, *10	1905 (74.9)*8, *9, *10	1905 (74.9)*8, *9, *10
	Wheel Base		mm (in.)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
	Tread	Front	mm (in.)	1680 (66.1), 1640 (64.5)*5	1680 (66.1), 1640 (64.5)*5	1680 (66.1), 1640 (64.5)*5	1680 (66.1)
		Rear	mm (in.)	1675 (65.9), 1635 (64.3)*5	1675 (65.9), 1635 (64.3)*5	1675 (65.9), 1635 (64.3)*5	1675 (65.9)
	Room	Length	mm (in.)	2715 (106.8)	2715 (106.8)	2715 (106.8)	1965 (77.4)
		Width	mm (in.)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1615 (63.6)
		Height	mm (in.)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
	Overhang	Front	mm (in.)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
		Rear	mm (in.)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)
	Min. Running Ground Clearance		mm (in.)	225 (8.9)	225 (8.9)	225 (8.9)	—
	Angle of Approach		degrees	30	30	30	30
	Angle of Departure		degrees	20	20	20	—
	Curb Weight	Front	kg (lb)	1430 - 1515 (3153 - 3340), 1420 - 1505 (3131 - 3318)*3	1430 - 1515 (3153 - 3340), 1420 - 1505 (3131 - 3318)*3	1410 - 1495 (3109 - 3296), 1400 - 1485 (3086 - 3274)*3	1395 - 1470 (3075 - 3241), 1385 - 1460 (3053 - 3219)*3
		Rear	kg (lb)	1200 - 1240 (2646 - 2734), 1255 - 1295 (2767 - 2855)*3	1200 - 1240 (2646 - 2734), 1255 - 1295 (2767 - 2855)*3	1190 - 1210 (2623 - 2668), 1245 - 1265 (2745 - 2789)*3	1125 - 1205 (2480 - 2657), 1180 - 1260 (2601 - 2778)*3
		Total	kg (lb)	2630 - 2755 (5798 - 6074), 2675 - 2800 (5897 - 6173)*3	2630 - 2755 (5798 - 6074), 2675 - 2800 (5897 - 6173)*3	2600 - 2705 (5732 - 5963), 2645 - 2750 (5831 - 6063)*3	2520 - 2675 (5556 - 5897), 2565 - 2720 (5655 - 5997)*3
	Gross Vehicle Weight	Front	kg (lb)	1600 (3527)	1600 (3527)	1565 (3450), 1570 (3461)*3	1500 (3307)
		Rear	kg (lb)	1750 (3858)	1750 (3858)	1785 (3935), 1780 (3924)*3	1850 (4079)
		Total	kg (lb)	3350 (7385)	3350 (7385)	3350 (7385)	3350 (7385)
	Fuel Tank Capacity		L (US.gal, Imp. gal)	93 (24.6, 20.5), 138 (36.5, 30.4)*1	93 (24.6, 20.5), 138 (36.5, 30.4)*1	93 (24.6, 20.5), 138 (36.5, 30.4)*1	138 (36.5, 30.4)
	Luggage Capacity (VDA)		m^3 (cu.ft.)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)	0.909 (32.1)
Performance	Max. Speed		km/h	210	210	170	170
	Max. Cruising Speed		km/h	210	210	170	—
	Acceleration	0 to 100 km/h	sec.	8.6	8.6	12.0	—
		0 to 400 m	sec.	16.2	16.2	18.2	—
	Max. Permissible Speed	1st Gear	km/h	51	51	35	—
		2nd Gear	km/h	86	86	64	—
		3rd Gear	km/h	125	125	106	—
		4th Gear	km/h	169	169	158	—
		5th Gear	km/h	210	210	170	—
		6th Gear	km/h	210	210	—	—
	Min. Turning Radius	Tire	m (ft.)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	—
		Body	m (ft.)	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	—
Engine	Engine Type			1VD-FTV	1VD-FTV	1VD-FTV	1VD-FTV
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve, DOHC	32-valve, DOHC	32-valve, DOHC	32-valve, DOHC
	Bore × Stroke		mm (in.)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)
	Displacement		cm^3 (cu.in.)	4461 (272.2)	4461 (272.2)	4461 (272.2)	4461 (272.2)
	Compression Ratio			16.8 : 1	16.8 : 1	16.8 : 1	16.8 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Cetane Number			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output		kW@rpm	173@3200*2	173@3200*2	162@3600*2	136@3200
	Max. Torque		N·m@rpm	615@1800 - 2200*2	615@1800 - 2200*2	430@1200 - 3600*2	430@1600 - 3000
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 110	12 - 110	12 - 110	12 - 110
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	2.7	2.7	2.7	2.7
Chassis	Clutch Type			—	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			AB60F	AB60F	H150F	H150F
	Gear Ratio	In 1st		3.333	3.333	4.529	4.529
		In 2nd		1.960	1.960	2.464	2.464
		In 3rd		1.353	1.353	1.490	1.490
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.728	0.728	0.881	0.881
		In 6th		0.588	0.588	—	—
		In Reverse		3.061	3.061	4.313	4.313
	Transfer Gear Ratio		H4/L4	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
	Differential Gear Ratio (Front/Rear)			3.909/3.909	3.909/3.909	3.909/3.909	3.909/3.909
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio			16.7	16.7	16.7	16.7
	Power Steering Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic

*1: Option
*2: ECE
*3: Models with sub fuel tank
*4: Models with bench type front passenger seat
*5: Models with 285 mm width tires
*6: Models with winch assembly: + 55 mm (2.2 in.)
*7: Models with pintle hook assembly: + 145 mm (5.7 in.)
*8: Models with roof side rail: + 40 mm (1.6 in.)
*9: Models with roof rack: + 235 mm (9.3 in.)

General Countries					
Station Wagon (Swing/9-seater, 10-seater*4)	Station Wagon (Lift-up/5-seater)	Station Wagon (Lift-up/8-seater)	Station Wagon (Swing/5-seater)	Station Wagon (Swing/9-seater, 10-seater*4)	Station Wagon (Lift-up/8-seater)
Standard	GX		Standard		VX
VDJ200R-GDMRZ	VDJ200L-GMMNZ	VDJ200L-GNMNZ	VDJ200L-GCMRZ	VDJ200L-GDMRZ	VDJ200R-GNTEZ
4950 (194.9)*6, *7	4950 (194.9)*6, *7	4950 (194.9)*6, *7	4950 (194.9)*6, *7	4950 (194.9)*6, *7	4950 (194.9)*6, *7
1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
1905 (74.9)*8, *9, *10	1905 (74.9)*8, *9, *10	1905 (74.9)*8, *9, *10	1905 (74.9)*8, *9, *10	1905 (74.9)*8, *9, *10	1905 (74.9)*8, *9, *10
2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
1680 (66.1)	1680 (66.1), 1640 (64.5)*5	1680 (66.1), 1640 (64.5)*5	1680 (66.1)	1680 (66.1)	1640 (64.5)
1675 (65.9)	1675 (65.9), 1635 (64.3)*5	1675 (65.9), 1635 (64.3)*5	1675 (65.9)	1675 (65.9)	1635 (64.3)
2905 (114.4)	1965 (77.4)	2715 (106.8)	1965 (77.4)	2905 (114.4)	2715 (106.8)
1640 (64.5)	1615 (63.6)	1640 (64.5)	1615 (63.6)	1640 (64.5)	1640 (64.5)
1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)
—	225 (8.9)	225 (8.9)	—	—	225 (8.9)
30	30	30	30	30	30
—	20	20	—	—	20
1395 - 1480 (3075 - 3263), 1385 - 1470 (3053 - 3241)*3	1410 - 1500 (3109 - 3307)	1400 - 1500 (3086 - 3307), 1390 - 1490 (3064 - 3285)*3	1395 - 1470 (3075 - 3241)	1395 - 1465 (3075 - 3230)	1425 - 1460 (3142 - 3219), 1415 - 1450 (3120 - 3197)*3
1150 - 1220 (2535 - 2690), 1205 - 1265 (2657 - 2789)*3	1140 - 1215 (2513 - 2679)	1175 - 1205 (2590 - 2657), 1230 - 1260 (2712 - 2778)*3	1125 - 1250 (2480 - 2756)	1145 - 1245 (2524 - 2745)	1195 - 1295 (2635 - 2855), 1250 - 1350 (2756 - 2976)*3
2545 - 2700 (5611 - 5952), 2590 - 2735 (5710 - 6030)*3	2550 - 2715 (5622 - 5986)	2575 - 2705 (5677 - 5963), 2620 - 2750 (5776 - 6063)*3	2520 - 2720 (5556 - 5997)	2540 - 2710 (5600 - 5975)	2620 - 2755 (5776 - 6074), 2665 - 2800 (5875 - 6173)*3
1610 (3549)	1575 (3472)	1570 (3461), 1575 (3472)*3	1540 (3395)	1590 (3505)	1545 (3406)
1740 (3836)	1775 (3913)	1780 (3924), 1775 (3913)*3	1810 (3990)	1760 (3880)	1805 (3979)
3350 (7385)	3350 (7385)	3350 (7385)	3350 (7385)	3350 (7385)	3350 (7385)
93 (24.6, 20.5), 138 (36.5, 30.4)*1	138 (36.5, 30.4)	93 (24.6, 20.5), 138 (36.5, 30.4)*1	138 (36.5, 30.4)	93 (24.6, 20.5), 138 (36.5, 30.4)*1	93 (24.6, 20.5), 138 (36.5, 30.4)*1
0.060 (2.1)	0.909 (32.1)	0.259 (9.1)	0.909 (32.1)	0.060 (2.1)	0.259 (9.1)
170	170	170	170	170	210
—	170	170	—	—	210
—	12.0	12.0	—	—	8.6
—	18.2	18.2	—	—	16.2
—	35	35	—	—	51
—	64	64	—	—	86
—	106	106	—	—	125
—	158	158	—	—	169
—	170	170	—	—	210
—	—	—	—	—	210
—	5.9 (19.4)	5.9 (19.4)	—	—	5.9 (19.4)
—	6.3 (20.7)	6.3 (20.7)	—	—	6.3 (20.7)
1VD-FTV	1VD-FTV	1VD-FTV	1VD-FTV	1VD-FTV	1VD-FTV
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
32-valve, DOHC	32-valve, DOHC	32-valve, DOHC	32-valve, DOHC	32-valve, DOHC	32-valve, DOHC
86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)
4461 (272.2)	4461 (272.2)	4461 (272.2)	4461 (272.2)	4461 (272.2)	4461 (272.2)
16.8 : 1	16.8 : 1	16.8 : 1	16.8 : 1	16.8 : 1	16.8 : 1
Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
48 or higher	48 or higher	48 or higher	48 or higher	48 or higher	48 or higher
136@3200	162@3600*2	162@3600*2	136@3200	136@3200	173@3200*2
430@1600 - 3000	430@1200 - 3600*2	430@1200 - 3600*2	430@1600 - 3000	430@1600 - 3000	615@1800 - 2200*2
12 - 110	12 - 110	12 - 110	12 - 110	12 - 110	12 - 110
1560	1560	1560	1560	1560	1800
2.7	2.7	2.7	2.7	2.7	2.7
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—
H150F	H150F	H150F	H150F	H150F	AB60F
4.529	4.529	4.529	4.529	4.529	3.333
2.464	2.464	2.464	2.464	2.464	1.960
1.490	1.490	1.490	1.490	1.490	1.353
1.000	1.000	1.000	1.000	1.000	1.000
0.881	0.881	0.881	0.881	0.881	0.728
—	—	—	—	—	0.588
4.313	4.313	4.313	4.313	4.313	3.061
1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
3.909/3.909	3.909/3.909	3.909/3.909	3.909/3.909	3.909/3.909	3.909/3.909
220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
16.7	16.7	16.7	16.7	16.7	16.7
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic

*10: Models with snorkel: + 65 mm (2.6 in.)

AP

Item \ Area				General Countries			
Body Type				Station Wagon (Lift-up/8-seater)	Station Wagon (Swing/9-seater, 10-seater*5)	Station Wagon (Lift-up/8-seater)	Station Wagon (Swing/5-seater)
Vehicle Grade				VX	Standard	GX	Standard
Model Code				VDJ200L-GNTEZ	GRJ200R-GDMRK	GRJ200L-GNMNK	GRJ200L-GCMRK
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4950 (194.9)*9, *10	4950 (194.9)*10	4950 (194.9)*8, *10	4950 (194.9)*8, *10
		Width	mm (in.)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
		Height	mm (in.)	1905 (74.9)*11, *12, *13	1905 (74.9)*11, *12	1905 (74.9)*11, *12	1905 (74.9)*11, *12
	Wheel Base		mm (in.)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
	Tread	Front	mm (in.)	1640 (64.5)	1680 (66.1)	1680 (66.1), 1640 (64.5)*7	1680 (66.1)
		Rear	mm (in.)	1635 (64.3)	1675 (65.9)	1675 (65.9), 1635 (64.3)*7	1675 (65.9)
	Room	Length	mm (in.)	2715 (106.8)	2905 (114.4)	2715 (106.8)	1965 (77.4)
		Width	mm (in.)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1615 (63.6)
		Height	mm (in.)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
	Overhang	Front	mm (in.)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
		Rear	mm (in.)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)
	Min. Running Ground Clearance		mm (in.)	225 (8.9)	—	225 (8.9)	—
	Angle of Approach		degrees	30	30	30	30
	Angle of Departure		degrees	20	—	20	—
	Curb Weight	Front	kg (lb)	1425 - 1460 (3142 - 3219), 1415 - 1450 (3120 - 3197)*3	1230 (2712)	1240 - 1335 (2734 - 2943)	1235 - 1305 (2723 - 2877)
		Rear	kg (lb)	1195 - 1295 (2635 - 2855), 1250 - 1350 (2756 - 2976)*3	1125 - 1275 (2480 - 2811)	1165 - 1260 (2568 - 2778)	1105 - 1235 (2436 - 2723)
		Total	kg (lb)	2620 - 2755 (5776 - 6074), 2665 - 2800 (5875 - 6173)*3	2355 - 2505 (5192 - 5523)	2405 - 2595 (5302 - 5721)	2340 - 2540 (5159 - 5600)
	Gross Vehicle Weight	Front	kg (lb)	1545 (3406)	1335 (2943)	1390 (3064)	1365 (3009)
		Rear	kg (lb)	1805 (3979)	1925 (4244)	1910 (4211)	1895 (4178)
		Total	kg (lb)	3350 (7385)	3260 (7187)	3300 (7275)	3260 (7187)
	Fuel Tank Capacity		L (US.gal, Imp. gal)	93 (24.6, 20.5), 138 (36.5, 30.4)*1	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)
	Luggage Capacity (VDA)		m^3 (cu.ft.)	0.259 (9.1)	0.060 (2.1)	0.259 (9.1)	0.909 (32.1)
Performance	Max. Speed		km/h	210	200	200	200
	Max. Cruising Speed		km/h	210	—	200	—
	Acceleration	0 to 100 km/h	sec.	8.6	—	11.0	—
		0 to 400 m	sec.	16.2	—	17.8	—
	Max. Permissible Speed	1st Gear	km/h	51	—	43	—
		2nd Gear	km/h	86	—	78	—
		3rd Gear	km/h	125	—	130	—
		4th Gear	km/h	169	—	193	—
		5th Gear	km/h	210	—	200	—
		6th Gear	km/h	210	—	—	—
	Min. Turning Radius	Tire	m (ft.)	5.9 (19.4)	—	5.9 (19.4)	—
		Body	m (ft.)	6.3 (20.7)	—	6.3 (20.7)	—
Engine	Engine Type			1VD-FTV	1GR-FE	1GR-FE	1GR-FE
	No. of Cyls. & Arrangement			8-cylinder, V Type	6-cylinder, V Type	6-cylinder, V Type	6-cylinder, V Type
	Valve Mechanism			32-valve, DOHC	24-valve DOHC, Chain Drive (with Dual VVT-i)	24-valve DOHC, Chain Drive (with Dual VVT-i)	24-valve DOHC, Chain Drive (with Dual VVT-i)
	Bore × Stroke		mm (in.)	86.0 × 96.0 (3.39 × 3.78)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)
	Displacement		cm^3 (cu.in.)	4461 (272.2)	3956 (241.4)	3956 (241.4)	3956 (241.4)
	Compression Ratio			16.8 : 1	10.4 : 1	10.4 : 1	10.4 : 1
	Fuel System			Common-rail Type	EFI	EFI	EFI
	Research Octane No. (RON) or Cetane Number (Diesel)			48 or higher	95 or higher	95 or higher	95 or higher
	Max. Output		kW@rpm	173@3200*2, 195@3400*14	202@5600*2	202@5600*2	202@5600*2
	Max. Torque		N·m@rpm	615@1800 - 2200*2, 650@1600 - 2600*14	385@4400*2	385@4400*2	385@4400*2
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 110	12 - 55	12 - 55	12 - 55
	Alternator Output		Watts	1800	1200	1200	1200
	Starter Output		kW	2.7	1.4	1.4	1.4
Chassis	Clutch Type			—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			AB60F	H150F	H150F	H150F
	Gear Ratio	In 1st		3.333	4.529	4.529	4.529
		In 2nd		1.960	2.464	2.464	2.464
		In 3rd		1.353	1.490	1.490	1.490
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.728	0.881	0.881	0.881
		In 6th		0.588	—	—	—
		In Reverse		3.061	4.313	4.313	4.313
	Transfer Gear Ratio		H4/L4	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
	Differential Gear Ratio (Front/Rear)			3.909/3.909	4.300/4.300	4.300/4.300	4.300/4.300
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio			16.7	16.7	16.7	16.7
	Power Steering Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic

*1: Option
*2: EEC-NET
*3: Models with sub fuel tank
*4: Towing Package
*5: Models with bench type front passenger seat
*6: Models with VGRS
*7: Models with 285 mm width tires
*8: Models with winch assembly: + 55 mm (2.2 in.)
*9: Models with front bumper guard: + 75 mm (3.0 in.)

General Countries		G.C.C. Countries			
Station Wagon (Swing/9-seater, 10-seater*5)	Station Wagon (Lift-up/8-seater)	Station Wagon (Lift-up/9-seater)	Station Wagon (Lift-up/8-seater)	Station Wagon (Swing/9-seater)	
Standard	VX	GX			
GRJ200L-GDMRK	URJ202L-GNTEK	GRJ200L-GNANKV	GRJ200L-GPANKV	GRJ200L-GNMNKV	GRJ200L-GDMNKV
4950 (194.9)*8, *10	4950 (194.9)*9, *10	4950 (194.9)*8, *9, *10	4950 (194.9)*10	4950 (194.9)*8, *9, *10	4950 (194.9)*8, *9, *10
1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
1905 (74.9)*11, *12	1905 (74.9)*11, *12	1890 (74.3)*11	1890 (74.3)	1890 (74.3)*11	1890 (74.3)*11
2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
1680 (66.1)	1640 (64.5)	1680 (66.1), 1640 (64.5)*7	1680 (66.1)	1680 (66.1), 1640 (64.5)*7	1680 (66.1), 1640 (64.5)*7
1675 (65.9)	1635 (64.3)	1675 (65.9), 1635 (64.3)*7	1675 (65.9)	1675 (65.9), 1635 (64.3)*7	1675 (65.9), 1635 (64.3)*7
2905 (114.4)	2715 (106.8)	2715 (106.8)	2905 (114.4)	2715 (106.8)	2905 (114.4)
1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)
1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)
—	—	225 (8.9)	225 (8.9)	225 (8.9)	—
30	30	30	30	30	30
—	—	20	20	20	—
1235 - 1315 (2723 - 2899)	1325 - 1350 (2921 - 2976)	1230 - 1360 (2712 - 2998)	1225 - 1300 (2701 - 2866)	1225 - 1320 (2701 - 2910)	1225 - 1330 (2701 - 2932)
1120 - 1250 (2469 - 2756)	1300 - 1450 (2866 - 3197)	1220 - 1305 (2690 - 2877)	1200 - 1270 (2646 - 2800)	1215 - 1280 (2679 - 2822)	1170 - 1265 (2579 - 2789)
2355 - 2565 (5192 - 5655)	2625 - 2800 (5787 - 6173)	2450 - 2665 (5401 - 5875)	2425 - 2570 (5346 - 5666)	2440 - 2600 (5379 - 5732)	2395 - 2595 (5280 - 5721)
1425 (3142)	1445 (3186)	1435 (3164)	1360 (2998)	1380 (3042)	1395 (3075)
1875 (4134)	1905 (4200)	1865 (4112)	1900 (4189)	1920 (4233)	1905 (4200)
3300 (7275)	3350 (7385)	3300 (7275)	3260 (7187)	3300 (7275)	3300 (7275)
138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)
0.060 (2.1)	0.259 (9.1)	0.259 (9.1)	0.060 (2.1)	0.259 (9.1)	0.060 (2.1)
200	205	190	190	200	200
—	—	190	190	200	—
—	—	10.7	10.7	11.0	—
—	—	17.6	17.6	17.6	—
—	—	56	56	56	—
—	—	96	96	96	—
—	—	140	140	140	—
—	—	190	190	200	—
—	—	190	190	200	—
—	—	—	—	—	—
—	—	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	—
—	—	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	—
1GR-FE	1UR-FE	1GR-FE	1GR-FE	1GR-FE	1GR-FE
6-cylinder, V Type	8-cylinder, V Type	6-cylinder, V Type	6-cylinder, V Type	6-cylinder, V Type	6-cylinder, V Type
24-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	24-valve DOHC, Chain Drive (with Dual VVT-i)	24-valve DOHC, Chain Drive (with Dual VVT-i)	24-valve DOHC, Chain Drive (with Dual VVT-i)	24-valve DOHC, Chain Drive (with Dual VVT-i)
94.0 × 95.0 (3.70 × 3.74)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)	94.0 × 95.0 (3.70 × 3.74)
3956 (241.4)	4608 (281.2)	3956 (241.4)	3956 (241.4)	3956 (241.4)	3956 (241.4)
10.4 : 1	10.2 : 1	10.4 : 1	10.4 : 1	10.4 : 1	10.4 : 1
EFI	EFI	EFI	EFI	EFI	EFI
95 or higher	91 or higher	95 or higher	95 or higher	95 or higher	95 or higher
202@5600*2	227@5500	202@5600*2	202@5600*2	202@5600*2	202@5600*2
385@4400*2	439@3400	385@4400*2	385@4400*2	385@4400*2	385@4400*2
12 - 55	12 - 55	12 - 58	12 - 58	12 - 58	12 - 58
1200	1560, 1800*4	1200	1200	1200	1200
1.4	2.0	1.4	1.4	1.4	1.4
Dry, Single Plate, Diaphragm	—	—	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
H150F	AB60F	A750F	A750F	H150F	H150F
4.529	3.333	3.520	3.520	4.529	4.529
2.464	1.960	2.042	2.042	2.464	2.464
1.490	1.353	1.400	1.400	1.490	1.490
1.000	1.000	1.000	1.000	1.000	1.000
0.881	0.728	0.716	0.716	0.881	0.881
—	0.588	—	—	—	—
4.313	3.061	3.224	3.224	4.313	4.313
1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
4.300/4.300	4.300/4.300	4.100/4.100	4.100/4.100	4.300/4.300	4.300/4.300
220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
16.7	16.7, 14.2 - 17.6*6	16.7	16.7	16.7	16.7
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic

*10: Models with pintle hook assembly: + 145 mm (5.7 in.)
*11: Models with roof side rail: + 40 mm (1.6 in.)
*12: Models with roof rack: + 235 mm (9.3 in.)
*13: Models with snorkel: + 65 mm (2.6 in.)
*14: Models for Argentina

AP

Item \ Area				G.C.C. Countries			
Body Type				Station Wagon (Swing/9-seater, 10-seater*1)	Station Wagon (Lift-up/8-seater)	Station Wagon (Swing/9-seater)	Station Wagon (Swing/9-seater, 10-seater*1)
Vehicle Grade				Standard	GX		Standard
Model Code				GRJ200L-GDMRKV	VDJ200L-GNMNZV	VDJ200L-GDMNZV	VDJ200L-GDMRZV
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4950 (194.9)*7, *9	4950 (194.9)*7, *8, *9	4950 (194.9)*8, *9	4950 (194.9)*9
		Width	mm (in.)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
		Height	mm (in.)	1890 (74.3)*10	1890 (74.3)*10	1890 (74.3)*10	1890 (74.3)*10
	Wheel Base		mm (in.)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
	Tread	Front	mm (in.)	1680 (66.1)	1680 (66.1), 1640 (64.5)*6	1680 (66.1), 1640 (64.5)*6	1680 (66.1)
		Rear	mm (in.)	1675 (65.9)	1675 (65.9), 1635 (64.3)*6	1675 (65.9), 1635 (64.3)*6	1675 (65.9)
	Room	Length	mm (in.)	2905 (114.4)	2715 (106.8)	2905 (114.4)	2905 (114.4)
		Width	mm (in.)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)
		Height	mm (in.)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
	Overhang	Front	mm (in.)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
		Rear	mm (in.)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)
	Min. Running Ground Clearance		mm (in.)	—	225 (8.9)	—	—
	Angle of Approach		degrees	30	30	30	30
	Angle of Departure		degrees	—	20	—	—
	Curb Weight	Front	kg (lb)	1225 - 1310 (2701 - 2888)	1390 - 1480 (3064 - 3263)	1420 - 1450 (3131 - 3197)	1420 - 1430 (3131 - 3153)
		Rear	kg (lb)	1180 - 1230 (2601 - 2712)	1215 - 1270 (2679 - 2800)	1175 - 1285 (2590 - 2833)	1190 - 1260 (2623 - 2778)
		Total	kg (lb)	2405 - 2540 (5302 - 5600)	2605 - 2750 (5743 - 6063)	2595 - 2735 (5721 - 6030)	2610 - 2690 (5754 - 5930)
	Gross Vehicle Weight	Front	kg (lb)	1420 (3131)	1565 (3450)	1525 (3362)	1550 (3417)
		Rear	kg (lb)	1840 (4057)	1785 (3935)	1825 (4023)	1800 (3968)
		Total	kg (lb)	3260 (7187)	3350 (7385)	3350 (7385)	3350 (7385)
	Fuel Tank Capacity		L (US.gal, Imp. gal)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)
	Luggage Capacity (VDA)		m^3 (cu.ft.)	0.060 (2.1)	0.259 (9.1)	0.060 (2.1)	0.060 (2.1)
Performance	Max. Speed		km/h	200	170	170	170
	Max. Cruising Speed		km/h	—	170	—	—
	Acceleration	0 to 100 km/h	sec.	—	12.0	—	—
		0 to 400 m	sec.	—	18.2	—	—
	Max. Permissible Speed	1st Gear	km/h	—	35	—	—
		2nd Gear	km/h	—	64	—	—
		3rd Gear	km/h	—	106	—	—
		4th Gear	km/h	—	158	—	—
		5th Gear	km/h	—	170	—	—
		6th Gear	km/h	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	—	5.9 (19.4)	—	—
		Body	m (ft.)	—	6.3 (20.7)	—	—
Engine	Engine Type			1GR-FE	1VD-FTV	1VD-FTV	1VD-FTV
	No. of Cyls. & Arrangement			6-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			24-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve, DOHC	32-valve, DOHC	32-valve, DOHC
	Bore × Stroke		mm (in.)	94.0 × 95.0 (3.70 × 3.74)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)
	Displacement		cm^3 (cu.in.)	3956 (241.4)	4461 (272.2)	4461 (272.2)	4461 (272.2)
	Compression Ratio			10.4 : 1	16.8 : 1	16.8 : 1	16.8 : 1
	Fuel System			EFI	Common-rail Type	Common-rail Type	Common-rail Type
	Research Octane No. (RON) or Cetane Number (Diesel)			95 or higher	48 or higher	48 or higher	48 or higher
	Max. Output		kW@rpm	202@5600*2	162@3600*2	162@3600*2	162@3600*2
	Max. Torque		N·m@rpm	385@4400*2	430@1200 - 3600*2	430@1200 - 3600*2	430@1200 - 3600*2
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 58	12 - 116	12 - 116	12 - 116
	Alternator Output		Watts	1200	1560	1560	1560
	Starter Output		kW	1.4	2.7	2.7	2.7
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			H150F	H150F	H150F	H150F
	Gear Ratio	In 1st		4.529	4.529	4.529	4.529
		In 2nd		2.464	2.464	2.464	2.464
		In 3rd		1.490	1.490	1.490	1.490
		In 4th		1.000	1.000	1.000	1.000
		In 5th		0.881	0.881	0.881	0.881
		In 6th		—	—	—	—
		In Reverse		4.313	4.313	4.313	4.313
	Transfer Gear Ratio		H4/L4	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
	Differential Gear Ratio (Front/Rear)			4.300/4.300	3.909/3.909	3.909/3.909	3.909/3.909
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio			16.7	16.7	16.7	16.7
	Power Steering Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic

*1: Models with bench type front passenger seat
*2: EEC-NET
*3: ECC
*4: Models with rear No. 2 seat for 2 passengers
*5: Models with VGRS
*6: Models with 285 mm width tires
*7: Models with winch assembly: + 55 mm (2.2 in.)
*8: Models with front bumper guard: + 75 mm (3.0 in.)
*9: Models with pintle hook assembly: + 145 mm (5.7 in.)

G.C.C. Countries				Australia	
Station Wagon (Lift-up/8-seater)					Station Wagon (Lift-up/7-seater*4, 8-seater)
GX		VX		GX	VX
VDJ200L-GNTNZV	URJ202L-GNTNKV	URJ202L-GNTEKV	URJ200L-GNTEKV	VDJ200R-GNTNZQ	VDJ200R-GNTEZQ
4950 (194.9)*8, *9	4950 (194.9)*7, *8, *9	4950 (194.9)*8, *9	4950 (194.9)*8, *9	4990 (196.5)	4990 (196.5)
1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
1890 (74.3)*10	1890 (74.3)*10	1890 (74.3)*10	1890 (74.3)*10	1945 (76.6)*11	1945 (76.6)*11
2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
1680 (66.1), 1640 (64.5)*6	1680 (66.1), 1640 (64.5)*6	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)
1675 (65.9), 1635 (64.3)*6	1675 (65.9), 1635 (64.3)*6	1635 (64.3)	1635 (64.3)	1635 (64.3)	1635 (64.3)
2715 (106.8)	2715 (106.8)	2715 (106.8)	2715 (106.8)	2715 (106.8)	2715 (106.8)
1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)
1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)
225 (8.9)	—	—	225 (8.9)	225 (8.9)	225 (8.9)
30	30	30	30	30	30
20	—	—	20	20	20
1400 - 1490 (3086 - 3285)	1300 - 1420 (2866 - 3131)	1305 - 1355 (2877 - 2987)	1310 - 1360 (2888 - 2998)	1410 - 1480 (3109 - 3263)	1460 - 1510 (3219 - 3329)
1215 - 1260 (2679 - 2778)	1255 - 1330 (2767 - 2932)	1280 - 1380 (2822 - 3042)	1280 - 1380 (2822 - 3042)	1220 - 1250 (2690 - 2756)	1245 - 1240 (2745 - 2734)
2615 - 2750 (5765 - 6063)	2555 - 2750 (5633 - 6063)	2585 - 2735 (5699 - 6030)	2590 - 2740 (5710 - 6041)	2630 - 2730 (5798 - 6019)	2705 - 2750 (5963 - 6063)
1575 (3472)	1505 (3318)	1435 (3164)	1440 (3175)	1560 (3439)	1580 (3483)*4, 1595 (3516)
1775 (3913)	1845 (4068)	1915 (4222)	1910 (4211)	1790 (3946)	1770 (3902)*4, 1755 (3869)
3350 (7385)	3350 (7385)	3350 (7385)	3350 (7385)	3350 (7385)	3350 (7385)
138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	93 (24.6, 20.5), 138 (36.5, 30.4)*4
0.259 (9.1)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)
210	205	205	210	210	210
210	—	—	210	210	210
8.6	—	—	7.8	8.6	8.6
16.2	—	—	15.8	16.2	16.2
51	—	—	66	51	51
86	—	—	113	86	86
125	—	—	164	125	125
169	—	—	210	169	169
210	—	—	210	210	210
210	—	—	210	210	210
5.9 (19.4)	—	—	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)
6.3 (20.7)	—	—	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)
1VD-FTV	1UR-FE	1UR-FE	3UR-FE	1VD-FTV	1VD-FTV
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
32-valve, DOHC	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve, DOHC	32-valve, DOHC
86.0 × 96.0 (3.39 × 3.78)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 102.0 (3.70 × 4.02)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)
4461 (272.2)	4608 (281.2)	4608 (281.2)	5663 (345.6)	4461 (272.2)	4461 (272.2)
16.8 : 1	10.2 : 1	10.2 : 1	10.2 : 1	16.8 : 1	16.8 : 1
Common-rail Type	EFI	EFI	EFI	Common-rail Type	Common-rail Type
48 or higher	91 or higher	91 or higher	91 or higher	48 or higher	48 or higher
173@3200*2	227@5500*3	227@5500*3	270@5600	195@3400*2	195@3400*2
615@1800 - 2200*2	439@3400*3	439@3400*3	530@3200	650@1600 - 2600*2	650@1600 - 2600*2
12 - 116	12 - 58	12 - 58	12 - 58	12 - 110	12 - 110
1560	1800	1800	1800	1800	1800
2.7	2.0	2.0	2.0	2.7	2.7
—	—	—	—	—	—
AB60F	AB60F	AB60F	AB60F	AB60F	AB60F
3.333	3.333	3.333	3.333	3.333	3.333
1.960	1.960	1.960	1.960	1.960	1.960
1.353	1.353	1.353	1.353	1.353	1.353
1.000	1.000	1.000	1.000	1.000	1.000
0.728	0.728	0.728	0.728	0.728	0.728
0.588	0.588	0.588	0.588	0.588	0.588
3.061	3.061	3.061	3.061	3.061	3.061
1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
3.909/3.909	4.300/4.300	4.300/4.300	3.909/3.909	3.909/3.909	3.909/3.909
220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
16.7	16.7	16.7, 14.2 - 17.6*5	16.7, 14.2 - 17.6*5	16.7	16.7
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic

*10: Models with roof side rail: + 40 mm (1.6 in.)
*11: Models with snorkel: + 65 mm (2.6 in.)

Item \ Area				Australia			Europe	
Body Type				Station Wagon (Swing/5-seater)	Station Wagon (Lift-up/8-seater)		Station Wagon (Lift-up/5-seater)	
Vehicle Grade				Standard	GX	VX		
Model Code				VDJ200R-GCTRZQ	URJ202R-GNTNKQ	URJ202R-GNTEKQ	URJ202L-GMTEKW	
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4990 (196.5)	4990 (196.5)	4990 (196.5)	4950 (194.9)	5
		Width	mm (in.)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	
		Height	mm (in.)	1945 (76.6)*7	1945 (76.6)	1945 (76.6)	1950 (76.8)	
	Wheel Base		mm (in.)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	
	Tread	Front	mm (in.)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	
		Rear	mm (in.)	1635 (64.3)	1635 (64.3)	1635 (64.3)	1635 (64.3)	10
	Room	Length	mm (in.)	1965 (77.4)	2715 (106.8)	2715 (106.8)	1965 (77.4)	
		Width	mm (in.)	1615 (63.6)	1640 (64.5)	1640 (64.5)	1615 (63.6)	
		Height	mm (in.)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	
	Overhang	Front	mm (in.)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	
		Rear	mm (in.)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	15
	Min. Running Ground Clearance		mm (in.)	—	—	—	—	
	Angle of Approach		degrees	30	30	30	30	
	Angle of Departure		degrees	—	—	—	—	
	Curb Weight	Front	kg (lb)	1430 - 1435 (3153 - 3164)	1320 - 1360 (2910 - 2998)	1340 - 1365 (2954 - 3009)	1350 - 1400 (2976 - 3086)	
		Rear	kg (lb)	1205 (2657)	1265 - 1300 (2789 - 2866)	1300 - 1355 (2866 - 2987)	1160 - 1280 (2557 - 2822)	20
		Total	kg (lb)	2635 - 2640 (5809 - 5820)	2585 - 2660 (5699 - 5864)	2640 - 2720 (5820 - 5997)	2510 - 2680 (5534 - 5908)	
	Gross Vehicle Weight	Front	kg (lb)	1495 (3296)	1420 (3131)	1440 (3175)	1470 (3241)	
		Rear	kg (lb)	1855 (4090)	1930 (4255)	1910 (4211)	1880 (4145)	
		Total	kg (lb)	3350 (7385)	3350 (7385)	3350 (7385)	3350 (7385)	
	Fuel Tank Capacity		L (US.gal, Imp. gal)	138 (36.5, 30.4)	138 (36.5, 30.4)	138 (36.5, 30.4)	93 (24.6, 20.5)	25
	Luggage Capacity (VDA)		m^3 (cu.ft.)	0.909 (32.1)	0.259 (9.1)	0.259 (9.1)	0.909 (32.1)	
Performance	Max. Speed		km/h	210	205	205	205	
	Max. Cruising Speed		km/h	—	—	—	—	
	Acceleration	0 to 100 km/h	sec.	—	—	—	—	
		0 to 400 m	sec.	—	—	—	—	30
	Max. Permissible Speed	1st Gear	km/h	—	—	—	—	
		2nd Gear	km/h	—	—	—	—	
		3rd Gear	km/h	—	—	—	—	
		4th Gear	km/h	—	—	—	—	
		5th Gear	km/h	—	—	—	—	35
		6th Gear	km/h	—	—	—	—	
	Min. Turning Radius	Tire	m (ft.)	—	—	—	—	
		Body	m (ft.)	—	—	—	—	
Engine	Engine Type			1VD-FTV	1UR-FE	1UR-FE	1UR-FE	
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	40
	Valve Mechanism			32-valve, DOHC	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve DOHC, Chain Drive (with Dual VVT-i)	
	Bore × Stroke		mm (in.)	86.0 × 96.0 (3.39 × 3.78)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	
	Displacement		cm^3 (cu.in.)	4461 (272.2)	4608 (281.2)	4608 (281.2)	4608 (281.2)	
	Compression Ratio			16.8 : 1	10.2 : 1	10.2 : 1	10.2 : 1	
	Fuel System			Common-rail Type	EFI	EFI	EFI	45
	Research Octane No. (RON) or Cetane Number (Diesel)			48 or higher	91 or higher	91 or higher	95 or higher	
	Max. Output		kW@rpm	195@3400*1	227@5500*4	227@5500*4	234@5600*4, *8, 227@5500*4, *9	
	Max. Torque		N·m@rpm	650@1600 - 2600*1	439@3400*4	439@3400*4	460@3400*4, 439@3400*4	
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 110	12 - 55	12 - 55	12 - 55, 12 - 64*2	
	Alternator Output		Watts	1800	1800	1800	1800	50
	Starter Output		kW	2.7	2.0	2.0	2.0	
Chassis	Clutch Type			—	—	—	—	
	Transmission Type			AB60F	AB60F	AB60F	AB60F	
	Gear Ratio	In 1st		3.333	3.333	3.333	3.333	
		In 2nd		1.960	1.960	1.960	1.960	55
		In 3rd		1.353	1.353	1.353	1.353	
		In 4th		1.000	1.000	1.000	1.000	
		In 5th		0.728	0.728	0.728	0.728	
		In 6th		0.588	0.588	0.588	0.588	
		In Reverse		3.061	3.061	3.061	3.061	60
	Transfer Gear Ratio		H4/L4	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	
	Differential Gear Ratio (Front/Rear)			3.909/3.909	4.300/4.300	4.300/4.300	4.300/4.300	
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	65
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	
	Brake Booster Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic	
	Proportioning Valve Type			—	—	—	—	
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	
		Rear		4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	70
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard	
		Rear		Standard	Standard	Standard	Standard	
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	
	Steering Gear Ratio			16.7	16.7	16.7	16.7, 14.2 - 17.6*3	
	Power Steering Type			Hydraulic	Hydraulic	Hydraulic	Hydraulic	75

*1: EEC-NET
*2: Cold area specification models
*3: Models with VGRS
*4: ECC
*5: Models for India
*6: Models compliant with EURO 5 emission regulations
*7: Models with snorkel: + 65 mm (2.6 in.)
*8: Models compliant with EURO 5 emission regulations
*9: Models compliant with EURO 4 emission regulations

Europe				South Africa	China
Station Wagon (Lift-up/7-seater)		Station Wagon (Lift-up/5-seater)	Station Wagon (Lift-up/7-seater)		Station Wagon (Lift-up/8-seater)
VX					GX
URJ202L-GNTEKW	VDJ200R-GNTEZW	VDJ200L-GMTEZW	VDJ200L-GNTEZW	URJ202R-GNTEKW	GRJ200L-GNANKC
4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)	4950 (194.9)	5095 (200.6)
1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)	1970 (77.6)
1950 (76.8)	1950 (76.8)	1950 (76.8)	1950 (76.8)	1950 (76.8)	1930 (76.0)
2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)	2850 (112.2)
1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)	1640 (64.5)
1635 (64.3)	1635 (64.3)	1635 (64.3)	1635 (64.3)	1635 (64.3)	1635 (64.3)
2715 (106.8)	2715 (106.8)	1965 (77.4)	2715 (106.8)	2715 (106.8)	2715 (106.8)
1640 (64.5)	1640 (64.5)	1615 (63.6)	1640 (64.5)	1640 (64.5)	1640 (64.5)
1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)	1200 (47.2)
930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)	930 (36.6)
1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1170 (46.1)	1315 (51.8)
—	225 (8.9)	225 (8.9)	225 (8.9)	—	225 (8.9)
30	30	30	30	30	30
—	20	20	20	—	20
1350 - 1390 (2976 - 3064)	1445 - 1480 (3186 - 3263)	1445 - 1515 (3186 - 3340)	1445 - 1480 (3186 - 3263)	1350 - 1400 (2976 - 3086)	1255 - 1360 (2767 - 2998)
1160 - 1320 (2557 - 2910)	1065 - 1260 (2348 - 2778)	1065 - 1225 (2348 - 2701)	1065 - 1260 (2348 - 2778)	1160 - 1320 (2557 - 2910)	1285 (2833)
2510 - 2710 (5534 - 5975)	2510 - 2740 (5534 - 6041)	2510 - 2740 (5534 - 6041)	2510 - 2740 (5534 - 6041)	2510 - 2720 (5534 - 5997)	2540 - 2645 (5600 - 5831)
1450 (3197)	1550 (3417)	1590 (3505)	1550 (3417)	1465 (3230)	1430 (3153)
1900 (4189)	1800 (3968)	1760 (3880)	1800 (3968)	1885 (4156)	1870 (4123)
3350 (7385)	3350 (7385)	3350 (7385)	3350 (7385)	3350 (7385)	3300 (7275)
93 (24.6, 20.5)	93 (24.6, 20.5)	93 (24.6, 20.5)	93 (24.6, 20.5)	93 (24.6, 20.5)	138 (36.5, 30.4)
0.259 (9.1)	0.259 (9.1)	0.909 (32.1)	0.259 (9.1)	0.259 (9.1)	0.259 (9.1)
205	210	210	210	205	190
—	210	210	210	—	190
—	8.6	8.6	8.6	—	10.7
—	16.2	16.2	16.2	—	17.6
—	51	51	51	—	56
—	86	86	86	—	96
—	125	125	125	—	140
—	169	169	169	—	190
—	210	210	210	—	190
—	210	210	210	—	—
—	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	—	5.9 (19.4)
—	6.3 (20.7)	6.3 (20.7)	6.3 (20.7)	—	6.3 (20.7)
1UR-FE	1VD-FTV	1VD-FTV	1VD-FTV	1UR-FE	1GR-FE
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	6-cylinder, V Type
32-valve DOHC, Chain Drive (with Dual VVT-i)	32-valve, DOHC	32-valve, DOHC	32-valve, DOHC	32-valve DOHC, Chain Drive (with Dual VVT-i)	24-valve DOHC, Chain Drive (with Dual VVT-i)
94.0 × 83.0 (3.70 × 3.27)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 95.0 (3.70 × 3.74)
4608 (281.2)	4461 (272.2)	4461 (272.2)	4461 (272.2)	4608 (281.2)	3956 (241.4)
10.2 : 1	16.8 : 1	16.8 : 1	16.8 : 1	10.2 : 1	10.4 : 1
EFI	Common-rail Type	Common-rail Type	Common-rail Type	EFI	EFI
95 or higher	48 or higher	48 or higher	48 or higher	91 or higher	95 or higher
234@5600*4, *8, 227@5500*4, *9	173@3200*1, 195@3400*5, 200@3600*6	173@3200*1, 200@3600*6	173@3200*1, 200@3600*6	234@5600*4, *8, 227@5500*4, *9	202@5600*1
460@3400*4, 439@3400*4	650@1600 - 2800*1	650@1600 - 2800*1	650@1600 - 2800*1	460@3400*4, 439@3400*4	385@4400*1
12 - 55, 12 - 64*2	12 - 110, 12 - 128*2	12 - 110, 12 - 128*2	12 - 110, 12 - 128*2	12 - 64	12 - 64
1800	2160, 1800*5	2160	2160	1800	1560
2.0	2.7	2.7	2.7	2.0	1.4
—	—	—	—	—	—
AB60F	AB60F	AB60F	AB60F	AB60F	A750F
3.333	3.333	3.333	3.333	3.333	3.520
1.960	1.960	1.960	1.960	1.960	2.042
1.353	1.353	1.353	1.353	1.353	1.400
1.000	1.000	1.000	1.000	1.000	1.000
0.728	0.728	0.728	0.728	0.728	0.716
0.588	0.588	0.588	0.588	0.588	—
3.061	3.061	3.061	3.061	3.061	3.224
1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618	1.000/2.618
4.300/4.300	3.909/3.909	3.909/3.909	3.909/3.909	4.300/4.300	4.100/4.100
220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)	220 (8.7)/240 (9.5)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod	4-link with Lateral Rod
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
16.7, 14.2 - 17.6*3	14.2 - 17.6	16.7, 14.2 - 17.6*3	16.7, 14.2 - 17.6*3	16.7	16.7
Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic

Item \ Area				China
Body Type				Station Wagon (Lift-up/8-seater)
Vehicle Grade				VX
Model Code				URJ202L-GNTEKC
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5095 (200.6)
		Width	mm (in.)	1970 (77.6)
		Height	mm (in.)	1945 (76.5)
	Wheel Base		mm (in.)	2850 (112.2)
	Tread	Front	mm (in.)	1640 (64.5)
		Rear	mm (in.)	1635 (64.3)
	Room	Length	mm (in.)	2715 (106.8)
		Width	mm (in.)	1640 (64.5)
		Height	mm (in.)	1200 (47.2)
	Overhang	Front	mm (in.)	930 (36.6)
		Rear	mm (in.)	1315 (51.8)
	Min. Running Ground Clearance		mm (in.)	—
	Angle of Approach		degrees	30
	Angle of Departure		degrees	—
	Curb Weight	Front	kg (lb)	1370 - 1395 (3020 - 3075)
		Rear	kg (lb)	1305 - 1330 (2877 - 2932)
		Total	kg (lb)	2675 - 2725 (5897 - 6008)
	Gross Vehicle Weight	Front	kg (lb)	1470 (3241)
		Rear	kg (lb)	1880 (4145)
		Total	kg (lb)	3350 (7385)
	Fuel Tank Capacity		L (US.gal, Imp. gal)	138 (36.5, 30.4)
	Luggage Capacity (VDA)		m^3 (cu.ft.)	0.259 (9.1)
Performance	Max. Speed		km/h	—
	Max. Cruising Speed		km/h	—
	Acceleration	0 to 100 km/h	sec.	—
		0 to 400 m	sec.	—
	Max. Permissible Speed	1st Gear	km/h	—
		2nd Gear	km/h	—
		3rd Gear	km/h	—
		4th Gear	km/h	—
		5th Gear	km/h	—
		6th Gear	km/h	—
	Min. Turning Radius	Tire	m (ft.)	—
		Body	m (ft.)	—
Engine	Engine Type			1UR-FE
	No. of Cyls. & Arrangement			8-cylinder, V Type
	Valve Mechanism			32-valve DOHC, Chain Drive (with Dual VVT-i)
	Bore × Stroke		mm (in.)	94.0 × 83.0 (3.70 × 3.27)
	Displacement		cm^3 (cu.in.)	4608 (281.2)
	Compression Ratio			10.2 : 1
	Fuel System			EFI
	Research Octane No. (RON)			97 or higher
	Max. Output		kW@rpm	228@5500*
	Max. Torque		N·m@rpm	453@3400*
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 64
	Alternator Output		Watts	1800
	Starter Output		kW	2.0
Chassis	Clutch Type			—
	Transmission Type			AB60F
	Gear Ratio	In 1st		3.333
		In 2nd		1.960
		In 3rd		1.353
		In 4th		1.000
		In 5th		0.728
		In 6th		0.588
		In Reverse		3.061
	Transfer Gear Ratio		H4/L4	1.000/2.618
	Differential Gear Ratio (Front/Rear)			4.300/4.300
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/240 (9.5)
	Brake Type	Front		Ventilated Disc
		Rear		Ventilated Disc
	Parking Brake Type			Duo-servo Drum
	Brake Booster Type			Hydraulic
	Proportioning Valve Type			—
	Suspension Type	Front		Double-wishbone
		Rear		4-link with Lateral Rod
	Stabilizer Bar	Front		Standard
		Rear		Standard
	Steering Gear Type			Rack and Pinion
	Steering Gear Ratio			16.7
	Power Steering Type			Hydraulic

*: ECC