(Station Wagon)

CLUTCH

Service Data

Pedal height (from asphalt sheet)			173 mm	6.81 in.
Pedal freeplay	w/o Clutch booster		13 — 23 mm	0.51 — 0.91 in.
	w/ Clutch booster		15 — 30 mm	0.59 — 1.18 in.
Push rod play at pedal top			1 — 5 mm	0.04 — 0.20 in.
Booster air valve stroke at pedal top			5 — 9 mm	0.20 — 0.35 in.
Booster push rod to piston clearance		w/SST	0 mm	0 in.
Disc rivet head depth		Limit	0.3 mm	0.012 in.
Disc runout		Limit	0.8 mm	0.031 in.
Diaphragm spring tip alignment		Limit	1.0 mm	0.039 in.
Diaphragm spring finger wear	Depth	Limit	0.6 mm	0.024 in.
	Width	Limit	5.0 mm	0.197 in.
Flywheel runout		Limit	0.2 mm	0.008 in.

Torque Specifications

Part tightened	N·m	kgf·cm	ft·lbf
Master cylinder × Body	7.8	80	69 in.·lbf
Clutch line union	15	155	11
Clevis lock nut	25	250	18
Master cylinder × Clutch booster	13	130	9
Clutch booster × Body	13	130	9
Accumulator bracket × Accumulator housing	5.4	55	48 in.·lbf
Accumulator line union	15	155	11
Accumulator bleeder plug	11	110	8
Release cylinder set bolt	12	120	9
Release cylinder bleeder plug	11	110	8
Clutch cover × Flywheel			
H151F transmission	39	400	29
Others	19	195	14