SERVICE SPECIFICATIONS

SERVICE DATA

Brake pedal height from asphalt sheet	167.5 – 177.5 mm (6.59 – 6.99 in.)
Brake pedal freeplay	3 – 6 mm (0.12 – 0.24 in.)
Brake pedal reserve distance at 490 N (50 kgf, 110.2 lbf)	More than 59 mm (2.32 in.)
Brake booster push rod to piston clearance (W/SST)	0 mm (0 in.)

TORQUE SPECIFICATIONS

Part tightened	N·m	kgf·cm	ft·lbf
Master cylinder × Piston stopper bolts	10	100	7
Master cylinder × Reservoir	1.7	17.5	15.2 in.·lbf
Master cylinder × Brake booster	13	130	9
Brake tube union nut	15	155	11
LSP & BV Bracket × Frame	19	195	14
LSP & BV × LSP & BV Bracket	13	130	9
LSP & BV Spring × LSP & BV Bracket	18	185	13
LSP & BV Spring × Shackle No. 1	18	185	13
LSP & BV Shackle lock nut	25	250	18
LSP & BV Shackle × Shackle bracket	13	130	9
LSP & BV Shackle bracket × Rear axle housing	19	195	14
ABS actuator bracket × Body	19	195	14
Front speed sensor installation bolt	18	185	13
Rear speed sensor installation bolt	18	185	13