

MAJOR TECHNICAL SPECIFICATIONS

Item		Area	U.S.A.				
Body Type			5-door Wagon				
Vehicle Grade			Standard (4WD)	Limited (4WD)	Sport (4WD)	Standard (2WD)	
Model Code			ACA33L-ANPXKA	ACA33L-ANPGKA	ACA33L-ANPSKA	ACA33L-ANPXKA	
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4570 (180.0) <sup>*2</sup> , 4575 (180.1) <sup>*3</sup>	4600 (181.1)	4580 (180.3)	4570 (180.0) <sup>*2</sup> , 4575 (180.1) <sup>*3</sup>
		Width	mm (in.)	1815 (71.5)	1815 (71.5), 1855 (73.0) <sup>*4</sup>	1855 (73.0)	1815 (71.5)
		Height <sup>*1</sup>	mm (in.)	1685 (66.3), 1745 (68.7) <sup>*5</sup> 1690 (66.5) <sup>*6</sup> , 1755 (69.1) <sup>*5,6</sup>	1745 (68.7), 1755 (69.1) <sup>*6</sup>	1745 (68.7)	1685 (66.3), 1745 (68.7) <sup>*5</sup> 1690 (66.5) <sup>*6</sup> , 1755 (69.1) <sup>*5,6</sup>
	Wheel Base	mm (in.)	2660 (104.7)	2660 (104.7)	2660 (104.7)	2660 (104.7)	
	Tread	Front	mm (in.)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
		Rear	mm (in.)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
	Effective Head Room	Front	mm (in.)	1037 (40.8)	1037 (40.8), 1002 (39.4) <sup>*7</sup>	1037 (40.8), 1002 (39.4) <sup>*7</sup>	1037 (40.8)
		Rear	mm (in.)	1009 (39.7)	1009 (39.7)	1009 (39.7)	1009 (39.7)
	Effective Leg Room	Front	mm (in.)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)
		Rear	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Shoulder Room	Front	mm (in.)	1450 (57.1)	1450 (57.1)	1450 (57.1)	1450 (57.1)
		Rear	mm (in.)	1405 (55.3)	1405 (55.3)	1405 (55.3)	1405 (55.3)
	Overhang	Front	mm (in.)	855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)
		Rear	mm (in.)	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)
	Min. Running Ground Clearance	mm (in.)	190 (7.5)	190 (7.5)	190 (7.5)	190 (7.5)	
	Angle of Approach	degrees	29	29	29	29	
	Angle of Departure	degrees	25	25	25	25	
	Curb Weight	Front	kg (lb)	892 (1967)	898 (1980)	903 (1991)	868 (1914)
		Rear	kg (lb)	670 (1477)	695 (1532)	691 (1523)	629 (1387)
		Total	kg (lb)	1562 (3444)	1593 (3512)	1594 (3514)	1497 (3300)
Gross Vehicle Weight	Front	kg (lb)	—	—	—	—	
	Rear	kg (lb)	—	—	—	—	
Total (2nd / 3rd)	kg (lb)	2057 (4535) / 2207 (4865)	2057 (4535) / 2207 (4865)	2057 (4535) / —	2009 (4430) / 2145 (4730)		
Fuel Tank Capacity	ℓ (US.gal., Imp.gal.)	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)		
Luggage Compartment Capacity	m <sup>3</sup> (cu.ft.)	—	—	—	—		
Performance	Max. Speed	km/h (mph)	185 (115)	185 (115)	185 (115)	190 (118)	
	Max. Cruising Speed	km/h (mph)	145 (90)	145 (90)	145 (90)	150 (93)	
	Acceleration	0 to 60 mph	sec.	10.2	10.2	10.2	10.0
		0 to 400 m	sec.	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	67 (41)	67 (41)	67 (41)	70 (43)
		2nd Gear	km/h (mph)	120 (74)	120 (74)	120 (74)	126 (78)
		3rd Gear	km/h (mph)	—	—	—	—
		4th Gear	km/h (mph)	—	—	—	—
Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	5.7 (18.7)	5.7 (18.7)	6.0 (19.7)	5.7 (18.7)	
	Curb to Curb	m (ft.)	5.3 (17.4)	5.3 (17.4)	5.6 (18.4)	5.3 (17.4)	
Engine	Engine Type		2AZ-FE	2AZ-FE	2AZ-FE	2AZ-FE	
	Valve Mechanism		16-Valve, DOHC	16-Valve, DOHC	16-Valve, DOHC	16-Valve, DOHC	
	Bore x Stroke	mm (in.)	88.5 x 96.0 (3.48 x 3.78)	88.5 x 96.0 (3.48 x 3.78)	88.5 x 96.0 (3.48 x 3.78)	88.5 x 96.0 (3.48 x 3.78)	
	Displacement	cm <sup>3</sup> (cu.in.)	2362 (144.2)	2362 (144.2)	2362 (144.2)	2362 (144.2)	
	Compression Ratio		9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	
	Fuel System		SFI	SFI	SFI	SFI	
	Octane Rating		87 or higher	87 or higher	87 or higher	87 or higher	
	Max. Output (SAE-NET) <sup>*8</sup>	kW / rpm (HP@rpm)	124 / 6000 (166@6000)	124 / 6000 (166@6000)	124 / 6000 (166@6000)	124 / 6000 (166@6000)	
	Max. Torque (SAE-NET) <sup>*8</sup>	N·m / rpm (lb-ft@rpm)	224 / 4000 (165@4000)	224 / 4000 (165@4000)	224 / 4000 (165@4000)	224 / 4000 (165@4000)	
Engine Electrical	Battery Capacity (SHR)	Voltage & Amp. hr.	12-55	12-55	12-55	12-55	
	Generator Output	Watts	1200	1200	1200	1200	
	Starter Output	kW	1.7	1.7	1.7	1.7	
Chassis	Clutch Type		—	—	—	—	
	Transmission Type		U140F	U140F	U140F	U241E	
		In First		3.938	3.938	3.938	3.943
	Gear Ratio (Counter Gear Ratio Included)	In Second		2.194	2.194	2.194	2.197
		In Third		1.411	1.411	1.411	1.413
		In Fourth		1.019	1.019	1.019	1.020
		In Fifth		—	—	—	—
		In Reverse		3.141	3.141	3.141	3.145
	Differential Gear Ratio (Final)		3.080	3.080	3.080	2.923	
	Transfer / Rear Differential Gear Ratio		0.439 / 2.277	0.439 / 2.277	0.439 / 2.277	—	
	Rear Differential Gear Size	mm (in.)	135 (5.3)	135 (5.3)	135 (5.3)	—	
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Solid Disc	Solid Disc	Solid Disc	Solid Disc
	Parking Brake Type		Duo Servo Drum	Duo Servo Drum	Duo Servo Drum	Duo Servo Drum	
Brake Booster Type and Size	in.	Single, 10"	Single, 10"	Single, 10"	Single, 10"		
Proportioning Valve Type		—	—	—	—		
Suspension Type	Front		MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	
	Rear		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	
Stabilizer Bar	Front		Standard	Standard	Standard	Standard	
	Rear		Standard	Standard	Standard	—, Option <sup>*6</sup>	
Steering Gear Type		Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion		
Steering Gear Ratio (Overall)		14.4	14.4	14.6	14.4		
Power Steering Type		Electric Motor	Electric Motor	Electric Motor	Electric Motor		

\*1: Unladen Vehicle      \*2: With 215/70R16 Tire      \*3: With 225/65R17 Tire      \*4: With Over-fender  
 \*5: With Roof Rail      \*6: With Rear No.2 Seat      \*7: With Roof Rail      \*8: Maximum output and torque rating is determined by revised SAE J1349 standard.

U. S. A.						
5-door Wagon						
Limited (2WD)	Sport (2WD)	Standard (4WD)	Limited (4WD)	Sport (4WD)	Standard (2WD)	
ACA38L-ANPGKA	ACA38L-ANPSKA	GSA33L-ANAXKA	GSA33L-ANAGKA	GSA33L-ANASKA	GSA38L-ANAXKA	
4600 (181.1)	4580 (180.3)	4570 (180.0)*2, 4575 (180.1)*3	4600 (181.1)	4580 (180.3)	4570 (180.0)*2, 4575 (180.1)*3	
1815 (71.5), 1855 (73.0)*4	1855 (73.0)	1815 (71.5)	1815 (71.5), 1855 (73.0)*4	1855 (73.0)	1815 (71.5)	
1745 (68.7), 1755 (69.1)*6	1745 (68.7)	1685 (66.3), 1745 (68.7)*5 1690 (66.5)*5, 1755 (69.1)*5, 6	1745 (68.7), 1755 (69.1)*6	1745 (68.7)	1685 (66.3), 1745 (68.7)*5 1690 (66.5)*5, 1755 (69.1)*5, 6	
2660 (104.7)	2660 (104.7)	2660 (104.7)	2660 (104.7)	2660 (104.7)	2660 (104.7)	
1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	
1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	
1037 (40.8), 1002 (39.4)*7	1037 (40.8), 1002 (39.4)*7	1037 (40.8)	1037 (40.8), 1002 (39.4)*7	1037 (40.8), 1002 (39.4)*7	1037 (40.8)	
1009 (39.7)	1009 (39.7)	1009 (39.7)	1009 (39.7)	1009 (39.7)	1009 (39.7)	
1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)	
940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)	
1450 (57.1)	1450 (57.1)	1450 (57.1)	1450 (57.1)	1450 (57.1)	1450 (57.1)	
1405 (55.3)	1405 (55.3)	1405 (55.3)	1405 (55.3)	1405 (55.3)	1405 (55.3)	
855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)	
1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)	
190 (7.5)	190 (7.5)	190 (7.5)	190 (7.5)	190 (7.5)	190 (7.5)	
29	29	29	29	29	29	
25	25	25	25	25	25	
874 (1927)	879 (1938)	977 (2154)	976 (2152)	981 (2163)	961 (2125)	
655 (1444)	651 (1435)	681 (1501)	691 (1523)	687 (1515)	639 (1409)	
1529 (3371)	1530 (3373)	1667 (3675)	1667 (3675)	1668 (3677)	1600 (3527)	
—	—	—	—	—	—	
—	—	—	—	—	—	
2009 (4430)/2145 (4730)	2009 (4430)/—	2141 (4720)/2275 (5015)	2141 (4720)/2275 (5015)	2141 (4720)/—	2087 (4600)/2220 (4895)	
60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)	
—	—	—	—	—	—	
190 (118)	190 (118)	210 (130)	210 (130)	210 (130)	210 (130)	
150 (93)	150 (93)	165 (102)	165 (102)	165 (102)	165 (102)	
10.0	10.0	6.7	6.7	6.7	6.9	
—	—	—	—	—	—	
70 (43)	70 (43)	63 (39)	63 (39)	63 (39)	63 (39)	
126 (78)	126 (78)	113 (70)	113 (70)	113 (70)	113 (70)	
—	—	175 (109)	175 (109)	175 (109)	175 (109)	
—	—	—	—	—	—	
5.7 (18.7)	6.0 (19.7)	6.0 (19.7)	6.0 (19.7)	6.0 (19.7)	6.0 (19.7)	
5.3 (17.4)	5.6 (18.4)	5.6 (18.4)	5.6 (18.4)	5.6 (18.4)	5.6 (18.4)	
2AZ-FE	2AZ-FE	2GR-FE	2GR-FE	2GR-FE	2GR-FE	
16-Valve, DOHC, Chain Drive	16-Valve, DOHC, Chain Drive	24-Valve, DOHC, Chain Drive	24-Valve, DOHC, Chain Drive	24-Valve, DOHC, Chain Drive	24-Valve, DOHC, Chain Drive	
88.5 x 96.0 (3.48 x 3.78)	88.5 x 96.0 (3.48 x 3.78)	94.0 x 83.0 (3.70 x 3.27)	94.0 x 83.0 (3.70 x 3.27)	94.0 x 83.0 (3.70 x 3.27)	94.0 x 83.0 (3.70 x 3.27)	
2362 (144.2)	2362 (144.2)	3456 (210.9)	3456 (210.9)	3456 (210.9)	3456 (210.9)	
9.8 : 1	9.8 : 1	10.8 : 1	10.8 : 1	10.8 : 1	10.8 : 1	
SFI	SFI	SFI	SFI	SFI	SFI	
87 or higher	87 or higher	91 or higher	91 or higher	91 or higher	91 or higher	
124/6000 (166@6000)	124/6000 (166@6000)	200/6200 (268@6200)	200/6200 (268@6200)	200/6200 (268@6200)	200/6200 (268@6200)	
224/4000 (165@4000)	224/4000 (165@4000)	336/4700 (248@4700)	336/4700 (248@4700)	336/4700 (248@4700)	336/4700 (248@4700)	
12-55	12-55	12-55	12-55	12-55	12-55	
1200	1200	1200, 1800*9	1200, 1800*9	1200, 1800*9	1200, 1800*9	
1.7	1.7	1.7	1.7	1.7	1.7	
—	—	—	—	—	—	
U241E	U241E	U151F	U151F	U151F	U151E	
3.943	3.943	4.235	4.235	4.235	4.235	
2.197	2.197	2.360	2.360	2.360	2.360	
1.413	1.413	1.517	1.517	1.517	1.517	
1.020	1.020	1.047	1.047	1.047	1.047	
—	—	0.756	0.756	0.756	0.756	
3.145	3.145	3.378	3.378	3.378	3.378	
2.923	2.923	3.080	3.080	3.080	3.080	
—	—	0.439/2.277	0.439/2.277	0.439/2.277	—	
—	—	135 (5.3)	135 (5.3)	135 (5.3)	—	
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	
Solid Disc	Solid Disc	Solid Disc	Solid Disc	Solid Disc	Solid Disc	
Duo Servo Drum	Duo Servo Drum	Duo Servo Drum	Duo Servo Drum	Duo Servo Drum	Duo Servo Drum	
Single, 10"	Single, 10"	Single, 10"	Single, 10"	Single, 10"	Single, 10"	
—	—	—	—	—	—	
MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	
Standard	Standard	Standard	Standard	Standard	Standard	
—, Option*6	—	Standard	Standard	Standard	Standard	
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	
14.4	14.6	14.4	14.4	14.6	14.4	
Electric Motor	Electric Motor	Electric Motor	Electric Motor	Electric Motor	Electric Motor	

\*9: Option

Item		Area	U.S.A.		Canada	
Body Type		5-door Wagon				
Vehicle Grade		Limited (2WD)	Sport (2WD)	Standard (4WD)	Limited (4WD)	
Model Code		GSA38L-ANAGKA	GSA38L-ANASKA	ACA33L-ANPXXK	ACA33L-ANPGKK	
Major Dimensions & Vehicle Weights	Overall	Length mm (in.)	4600 (181.1)	4580 (180.3)	4570 (180.0)*2, 4575 (180.1)*3	4600 (181.1)
		Width mm (in.)	1815 (71.5), 1855 (73.0)*4	1855 (73.0)	1815 (71.5)	1815 (71.5), 1855 (73.0)*4
		Height*1 mm (in.)	1745 (68.7), 1755 (69.1)*6	1745 (68.7)	1685 (66.3), 1745 (68.7)*5, 1690 (66.5)*6, 1755 (69.1)*5, 6	1745 (68.7), 1755 (69.1)*6
	Wheel Base	mm (in.)	2660 (104.7)	2660 (104.7)	2660 (104.7)	2660 (104.7)
	Tread	Front mm (in.)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
		Rear mm (in.)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
	Effective Head Room	Front mm (in.)	1037 (40.8), 1002 (39.4)*7	1037 (40.8), 1002 (39.4)*7	1037 (40.8)	1037 (40.8), 1002 (39.4)*7
		Rear mm (in.)	1009 (39.7)	1009 (39.7)	1009 (39.7)	1009 (39.7)
	Effective Leg Room	Front mm (in.)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)
		Rear mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Shoulder Room	Front mm (in.)	1450 (57.1)	1450 (57.1)	1450 (57.1)	1450 (57.1)
		Rear mm (in.)	1405 (55.3)	1405 (55.3)	1405 (55.3)	1405 (55.3)
	Overhang	Front mm (in.)	855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)
		Rear mm (in.)	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)
	Min. Running Ground Clearance	mm (in.)	190 (7.5)	190 (7.5)	190 (7.5)	190 (7.5)
	Angle of Approach	degrees	29	29	29	29
	Angle of Departure	degrees	25	25	25	25
	Curb Weight	Front kg (lb)	960 (2116)	964 (2125)	892 (1967)	898 (1980)
		Rear kg (lb)	649 (1431)	646 (1424)	670 (1477)	695 (1532)
		Total kg (lb)	1609 (3547)	1610 (3549)	1562 (3444)	1593 (3512)
Gross Vehicle Weight	Front kg (lb)	—	—	—	—	
	Rear kg (lb)	—	—	—	—	
	Total (2nd / 3rd) kg (lb)	2087 (4600) / 2220 (4895)	2087 (4600) / —	2057 (4535) / 2207 (4865)	2057 (4535) / 2207 (4865)	
Fuel Tank Capacity	ℓ (US.gal., Imp.gal.)	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)	
Luggage Compartment Capacity	m <sup>3</sup> (cu.ft.)	—	—	—	—	
Performance	Max. Speed	km/h (mph)	210 (130)	210 (130)	185 (115)	185 (115)
	Max. Cruising Speed	km/h (mph)	165 (102)	165 (102)	145 (90)	145 (90)
	Acceleration	0 to 60 mph sec.	6.9	6.9	10.2	10.2
		0 to 400 m sec.	—	—	—	—
	Max. Permissible Speed	1st Gear km/h (mph)	63 (39)	63 (39)	67 (41)	67 (41)
		2nd Gear km/h (mph)	113 (70)	113 (70)	120 (74)	120 (74)
		3rd Gear km/h (mph)	175 (109)	175 (109)	—	—
		4th Gear km/h (mph)	—	—	—	—
Turning Diameter (Outside Front)	Wall to Wall m (ft.)	6.0 (19.7)	6.0 (19.7)	5.7 (18.7)	5.7 (18.7)	
	Curb to Curb m (ft.)	5.6 (18.4)	5.6 (18.4)	5.3 (17.4)	5.3 (17.4)	
Engine	Engine Type	2GR-FE		2AZ-FE		
	Valve Mechanism	24-Valve, DOHC, Chain Drive		16-Valve, DOHC, Chain Drive		
	Bore x Stroke mm (in.)	94.0 x 83.0 (3.70 x 3.27)		88.5 x 96.0 (3.48 x 3.78)		
	Displacement cm <sup>3</sup> (cu.in.)	3456 (210.9)		2362 (144.2)		
	Compression Ratio	10.8 : 1		9.8 : 1		
	Fuel System	SFI		SFI		
	Octane Rating	91 or higher		87 or higher		
	Max. Output (SAE-NET)*8 kW / rpm (HP@rpm)	200 / 6200 (268@6200)		124 / 6000 (166@6000)		
Max. Torque (SAE-NET)*8 N-m / rpm (lb-ft@rpm)	336 / 4700 (248@4700)		224 / 4000 (165@4000)			
Engine Electrical	Battery Capacity (SHR) Voltage & Amp. hr.	12-55		12-55		
	Generator Output Watts	1200, 1800*9		1200		
	Starter Output kW	1.7		1.7		
Chassis	Clutch Type	—				
	Transmission Type	U151E		U140F		
		In First	4.235	4.235	3.938	3.938
	Gear Ratio (Counter Gear Ratio Included)	In Second	2.360	2.360	2.194	2.194
		In Third	1.517	1.517	1.411	1.411
		In Fourth	1.047	1.047	1.019	1.019
		In Fifth	0.576	0.576	—	—
		In Reverse	3.378	3.378	3.141	3.141
	Differential Gear Ratio (Final)	3.080		3.080		
	Transfer / Rear Differential Gear Ratio	—		0.439 / 2.277		
	Rear Differential Gear Size mm (in.)	—		135 (5.3)		
	Brake Type	Front	Ventilated Disc		Ventilated Disc	
		Rear	Solid Disc		Solid Disc	
	Parking Brake Type	Duo Servo Drum				
	Brake Booster Type and Size in.	Single, 10"				
Proportioning Valve Type	—					
Suspension Type	Front	MacPherson Strut		MacPherson Strut		
	Rear	Double Wishbone		Double Wishbone		
Stabilizer Bar	Front	Standard		Standard		
	Rear	Standard		Standard		
Steering Gear Type	Rack and Pinion					
Steering Gear Ratio (Overall)	14.4					
Power Steering Type	Electric Motor					

\*1: Unladen Vehicle      \*3: With 225/65R17 Tire      \*5: With Roof Rail      \*7: With Roof Rail  
 \*2: With 215/70R16 Tire      \*4: With Over-fender      \*6: With Rear No.2 Seat      \*8: Maximum output and torque rating is determined by revised SAE J1349 standard.

Canada				
5-door Wagon				
	Sport (4WD)	Standard (4WD)	Limited (4WD)	Sport (4WD)
	ACA33L-ANPSKK	GSA33L-ANAXKK	GSA33L-ANAGKK	GSA33L-ANASKK
5	4580 (180.3)	4570 (180.0)*2, 4575 (180.1)*3	4600 (181.1)	4580 (180.3)
	1855 (73.0)	1815 (71.5)	1815 (71.5), 1855 (73.0)*4	1855 (73.0)
	1745 (68.7)	1685 (66.3), 1745 (68.7)*5 1690 (66.5)*6, 1755 (69.1)*5, 6	1745 (68.7), 1755 (69.1)*6	1745 (68.7)
	2660 (104.7)	2660 (104.7)	2660 (104.7)	2660 (104.7)
	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
10	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
	1037 (40.8), 1002 (39.4)*7	1037 (40.8)	1037 (40.8), 1002 (39.4)*7	1037 (40.8), 1002 (39.4)*7
	1009 (39.7)	1009 (39.7)	1009 (39.7)	1009 (39.7)
	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)
	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
15	1450 (57.1)	1450 (57.1)	1450 (57.1)	1450 (57.1)
	1405 (55.3)	1405 (55.3)	1405 (55.3)	1405 (55.3)
	855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)
	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)
	190 (7.5)	190 (7.5)	190 (7.5)	190 (7.5)
20	29	29	29	29
	25	25	25	25
	903 (1991)	977 (2154)	976 (2152)	981 (2163)
	691 (1523)	681 (1501)	691 (1523)	687 (1515)
	1594 (3514)	1658 (3655)	1667 (3675)	1667 (3675)
25	—	—	—	—
	—	—	—	—
	2057 (4535) / —	2141 (4720) / 2275 (5015)	2141 (4720) / 2275 (5015)	2141 (4720) / —
	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)
	—	—	—	—
30	185 (115)	210 (130)	210 (130)	210 (130)
	145 (90)	165 (102)	165 (102)	165 (102)
	10.2	6.7	6.7	6.7
	—	—	—	—
	67 (41)	63 (39)	63 (39)	63 (39)
35	120 (74)	113 (70)	113 (70)	113 (70)
	—	175 (109)	175 (109)	175 (109)
	—	—	—	—
	6.0 (19.7)	6.0 (19.7)	6.0 (19.7)	6.0 (19.7)
	5.6 (18.4)	5.6 (18.4)	5.6 (18.4)	5.6 (18.4)
40	2AZ-FE	2GR-FE	2GR-FE	2GR-FE
	16-Valve, DOHC, Chain Drive	24-Valve, DOHC, Chain Drive	24-Valve, DOHC, Chain Drive	24-Valve, DOHC, Chain Drive
	88.5 x 96.0 (3.48 x 3.78)	94.0 x 83.0 (3.70 x 3.27)	94.0 x 83.0 (3.70 x 3.27)	94.0 x 83.0 (3.70 x 3.27)
	2362 (144.2)	3456 (210.9)	3456 (210.9)	3456 (210.9)
	9.8 : 1	10.8 : 1	10.8 : 1	10.8 : 1
45	SFI	SFI	SFI	SFI
	87 or higher	91 or higher	91 or higher	91 or higher
	124 / 6000 (166@6000)	200 / 6200 (268@6200)	200 / 6200 (268@6200)	200 / 6200 (268@6200)
	224 / 4000 (165@4000)	336 / 4700 (248@4700)	336 / 4700 (248@4700)	336 / 4700 (248@4700)
	12-55	12-55	12-55	12-55
50	1200	1200, 1800*9	1200, 1800*9	1200, 1800*9
	1.7	1.7	1.7	1.7
	—	—	—	—
	U140F	U151F	U151F	U151F
	3.938	4.235	4.235	4.235
55	2.194	2.360	2.360	2.360
	1.411	1.517	1.517	1.517
	1.019	1.047	1.047	1.047
	—	0.576	0.576	0.576
	3.141	3.378	3.378	3.378
60	3.080	3.080	3.080	3.080
	0.439 / 2.277	0.439 / 2.277	0.439 / 2.277	0.439 / 2.277
	135 (5.3)	135 (5.3)	135 (5.3)	135 (5.3)
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Solid Disc	Solid Disc	Solid Disc	Solid Disc
65	Duo Servo Drum	Duo Servo Drum	Duo Servo Drum	Duo Servo Drum
	Single, 10"	Single, 10"	Single, 10"	Single, 10"
	—	—	—	—
	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
70	Standard	Standard	Standard	Standard
	Standard	Standard	Standard	Standard
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	14.6	14.4	14.4	14.6
	Electric Motor	Electric Motor	Electric Motor	Electric Motor

\*9: Option

- MEMO -