MAJOR TECHNICAL SPECIFICATIONS

Item \ Area				Europe			
Body Type				5-door Wagon (Short)			
Vehicle Grade				Standard (4WD)	High (4WD)	Standard (4WD)	High (4WD)
Model Code				ACA30R-AWMXKW	ACA30R-AWMGKW	ACA30R-AWPXKW	ACA30R-AWPGKW
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4395 (173.0)	4395 (173.0)	4395 (173.0)	4395 (173.0)
		Width	mm (in.)	1815 (71.5)	1815 (71.5)	1815 (71.5)	1815 (71.5)
		Height	mm (in.)	1685 (66.3), 1720 (67.7)*1	1685 (66.3), 1720 (67.7)*1	1685 (66.3), 1720 (67.7)*1	1685 (66.3), 1720 (67.7)*1
	Wheel Base		mm (in.)	2560 (100.8)	2560 (100.8)	2560 (100.8)	2560 (100.8)
	Tread	Front	mm (in.)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
		Rear	mm (in.)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
	Room	Length	mm (in.)	1805 (71.1)	1805 (71.1)	1805 (71.1)	1805 (71.1)
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	860 (33.9)	860 (33.9)	860 (33.9)	860 (33.9)
		Rear	mm (in.)	975 (38.4)	975 (38.4)	975 (38.4)	975 (38.4)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
	Angle of Approach		degrees	30	30	30	30
	Angle of Departure		degrees	30	30	30	30
	Curb Weight	Front	kg (lb)	825 (1819)	825 (1819)	865 (1907)	865 (1907)
		Rear	kg (lb)	640 (1411)	640 (1411)	640 (1411)	640 (1411)
		Total	kg (lb)	1465 (3230)	1465 (2083)	1505 (3318)	1505 (3318)
	Gross Vehicle Weight	Front	kg (lb)	945 (2083)	950 (2094)	985 (2172)	990 (2183)
		Rear	kg (lb)	1125 (2480)	1120 (2469)	1125 (2480)	1120 (2469)
		Total	kg (lb)	2070 (4564)	2070 (4564)	2110 (4652)	2110 (4652)
	Fuel Tank Capacity		ℓ (Imp.gal.)	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)
	Luggage Compartment Capacity		m^3 (cu.ft.)	0.45 (15.89)	0.45 (15.89)	0.45 (15.89)	0.45 (15.89)
Performance	Max. Speed		km/h (mph)	185 (115)	185 (115)	175 (109)	175 (109)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Acceleration	0 to 100 km/h	sec.	—	—	—	—
		0 to 400 m	sec.	17.2	17.2	18.3	18.3
	Max. Permissible Speed	1st Gear	km/h (mph)	47 (29)	47 (29)	63 (39)	63 (39)
		2nd Gear	km/h (mph)	89 (55)	89 (55)	113 (70)	113 (70)
		3rd Gear	km/h (mph)	136 (84)	136 (84)	—	—
		4th Gear	km/h (mph)	177 (110)	177 (110)	—	—
	Min. Turning Radius	Tire	m (ft.)	5.1 (16.7)	5.1 (16.7)	5.1 (16.7)	5.1 (16.7)
		Body	m (ft.)	—	—	—	—
Engine	Engine Type			1AZ-FE	1AZ-FE	1AZ-FE	1AZ-FE
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	86.0 × 86.0 (3.39 × 3.39)	86.0 × 86.0 (3.39 × 3.39)	86.0 × 86.0 (3.39 × 3.39)	86.0 × 86.0 (3.39 × 3.39)
	Displacement		cm^3 (cu.in.)	1998 (121.9)	1998 (121.9)	1998 (121.9)	1998 (121.9)
	Compression Ratio			9.8 : 1	9.8 : 1	9.8 : 1	9.8 : 1
	Fuel System			EFI	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			95 or higher	95 or higher	95 or higher	95 or higher
	Max. Output (EEC)		kW/rpm	112/6000	112/6000	112/6000	112/6000
	Max. Torque (EEC)		N·m/rpm	194/4000	194/4000	194/4000	194/4000
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 48, 55*2	12 - 48, 55*2	12 - 48, 55*2	12 - 48, 55*2
	Alternator Output		Watts	1200	1200	1200	1200
	Starter Output		kW	1.3	1.3	1.3	1.3
Chassis	Clutch Type			Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	—	—
	Transaxle Type			E352F	E352F	U140F	U140F
	Gear Ratio (Counter Gear Ratio Included*3)	In First		3.833	3.833	3.938	3.938
		In Second		2.045	2.045	2.194	2.194
		In Third		1.333	1.333	1.411	1.411
		In Fourth		1.028	1.028	1.019	1.019
		In Fifth		0.820	0.820	—	—
		In Sixth		—	—	—	—
		In Reverse		3.583	3.583	3.141	3.141
	Differential Gear Ratio (Final)			4.562	4.562	3.291	3.291
	Transfer/Rear Differential Gear Ratio			0.439/2.277	0.439/2.277	0.439/2.277	0.439/2.277
	Rear Differential Gear Size		mm (in.)	135 (5.3)	135 (5.3)	135 (5.3)	135 (5.3)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Solid Disc	Solid Disc	Solid Disc	Solid Disc
	Parking Brake Type			Duo Servo	Duo Servo	Duo Servo	Duo Servo
	Brake Booster Type and Size		in.	Single, 10	Single, 10	Single, 10	Single, 10
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
		Rear		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			14.4	14.4	14.4	14.4
	Power Steering Type			Electric Motor	Electric Motor	Electric Motor	Electric Motor

*1: With Roof Rail
*2: Models with Theft Deterrent System
*3: Only for A/T Models

Europe					
5-door Wagon (Short)					
Standard (4WD)	High (4WD)	Standard (4WD)	High (4WD)		Standard (4WD)
ACA30L-AWMXKW	ACA30L-AWMGKW	ACA30L-AWPXKW	ACA30L-AWPGKW	ACA31L-AWPGKW	ALA30R-AWFXYW
4395 (173.0)	4395 (173.0)	4395 (173.0)	4395 (173.0)	4395 (173.0)	4395 (173.0)
1815 (71.5)	1815 (71.5)	1815 (71.5)	1815 (71.5)	1815 (71.5)	1815 (71.5)
1685 (66.3), 1720 (67.7)*1	1685 (66.3), 1720 (67.7)*1	1685 (66.3), 1720 (67.7)*1	1685 (66.3), 1720 (67.7)*1	1685 (66.3), 1720 (67.7)*1	1685 (66.3), 1720 (67.7)*1
2560 (100.8)	2560 (100.8)	2560 (100.8)	2560 (100.8)	2560 (100.8)	2560 (100.8)
1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
1805 (71.1)	1805 (71.1)	1805 (71.1)	1805 (71.1)	1805 (71.1)	1805 (71.1)
—	—	—	—	—	—
—	—	—	—	—	—
860 (33.9)	860 (33.9)	860 (33.9)	860 (33.9)	860 (33.9)	860 (33.9)
975 (38.4)	975 (38.4)	975 (38.4)	975 (38.4)	975 (38.4)	975 (38.4)
195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
30	30	30	30	30	30
30	30	30	30	30	30
825 (1819)	825 (1819)	865 (1907)	865 (1907)	865 (1907)	950 (2094)
640 (1411)	640 (1411)	640 (1411)	640 (1411)	640 (1411)	635 (1400)
1465 (3230)	1465 (3230)	1505 (3318)	1505 (3318)	1505 (3318)	1585 (3494)
945 (2083)	950 (2094)	985 (2172)	990 (2183)	990 (2183)	1070 (2359)
1125 (2480)	1120 (2469)	1125 (2480)	1120 (2469)	1120 (2469)	1120 (2469)
2070 (4564)	2070 (4564)	2110 (4652)	2110 (4652)	2110 (4652)	2190 (4828)
60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)
0.45 (15.89)	0.45 (15.89)	0.45 (15.89)	0.45 (15.89)	0.45 (15.89)	0.45 (15.89)
185 (115)	185 (115)	175 (109)	175 (109)	175 (109)	180 (112)
—	—	—	—	—	—
—	—	—	—	—	—
17.2	17.2	18.3	18.3	18.3	10.5
47 (29)	47 (29)	63 (39)	63 (39)	63 (39)	41 (25)
89 (55)	89 (55)	113 (70)	113 (70)	113 (70)	82 (51)
136 (84)	136 (84)	—	—	—	128 (79)
177 (110)	177 (110)	—	—	—	178 (110)
5.1 (16.7)	5.1 (16.7)	5.1 (16.7)	5.1 (16.7)	5.1 (16.7)	5.1 (16.7)
—	—	—	—	—	—
1AZ-FE	1AZ-FE	1AZ-FE	1AZ-FE	2AZ-FE	2AD-FTV
16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
86.0 × 86.0 (3.39 × 3.39)	86.0 × 86.0 (3.39 × 3.39)	86.0 × 86.0 (3.39 × 3.39)	86.0 × 86.0 (3.39 × 3.39)	88.5 × 96.0 (3.48 × 3.78)	86.0 × 96.0 (3.39 × 3.78)
1998 (121.9)	1998 (121.9)	1998 (121.9)	1998 (121.9)	2362 (144.2)	2231 (136.1)
9.8 : 1	9.8 : 1	9.8 : 1	9.8 : 1	9.8 : 1	16.8 : 1
EFI	EFI	EFI	EFI	EFI	Common-rail Type
95 or higher	95 or higher	95 or higher	95 or higher	91 or higher	48 or higher
112/6000	112/6000	112/6000	112/6000	125/6000	100/3600
194/4000	194/4000	194/4000	194/4000	224/4000	310/2000 - 2800
12 - 48	12 - 48	12 - 48	12 - 48	12 - 55	12 - 64
1200	1200	1200	1200	1200	1560
1.3	1.3	1.3	1.3	1.7	2.0
Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	—	—	—	Dry, Single Plate Diaphragm
E352F	E352F	U140F	U140F	U140F	EA64F
3.833	3.833	3.938	3.938	3.938	3.818
2.045	2.045	2.194	2.194	2.194	1.913
1.333	1.333	1.411	1.411	1.411	1.218
1.028	1.028	1.019	1.019	1.019	0.880
0.820	0.820	—	—	—	0.809
—	—	—	—	—	0.711
3.583	3.583	3.141	3.141	3.141	4.139
4.562	4.562	3.291	3.291	3.080	4.312 (1-4), 3.631 (5-6&REV)
0.439/2.277	0.439/2.277	0.439/2.277	0.439/2.277	0.439/2.277	0.439/2.277
135 (5.3)	135 (5.3)	135 (5.3)	135 (5.3)	135 (5.3)	135 (5.3)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Solid Disc	Solid Disc	Solid Disc	Solid Disc	Solid Disc	Solid Disc
Duo Servo	Duo Servo	Duo Servo	Duo Servo	Duo Servo	Duo Servo
Single, 10	Single, 10	Single, 10	Single, 10	Single, 10	Single, 10
—	—	—	—	—	—
MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
14.4	14.4	14.4	14.4	14.4	14.4
Electric Motor	Electric Motor	Electric Motor	Electric Motor	Electric Motor	Electric Motor

Item \ Area				Europe			
Body Type				5-door Wagon (Short)			
Vehicle Grade				High (4WD)	Standard (4WD)	High (4WD)	
Model Code				ALA30R-AWFGYW	ALA30L-AWFXYW	ALA30L-AWFGYW	ALA30R-AWFGXW
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4395 (173.0)	4395 (173.0)	4395 (173.0)	4395 (173.0), 4315 (169.9)*1
		Width	mm (in.)	1815 (71.5)	1815 (71.5)	1815 (71.5)	1815 (71.5), 1855 (73.0)*2
		Height	mm (in.)	1685 (66.3), 1720 (67.7)*3	1685 (66.3), 1720 (67.7)*3	1685 (66.3), 1720 (67.7)*3	1685 (66.3), 1720 (67.7)*3
	Wheel Base		mm (in.)	2560 (100.8)	2560 (100.8)	2560 (100.8)	2560 (100.8)
	Tread	Front	mm (in.)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
		Rear	mm (in.)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
	Room	Length	mm (in.)	1805 (71.1)	1805 (71.1)	1805 (71.1)	1805 (71.1)
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	860 (33.9)	860 (33.9)	860 (33.9)	860 (33.9)
		Rear	mm (in.)	975 (38.4)	975 (38.4)	975 (38.4)	975 (38.4), 895 (35.2)*1
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
	Angle of Approach		degrees	30	30	30	30
	Angle of Departure		degrees	30	30	30	30
	Curb Weight	Front	kg (lb)	950 (2094)	950 (2094)	950 (2094)	960 (2116)
		Rear	kg (lb)	635 (1400)	635 (1400)	635 (1400)	635 (1400)
		Total	kg (lb)	1585 (3494)	1585 (3494)	1585 (3494)	1595 (3516)
	Gross Vehicle Weight	Front	kg (lb)	1070 (2359)	1070 (2359)	1070 (2359)	1080 (2381), 1105 (2436)*1
		Rear	kg (lb)	1120 (2469)	1120 (2469)	1120 (2469)	1110 (2447), 1085 (2392)*1
		Total	kg (lb)	2190 (4828)	2190 (4828)	2190 (4828)	2190 (4828)
	Fuel Tank Capacity		ℓ (Imp.gal.)	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)
	Luggage Compartment Capacity		m^3 (cu.ft.)	0.45 (15.89)	0.45 (15.89)	0.45 (15.89)	0.45 (15.89)
Performance	Max. Speed		km/h (mph)	180 (112)	180 (112)	180 (112)	200 (124)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Acceleration	0 to 100 km/h	sec.	—	—	—	—
		0 to 400 m	sec.	10.5	10.5	10.5	9.3
	Max. Permissible Speed	1st Gear	km/h (mph)	41 (25)	41 (25)	41 (25)	41 (25)
		2nd Gear	km/h (mph)	82 (51)	82 (51)	82 (51)	82 (51)
		3rd Gear	km/h (mph)	128 (79)	128 (79)	128 (79)	128 (79)
		4th Gear	km/h (mph)	178 (110)	178 (110)	178 (110)	178 (110)
	Min. Turning Radius	Tire	m (ft.)	5.1 (16.7)	5.1 (16.7)	5.1 (16.7)	5.1 (16.7)*4, 5.4 (17.7)*5
		Body	m (ft.)	—	—	—	5.5 (18.0)*4, 5.8 (19.0)*5
Engine	Engine Type			2AD-FTV	2AD-FTV	2AD-FTV	2AD-FHV
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)
	Displacement		cm^3 (cu.in.)	2231 (136.1)	2231 (136.1)	2231 (136.1)	2231 (136.1)
	Compression Ratio			16.8 : 1	16.8 : 1	16.8 : 1	15.8 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	100/3600	100/3600	100/3600	130/3600
	Max. Torque (EEC)		N·m/rpm	310/2000 - 2800	310/2000 - 2800	310/2000 - 2800	400/2000 - 2600
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 64	12 - 64	12 - 64	12 - 64
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	2.0	2.0	2.0	2.0
Chassis	Clutch Type			Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	Transaxle Type			EA64F	EA64F	EA64F	EA64F
	Gear Ratio (Counter Gear Ratio Included*3)	In First		3.818	3.818	3.818	3.818
		In Second		1.913	1.913	1.913	1.913
		In Third		1.218	1.218	1.218	1.218
		In Fourth		0.880	0.880	0.880	0.880
		In Fifth		0.809	0.809	0.809	0.809
		In Sixth		0.711	0.711	0.711	0.711
		In Reverse		4.139	4.139	4.139	4.139
	Differential Gear Ratio (Final)			4.312 (1-4), 3.631 (5-6&REV)	4.312 (1-4), 3.631 (5-6&REV)	4.312 (1-4), 3.631 (5-6&REV)	4.312 (1-4), 3.631 (5-6&REV)
	Transfer/Rear Differential Gear Ratio			0.439/2.277	0.439/2.277	0.439/2.277	0.439/2.277
	Rear Differential Gear Size		mm (in.)	135 (5.3)	135 (5.3)	135 (5.3)	135 (5.3)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Solid Disc	Solid Disc	Solid Disc	Solid Disc
	Parking Brake Type			Duo Servo	Duo Servo	Duo Servo	Duo Servo
	Brake Booster Type and Size		in.	Single, 10	Single, 10	Single, 10	Single, 10
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
		Rear		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			14.4	14.4	14.4	14.4, 14.6*5
	Power Steering Type			Electric Motor	Electric Motor	Electric Motor	Electric Motor

*1: Without Spare Tire
*2: With Over-fender
*3: With Roof Rail
*4: With 225/65R17 Tire
*5: With 235/55R18 Tire
*6: Only for A/T Models

Europe					Australia
5-door Wagon (Short)					5-door Wagon (Long)
High (4WD)	Standard (4WD)	High (4WD)	Standard (4WD)	High (4WD)	Standard (4WD)
ALA30L-AWFGXW	ALA30R-AWFXRW	ALA30R-AWFGRW	ALA30L-AWFXRW	ALA30L-AWFGRW	ACA33R-ANMXKQ
4395 (173.0), 4315 (169.9)*1	4395 (173.0)	4395 (173.0), 4315 (169.9)*1	4395 (173.0)	4395 (173.0), 4315 (169.9)*1	4600 (181.1)
1815 (71.5), 1855 (73.0)*2	1815 (71.5)	1815 (71.5)	1815 (71.5)	1815 (71.5), 1855 (73.0)*2	1815 (71.5)
1685 (66.3), 1720 (67.7)*3	1685 (66.3), 1720 (67.7)*3	1685 (66.3), 1720 (67.7)*3	1685 (66.3), 1720 (67.7)*3	1685 (66.3), 1720 (67.7)*3	1695 (66.7)
2560 (100.8)	2560 (100.8)	2560 (100.8)	2560 (100.8)	2560 (100.8)	2660 (104.7)
1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
1805 (71.1)	1805 (71.1)	1805 (71.1)	1805 (71.1)	1805 (71.1)	1950 (76.8)
—	—	—	—	—	—
—	—	—	—	—	—
860 (33.9)	860 (33.9)	860 (33.9)	860 (33.9)	860 (33.9)	855 (33.7)
975 (38.4), 895 (35.2)*1	975 (38.4)	975 (38.4)	975 (38.4)	975 (38.4), 895 (35.2)*1	1085 (42.7)
195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
30	30	30	30	30	30
30	30	30	30	30	30
960 (2116)	950 (2094)	950 (2094)	950 (2094)	960 (2116)	850 (1874)
635 (1400)	635 (1400)	635 (1400)	635 (1400)	635 (1400)	700 (1543)
1595 (3516)	1585 (3494)	1585 (3494)	1585 (3494)	1595 (3516)	1550 (3417)
1080 (2381), 1105 (2436)*1	1070 (2359)	1070 (2359)	1070 (2359)	1080 (2381), 1105 (2436)*1	950 (2094)
1110 (2447), 1085 (2392)*1	1120 (2469)	1120 (2469)	1120 (2469)	1110 (2447), 1085 (2392)*1	1110 (2447)
2190 (4828)	2190 (4828)	2190 (4828)	2190 (4828)	2190 (4828)	2060 (4542)
60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)
0.45 (15.89)	0.45 (15.89)	0.45 (15.89)	0.45 (15.89)	0.45 (15.89)	0.54 (19.07)
200 (124)	180 (112)	180 (112)	180 (112)	200 (124)	190 (118)
—	—	—	—	—	—
—	—	—	—	—	—
9.3	10.5	10.5	10.5	9.3	16.6
41 (25)	41 (25)	41 (25)	41 (25)	41 (25)	47 (29)
82 (51)	82 (51)	82 (51)	82 (51)	82 (51)	95 (59)
128 (79)	128 (79)	128 (79)	128 (79)	128 (79)	145 (90)
178 (110)	178 (110)	178 (110)	178 (110)	178 (110)	187 (116)
5.1 (16.7)*4, 5.4 (17.7)*5	5.1 (16.7)	5.1 (16.7)	5.1 (16.7)	5.1 (16.7)*4, 5.4 (17.7)*5	5.3 (17.4)
5.5 (18.0)*4, 5.8 (19.0)*5	—	—	—	5.5 (18.0)*4, 5.8 (19.0)*5	5.7 (18.7)
2AD-FHV	2AD-FTV	2AD-FTV	2AD-FTV	2AD-FTV	2AZ-FE
16-valve, DOHC	16-valve DOHC	16-valve DOHC	16-valve DOHC	16-valve DOHC	16-valve, DOHC
86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	86.0 × 96.0 (3.39 × 3.78)	88.5 × 96.0 (3.48 × 3.78)
2231 (136.1)	2231 (136.1)	2231 (136.1)	2231 (136.1)	2231 (136.1)	2362 (144.2)
15.8 : 1	16.8 : 1	16.8 : 1	16.8 : 1	16.8 : 1	9.8 : 1
Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	EFI
48 or higher	48 or higher	48 or higher	48 or higher	48 or higher	91 or higher
130/3600	100/3600	100/3600	100/3600	100/3600	125/6000
400/2000 - 2600	310/2000 - 2800	310/2000 - 2800	310/2000 - 2800	310/2000 - 2800	224/4000
12 - 64	12 - 64	12 - 64	12 - 64	12 - 64	12 - 48
1560	1560	1560	1560	1560	1200
2.0	2.0	2.0	2.0	2.0	1.6
Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
EA64F	EA64F	EA64F	EA64F	EA64F	E359F
3.818	3.818	3.818	3.818	3.818	3.833
1.913	1.913	1.913	1.913	1.913	1.913
1.218	1.218	1.218	1.218	1.218	1.258
0.880	0.880	0.880	0.880	0.880	0.972
0.809	0.809	0.809	0.809	0.809	0.775
0.711	0.711	0.711	0.711	0.711	—
4.139	4.139	4.139	4.139	4.139	3.583
4.312 (1-4), 3.631 (5-6&REV)	4.312 (1-4), 3.631 (5-6&REV)	4.312 (1-4), 3.631 (5-6&REV)	4.312 (1-4), 3.631 (5-6&REV)	4.312 (1-4), 3.631 (5-6&REV)	4.562
0.439/2.277	0.439/2.277	0.439/2.277	0.439/2.277	0.439/2.277	0.439/2.277
135 (5.3)	135 (5.3)	135 (5.3)	135 (5.3)	135 (5.3)	135 (5.3)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Solid Disc	Solid Disc	Solid Disc	Solid Disc	Solid Disc	Solid Disc
Duo Servo	Duo Servo	Duo Servo	Duo Servo	Duo Servo	Duo Servo
Single, 10	Single, 10	Single, 10	Single, 10	Single, 10	Single, 10
—	—	—	—	—	—
MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
14.4, 14.6*5	14.4	14.4	14.4	14.4	14.4
Electric Motor	Electric Motor	Electric Motor	Electric Motor	Electric Motor	Electric Motor

Item \ Area				Australia			
Body Type				5-door Wagon (Long)			
Vehicle Grade				High (4WD)	Standard (4WD)	High (4WD)	Standard (4WD)
Model Code				ACA33R-ANMGKQ	ACA33R-ANPXKQ	ACA33R-ANPGKQ	GSA33R-ANAXKQ
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4600 (181.1)	4600 (181.1)	4600 (181.1)	4600 (181.1)
		Width	mm (in.)	1855 (73.0)	1815 (71.5)	1855 (73.0)	1815 (71.5)
		Height	mm (in.)	1730 (68.1)	1695 (66.7)	1730 (68.1)	1695 (66.7)
	Wheel Base		mm (in.)	2660 (104.7)	2660 (104.7)	2660 (104.7)	2660 (104.7)
	Tread	Front	mm (in.)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
		Rear	mm (in.)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
	Room	Length	mm (in.)	1950 (76.8)	1950 (76.8)	1950 (76.8)	1865 (73.4)
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)
		Rear	mm (in.)	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	195 (7.7)	195 (7.7)	200 (7.9)
	Angle of Approach		degrees	30	30	30	30
	Angle of Departure		degrees	30	30	30	26
	Curb Weight	Front	kg (lb)	850 (1874)	895 (1973)	895 (1973)	975 (2150)
		Rear	kg (lb)	700 (1543)	695 (1532)	695 (1532)	680 (1499)
		Total	kg (lb)	1550 (3417)	1590 (3505)	1590 (3505)	1655 (3649)
	Gross Vehicle Weight	Front	kg (lb)	960 (2116)	995 (2194)	1005 (2216)	1075 (2370)
		Rear	kg (lb)	1100 (2425)	1105 (2436)	1095 (2414)	1095 (2414)
		Total	kg (lb)	2060 (4542)	2100 (4630)	2100 (4630)	2170 (4784)
	Fuel Tank Capacity		ℓ (Imp.gal.)	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)
	Luggage Compartment Capacity		m^3 (cu.ft.)	0.54 (19.07)	0.54 (19.07)	0.54 (19.07)	0.54 (19.07)
Performance	Max. Speed		km/h (mph)	190 (118)	180 (112)	180 (112)	—
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Acceleration	0 to 100 km/h	sec.	—	—	—	—
		0 to 400 m	sec.	16.6	17.5	17.5	—
	Max. Permissible Speed	1st Gear	km/h (mph)	47 (29)	67 (42)	67 (42)	—
		2nd Gear	km/h (mph)	95 (59)	120 (74)	120 (74)	—
		3rd Gear	km/h (mph)	145 (90)	—	—	—
		4th Gear	km/h (mph)	187 (116)	—	—	—
	Min. Turning Radius	Tire	m (ft.)	5.3 (17.4)	5.3 (17.4)	5.3 (17.4)	—
		Body	m (ft.)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	—
Engine	Engine Type			2AZ-FE	2AZ-FE	2AZ-FE	2GR-FE
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	24-valve, DOHC with Dual VVT-i
	Bore × Stroke		mm (in.)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)	94.0 × 83.0 (3.70 × 3.27)
	Displacement		cm^3 (cu.in.)	2362 (144.2)	2362 (144.2)	2362 (144.2)	3456 (210.9)
	Compression Ratio			9.8 : 1	9.8 : 1	9.8 : 1	10.8 : 1
	Fuel System			EFI	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	91 or higher	91 or higher
	Max. Output (EEC)		kW/rpm	125/6000	125/6000	125/6000	201/6200
	Max. Torque (EEC)		N·m/rpm	224/4000	224/4000	224/4000	333/4700
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 48	12 - 48	12 - 48	12 - 55
	Alternator Output		Watts	1200	1200	1200	1800
	Starter Output		kW	1.6	1.6	1.6	1.7
Chassis	Clutch Type			Dry, Single Plate Diaphragm	—	—	—
	Transaxle Type			E359F	U140F	U140F	U151F
	Gear Ratio (Counter Gear Ratio Included*3)	In First		3.833	3.938	3.938	4.235
		In Second		1.913	2.194	2.194	2.360
		In Third		1.258	1.411	1.411	1.517
		In Fourth		0.972	1.019	1.019	1.047
		In Fifth		0.775	—	—	0.756
		In Sixth		—	—	—	—
		In Reverse		3.583	3.141	3.141	3.378
	Differential Gear Ratio (Final)			4.562	3.080	3.080	3.080
	Transfer/Rear Differential Gear Ratio			0.439/2.277	0.439/2.277	0.439/2.277	0.439/2.277
	Rear Differential Gear Size		mm (in.)	135 (5.3)	135 (5.3)	135 (5.3)	135 (5.3)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Solid Disc	Solid Disc	Solid Disc	Solid Disc
	Parking Brake Type			Duo Servo	Duo Servo	Duo Servo	Duo Servo
	Brake Booster Type and Size		in.	Single, 10	Single, 10	Single, 10	Single, 10
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
		Rear		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			14.4	14.4	14.4	14.6
	Power Steering Type			Electric Motor	Electric Motor	Electric Motor	Electric Motor

*1: Only for A/T Models
*2: For China, Beijing

Australia	G.C.C. Countries			General Countries	
5-door Wagon (Long)					
High (4WD)	Standard (4WD)		High (4WD)	Standard (4WD)	
GSA33R-ANAGKQ	ACA33L-ANMXKV	ACA33L-ANPXKV	ACA33L-ANPGKV	ACA33L-ANMXK	ACA33L-ANPXK
4600 (181.1)	4600 (181.1)	4600 (181.1)	4600 (181.1)	4600 (181.1)	4600 (181.1)
1855 (73.0)	1815 (71.5)	1815 (71.5)	1855 (73.0)	1815 (71.5)	1815 (71.5)
1730 (68.1)	1685 (66.3)	1685 (66.3)	1720 (67.7)	1685 (66.3)	1685 (66.3)
2660 (104.7)	2660 (104.7)	2660 (104.7)	2660 (104.7)	2660 (104.7)	2660 (104.7)
1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
1865 (73.4)	1950 (76.8)	1950 (76.8)	1950 (76.8)	1950 (76.8)	1950 (76.8)
—	—	—	—	—	—
—	—	—	—	—	—
855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)
1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)
200 (7.9)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
30	30	30	30	30	30
26	30	30	30	30	30
975 (2150)	850 (1874)	895 (1973)	895 (1973)	850 (1874)	890 (1962)
680 (1499)	700 (1543)	695 (1532)	695 (1532)	695 (1532)	695 (1532)
1655 (3649)	1550 (3417)	1590 (3505)	1590 (3505)	1545 (3406)	1585 (3494)
1085 (2392)	950 (2094)	995 (2194)	1015 (2238)	950 (2094)	990 (2183)
1085 (2392)	1110 (2447)	1105 (2436)	1085 (2392)	1110 (2447)	1110 (2447)
2170 (4784)	2060 (4542)	2100 (4630)	2100 (4630)	2060 (4542)	2100 (4630)
60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)
0.54 (19.07)	0.54 (19.07)	0.54 (19.07)	0.54 (19.07)	0.54 (19.07)	0.54 (19.07)
—	190 (118)	180 (112)	180 (112)	190 (118)	180 (112)
—	—	—	—	—	—
—	—	—	—	—	—
—	16.6	17.5	17.5	16.6	17.5
—	47 (29)	67 (42)	67 (42)	47 (29)	67 (42)
—	95 (59)	120 (42)	120 (74)	95 (59)	120 (74)
—	145 (90)	—	—	145 (90)	—
—	187 (116)	—	—	187 (116)	—
—	5.3 (17.4)	5.3 (17.4)	5.3 (17.4)	5.3 (17.4)	5.3 (17.4)
—	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
2GR-FE	2AZ-FE	2AZ-FE	2AZ-FE	2AZ-FE	2AZ-FE
24-valve, DOHC with Dual VVT-i	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
94.0 × 83.0 (3.70 × 3.27)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)
3456 (210.9)	2362 (144.2)	2362 (144.2)	2362 (144.2)	2362 (144.2)	2362 (144.2)
10.8 : 1	9.8 : 1	9.8 : 1	9.8 : 1	9.8 : 1	9.8 : 1
EFI	EFI	EFI	EFI	EFI	EFI
95 or higher	91 or higher	91 or higher	91 or higher	91 or higher	91 or higher
202/6200	125/6000	125/6000	125/6000	125/6000	125/6000
340/4700	224/4000	224/4000	224/4000	224/4000	224/4000
12 - 55	12 - 48	12 - 48	12 - 48, 55*2	12 - 48	12 - 48
1800	1200	1200	1200	1200	1200
1.7	1.6	1.6	1.6, 1.7*2	1.6	1.6
—	Dry, Single Plate Diaphragm	—	—	Dry, Single Plate Diaphragm	—
U151F	E359F	U140F	U140F	E359F	U140F
4.235	3.833	3.938	3.938	3.833	3.938
2.360	1.913	2.194	2.194	1.913	2.194
1.517	1.258	1.411	1.411	1.258	1.411
1.047	0.972	1.019	1.019	0.972	1.019
0.756	0.775	—	—	0.775	—
—	—	—	—	—	—
3.378	3.583	3.141	3.141	3.583	3.141
3.080	4.562	3.080	3.080	4.562	3.080
0.439/2.277	0.439/2.277	0.439/2.277	0.439/2.277	0.439/2.277	0.439/2.277
135 (5.3)	135 (5.3)	135 (5.3)	135 (5.3)	135 (5.3)	135 (5.3)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Solid Disc	Solid Disc	Solid Disc	Solid Disc	Solid Disc	Solid Disc
Duo Servo	Duo Servo	Duo Servo	Duo Servo	Duo Servo	Duo Servo
Single, 10	Single, 10	Single, 10	Single, 10	Single, 10	Single, 10
—	—	—	—	—	—
MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
14.6	14.4	14.4	14.4	14.4	14.4
Electric Motor	Electric Motor	Electric Motor	Electric Motor	Electric Motor	Electric Motor

Item \ Area			General Countries			
Body Type			5-door Wagon (Long)			
Vehicle Grade			High (4WD)	Standard (2WD)		High (2WD)
Model Code			ACA33L-ANPGK	ACA38L-ANMXK	ACA38L-ANPXK	ACA38L-ANPGK
Major Dimensions & Vehicle Weights	Overall	Length mm (in.)	4600 (181.1)	4600 (181.1)	4600 (181.1)	4600 (181.1)
		Width mm (in.)	1815 (71.5), 1855 (73.0)*1	1815 (71.5)	1815 (71.5)	1815 (71.5)
		Height mm (in.)	1720 (67.7)	1685 (66.3)	1685 (66.3)	1720 (67.7)
	Wheel Base	mm (in.)	2660 (104.7)	2660 (104.7)	2660 (104.7)	2660 (104.7)
	Tread	Front mm (in.)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
		Rear mm (in.)	1560 (61.4)	1560 (61.4)	1560 (61.4)	1560 (61.4)
	Room	Length mm (in.)	1950 (76.8)	1950 (76.8)	1950 (76.8)	1950 (76.8)
		Width mm (in.)	—	—	—	—
		Height mm (in.)	—	—	—	—
	Overhang	Front mm (in.)	855 (33.7)	855 (33.7)	855 (33.7)	855 (33.7)
		Rear mm (in.)	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)
	Min. Running Ground Clearance	mm (in.)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
	Angle of Approach	degrees	30	30	30	30
	Angle of Departure	degrees	30	30	30	30
	Curb Weight	Front kg (lb)	890 (1962)	830 (1830)	870 (1918)	870 (1918)
		Rear kg (lb)	695 (1532)	655 (1444)	650 (1433)	650 (1433)
		Total kg (lb)	1585 (3494)	1485 (3274)	1520 (3351)	1520 (3351)
	Gross Vehicle Weight	Front kg (lb)	1000 (2205)	930 (2050)	970 (2138)	975 (2150)
		Rear kg (lb)	1110 (2447)	1070 (2359)	1070 (2359)	1065 (2348)
		Total kg (lb)	2100 (4630)	2000 (4409)	2040 (4497)	2040 (4497)
	Fuel Tank Capacity	ℓ (Imp.gal.)	60 (13.2)	60 (13.2)	60 (13.2)	60 (13.2)
	Luggage Compartment Capacity	m^3 (cu.ft.)	0.54 (19.07)	0.54 (19.07)	0.54 (19.07)	0.54 (19.07)
Performance	Max. Speed	km/h (mph)	180 (112)	190 (118)	180 (112)	180 (112)
	Max. Cruising Speed	km/h (mph)	—	—	—	—
	Acceleration	0 to 100 km/h sec.	—	—	—	—
		0 to 400 m sec.	17.5	16.6	17.5	17.5
	Max. Permissible Speed	1st Gear km/h (mph)	67 (42)	55 (34)	70 (43)	70 (43)
		2nd Gear km/h (mph)	120 (74)	103 (64)	126 (78)	126 (78)
		3rd Gear km/h (mph)	—	158 (98)	—	—
		4th Gear km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire m (ft.)	5.3 (17.4)	5.3 (17.4)	5.3 (17.4)	5.3 (17.4)
		Body m (ft.)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
Engine	Engine Type		2AZ-FE	2AZ-FE	2AZ-FE	2AZ-FE
	Valve Mechanism		16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke	mm (in.)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)
	Displacement	cm^3 (cu.in.)	2362 (144.2)	2362 (144.2)	2362 (144.2)	2362 (144.2)
	Compression Ratio		9.8 : 1	9.8 : 1	9.8 : 1	9.8 : 1
	Fuel System		EFI	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)		91 or higher	91 or higher	91 or higher	91 or higher
	Max. Output (EEC)	kW/rpm	125/6000	125/6000	125/6000	125/6000
	Max. Torque (EEC)	N·m/rpm	224/4000	224/4000	224/4000	224/4000
Engine Electrical	Battery Capacity (5HR)	Voltage & Amp. hr.	12 - 48	12 - 48	12 - 48	12 - 48
	Alternator Output	Watts	1200	1200	1200	1200
	Starter Output	kW	1.6	1.6	1.6	1.6
Chassis	Clutch Type		—	Dry, Single Plate Diaphragm	—	—
	Transaxle Type		U140F	E352	U241E	U241E
	Gear Ratio (Counter Gear Ratio Included*3)	In First	3.938	3.833	3.943	3.943
		In Second	2.194	2.045	2.197	2.197
		In Third	1.411	1.333	1.413	1.413
		In Fourth	1.019	1.028	1.020	1.020
		In Fifth	—	0.820	—	—
		In Sixth	—	—	—	—
		In Reverse	3.141	3.583	3.145	3.145
	Differential Gear Ratio (Final)		3.080	3.944	2.923	2.923
	Transfer/Rear Differential Gear Ratio		0.439/2.277	—	—	—
	Rear Differential Gear Size	mm (in.)	135 (5.3)	—	—	—
	Brake Type	Front	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear	Solid Disc	Solid Disc	Solid Disc	Solid Disc
	Parking Brake Type		Duo Servo	Duo Servo	Duo Servo	Duo Servo
	Brake Booster Type and Size	in.	Single, 10	Single, 10	Single, 10	Single, 10
	Proportioning Valve Type		—	—	—	—
	Suspension Type	Front	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
		Rear	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Stabilizer Bar	Front	Standard	Standard	Standard	Standard
		Rear	Standard	—	—	—
	Steering Gear Type		Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)		14.4	14.4	14.4	14.4
	Power Steering Type		Electric Motor	Electric Motor	Electric Motor	Electric Motor

*1: With over fender
*2: Only for A/T Models