MAJOR TECHNICAL SPECIFICATIONS

Item / Area				U.S.A. and Mexico		U.S.A. and Canada	
Body Type				Wagon			
Vehicle Grade				SR5	Limited	SR5	Limited
Model Code				UCK60L-GKASKA	UCK60L-GKALKA	UCK65L-GKASKA	UCK65L-GKALKA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5210 (205.1)	5210 (205.1)	5210 (205.1)	5210 (205.1)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1955 (77.0), 1895 (74.6)*1	1955 (77.0)	1955 (77.0), 1895 (74.6)*1	1955 (77.0)
	Wheel Base		mm (in.)	3100 (122.0)	3100 (122.0)	3100 (122.0)	3100 (122.0)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1755 (69.1)	1755 (69.1)	1755 (69.1)	1755 (69.1)
	Effective Head Room	Front	mm (in.)	—	—	—	—
		Rear	mm (in.)	—	—	—	—
	Effective Leg Room	Front	mm (in.)	—	—	—	—
		Rear	mm (in.)	—	—	—	—
	Shoulder Room	Front	mm (in.)	—	—	—	—
		Rear	mm (in.)	—	—	—	—
	Cargo Space	**Length**	**mm (in.)**	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance		mm (in.)	—	—	—	—
	Angle of Approach		degrees	26.9	26.9	27.1	27.2
	Angle of Departure		degrees	—	—	—	—
	Curb Weight	Front	kg (lb)	1267 (2795)	1267 (2795)	1374 (3030)	1372 (3025)
		Rear	kg (lb)	1308 (2885)	1317 (2905)	1310 (2890)	1315 (2900)
		Total	kg (lb)	2575 (5680)	2584 (5700)	2684 (5920)	2687 (5925)
	Gross Vehicle Weight	Front	kg (lb)	1385 (3055)	1372 (3025)	1481 (3267)	1468 (3237)
		Rear	kg (lb)	1771 (3905)	1784 (3935)	1811 (3993)	1824 (4023)
		Total	kg (lb)	3156 (6960)	3156 (6960)	3292 (7260)	3292 (7260)
	Fuel Tank Capacity		ℓ (U.S. gal., Imp. gal.)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	180 (111)	180 (111)	180 (111), 170 (105)*2	180 (111) 170 (105)*2
	Max. Cruising Speed		km/h (mph)	180 (111)	180 (111)	180 (111) 170 (105)*2	180 (111) 170 (105)*2
	Max. Permissible Speed	1st Gear	km/h (mph)	61 (37), 55 (34)*2	61 (37), 55 (34)*2	61 (37)*4, 55 (34)*2, 4 23 (14)*5, 21 (13)*2, 5	61 (37)*4, 55 (34)*2, 4 23 (14)*5, 21 (13)*2, 5
		2nd Gear	km/h (mph)	105 (65), 96 (59)*2	105 (65), 96 (59)*2	105 (65)*4, 96 (59)*2, 4 40 (24)*5, 36 (22)*2, 5	105 (65)*4, 96 (59)*2, 4 40 (24)*5, 36 (22)*2, 5
		3rd Gear	km/h (mph)	154 (95), 140 (87)*2	154 (95), 140 (87)*2	154 (95)*4, 140 (87)*2, 4 58 (36)*5, 53 (32)*2, 5	154 (95)*4, 140 (87)*2, 4 58 (36)*5, 53 (32)*2, 5
		4th Gear	km/h (mph)	180 (111)	180 (111)	180 (111)*4, 170 (105)*2, 4 68 (42)*5, 64 (39)*2, 5	180 (111)*4, 170 (105)*2, 4 68 (42)*5, 64 (39)*2, 5
		5th Gear	km/h (mph)	180 (111)	180 (111)	180 (111)*4, 170 (105)*2, 4 68 (42)*5, 64 (39)*2, 5	180 (111)*4, 170 (105)*2, 4 68 (42)*5, 64 (39)*2, 5
		6th Gear	km/h (mph)	—	—	—	—
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	—	—	—	—
		Curb to Curb	m (ft.)	—	—	—	—
Engine	Engine Type			2UZ-FE	2UZ-FE	2UZ-FE	2UZ-FE
	Valve Mechanism			32-valve DOHC with VVT-i	32-valve DOHC with VVT-i	32-valve DOHC with VVT-i	32-valve DOHC with VVT-i
	Bore × Stroke		mm (in.)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)	94.0 × 84.0 (3.70 × 3.31)
	Displacement		cm^3 (cu.in.)	4664 (284.5)	4664 (284.5)	4664 (284.5)	4664 (284.5)
	Compression Ratio			10.0 : 1	10.0 : 1	10.0 : 1	10.0 : 1
	Fuel System			SFI	SFI	SFI	SFI
	Octane Rating			87 or higher	87 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)		kW/rpm (HP/rpm)	206/5400 (276/5400)	206/5400 (276/5400)	206/5400 (276/5400)	206/5400 (276/5400)
	Max. Torque (SAE-NET)		N·m/rpm (ft-lbf/rpm)	426/3400 (314/3400)	426/3400 (314/3400)	426/3400 (314/3400)	426/3400 (314/3400)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 64	12 - 64	12 - 64	12 - 64
	Generator Output		Watts	1560, 1800*2	1560, 1800*2	1560, 1800*2	1560, 1800*2
	Starter Output		kW	2.0	2.0	2.0	2.0
Chassis	Clutch Type			—	—	—	—
	Transmission Type			A750E	A750E	A750F	A750F
	Gear Ratio	In First		3.520	3.520	3.520	3.520
		In Second		2.042	2.042	2.042	2.042
		In Third		1.400	1.400	1.400	1.400
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.716	0.716	0.716	0.716
		In Sixth		—	—	—	—
		In Reverse		3.224	3.224	3.224	3.224
	Transfer Gear Ratio 2WD/H4/L4			—	—	1.000/1.000/2.618	1.000/1.000/2.618
	Differential Gear Ratio (Front/Rear)			—/3.909, 4.300*2	—/3.909, 4.300*2	3.909, 4.300*2/3.909, 4.300*2	3.909, 4.300*2/3.909, 4.300*2
	Differential Gear Size (Front/Rear)		mm (in.)	—/252(9.92)	—/252 (9.92)	220 (8.66)/252 (9.92)	220 (8.66)/252 (9.92)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Double-wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18.0	18.0	18.0	18.0
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Without Roof Ruck
*2: Towing Package
*3: Leather Package or With RSE
*4: Transfer in 2WD or H4
*5: Transfer in L4

U.S.A.			U.S.A. and Canada		
Wagon					
SR5	Limited	Platinum	SR5	Limited	Platinum
USK60L-GKTSKA	USK60L-GKTLKA	USK60L-GKTZKA	USK65L-GKTSKA	USK65L-GKTLKA	USK65L-GKTZKA
5210 (205.1)	5210 (205.1)	5210 (205.1)	5210 (205.1)	5210 (205.1)	5210 (205.1)
2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
1955 (77.0), 1895 (74.6)*1	1955 (77.0)	1955 (77.0)	1955 (77.0), 1895 (74.6)*1	1955 (77.0)	1955 (77.0)
3100 (122.0)	3100 (122.0)	3100 (122.0)	3100 (122.0)	3100 (122.0)	3100 (122.0)
1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
1755 (69.1)	1755 (69.1)	1755 (69.1)	1755 (69.1)	1755 (69.1)	1755 (69.1)
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
—	—	—	—	—	—
26.9	26.9	27.0	27.0	27.0	27.2
—	—	—	—	—	—
1281 (2825)	1276 (2815)	1281 (2825)	1390 (3065)	1387 (3060)	1390 (3065)
1317 (2905)	1322 (2915)	1326 (2925)	1344 (2965)	1347 (2970)	1351 (2980)
2598 (5730)	2598 (5730)	2607 (5750)	2734 (6030)	2734 (6030)	2741 (6045)
1385 (3055)	1385 (3055)	1346 (2969)	1504 (3317)	1490 (3287)	1467 (3235)
1825 (4025)	1825 (4025)	1864 (4111)	1797 (3963)	1811 (3993)	1834 (4045)
3210 (7080)	3210 (7080)	3210 (7080)	3301 (7280)	3301 (7280)	3301 (7280)
100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
—	—	—	—	—	—
180 (111)	180 (111)	180 (111)	180 (111)	180 (111)	180 (111)
180 (111)	180 (111)	180 (111)	180 (111)	180 (111)	180 (111)
65 (40), 59 (36)*2	65 (40), 59 (36)*2	65 (40), 59 (36)*2	62 (38)*4, 59 (36)*2, 4 23 (14)*5, 22 (13)*2, 5	62 (38)*4, 59 (36)*2, 4 23 (14)*5, 22 (13)*2, 5	62 (38)*4, 59 (36)*2, 4 23 (14)*5, 22 (13)*2, 5
112 (69), 101 (62)*2	112 (69), 101 (62)*2	112 (69), 101 (62)*2	106 (65)*4, 101 (62)*2, 4 40 (24)*5, 38 (23)*2, 5	106 (65)*4, 101 (62)*2, 4 40 (24)*5, 38 (23)*2, 5	106 (65)*4, 101 (62)*2, 4 40 (24)*5, 38 (23)*2, 5
154 (95), 147 (91)*2	154 (95), 147 (91)*2	154 (95), 147 (91)*2	154 (95)*4, 147 (91)*2, 4 58 (36)*5, 56 (34)*2, 5	154 (95)*4, 147 (91)*2, 4 58 (36)*5, 56 (34)*2, 5	154 (95)*4, 147 (91)*2, 4 58 (36)*5, 56 (34)*2, 5
180 (111)	180 (111)	180 (111)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
180 (111)	180 (111)	180 (111)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
180 (111)	180 (111)	180 (111)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
—	—	—	—	—	—
—	—	—	—	—	—
3UR-FE	3UR-FE	3UR-FE	3UR-FE	3UR-FE	3UR-FE
32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)
10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
SFI	SFI	SFI	SFI	SFI	SFI
87 or higher	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher
284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)	284/5600 (381/5600)
544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)	544/3600 (401/3600)
12 - 64	12 - 64	12 - 64	12 - 64	12 - 64	12 - 64
1560, 1800*3, 2160*2	1800, 2160*2	1800, 2160*2	1560, 1800*3, 2160*2	1800, 2160*2	1800, 2160*2
2.0	2.0	2.0	2.0	2.0	2.0
—	—	—	—	—	—
AB60E	AB60E	AB60E	AB60F	AB60F	AB60F
3.333	3.333	3.333	3.333	3.333	3.333
1.960	1.960	1.960	1.960	1.960	1.960
1.353	1.353	1.353	1.353	1.353	1.353
1.000	1.000	1.000	1.000	1.000	1.000
0.728	0.728	0.728	0.728	0.728	0.728
0.588	0.588	0.588	0.588	0.588	0.588
3.061	3.061	3.061	3.061	3.061	3.061
—	—	—	1.000/1.000/2.618	1.000/1.000/2.618	1.000/1.000/2.618
—/3.909, 4.300*2	—/3.909, 4.300*2	—/3.909, 4.300*2	3.909, 4.300*2/3.909, 4.300*2	3.909, 4.300*2/3.909, 4.300*2	3.909, 4.300*2/3.909, 4.300*2
—/252 (9.92)	—/252 (9.92)	—/252 (9.92)	220 (8.66)/252 (9.92)	220 (8.66)/252 (9.92)	220 (8.66)/252 (9.92)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
18.0	18.0	18.0	18.0	18.0	18.0
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type