■ FEATURES OF 3UR-FE ENGINE

The 3UR-FE engine has achieved the following performance through the use of the items listed below.

(1) High performance and reliability

(2) Low noise and vibration

(3) Lightweight and compact design

(4) Good serviceability

(5) Clean emission and fuel economy

Item		(1)	(2)	(3)	(4)	(5)
Engine Proper	A taper squish shape is used for the combustion chamber.	○				○
	An aluminum alloy cylinder block containing an engine coolant distribution pathway is used.	○		○		
	Spiny-type liners are used in the cylinder bores.	○		○		
	Water jacket spacers are used.	○				
	The piston skirt is coated with resin.	○	○			○
	A No. 1 oil pan made of aluminum alloy is used.	○	○	○		
Valve Mechanism	Timing chains and chain tensioners are used.	○		○		
	Hydraulic lash adjusters are used.	○	○		○	○
	Roller rocker arms are used.	○				○
Lubrication System	An oil filter with a replaceable element is used.				○	
	A water-cooled type oil cooler is used.*	○				
Cooling System	TOYOTA Genuine SLLC (Super Long Life Coolant) is used.				○	
Intake and Exhaust System	A carbon filter is used in the air cleaner cap.					○
	A linkless-type throttle body is used.	○		○		
	An intake manifold made of plastic is used.	○		○		
	Stainless steel exhaust manifolds are used.	○		○		○
	Ceramic type TWCs (Three-Way Catalytic converters) are used.					○
Fuel System	12-hole type fuel injectors are used to improve the atomization of fuel.	○				○
	A fuel delivery pipe with an integrated pulsation damper function is used.			○		
Ignition System	The DIS (Direct Ignition System) makes ignition timing adjustment unnecessary.	○			○	○
	Long-reach type iridium-tipped spark plugs are used.	○			○	○

*: Optional Equipment

(Continued)

Item		(1)	(2)	(3)	(4)	(5)
Charging System	A segment conductor type generator is used.	○		○		
Starting System	A planetary reduction type starter is used.			○		
Serpentine Belt Drive System	A serpentine belt drive system is used.			○	○	
Blowby Gas Ventilation System	A separator case is provided between the cylinder block and the intake manifold.	○				○
Engine Control System	MRE (Magnetic Resistance Element) type crankshaft position, camshaft position, and VVT sensors are used.	○				
	The ETCS-i (Electronic Throttle Control System-intelligent) is used.	○				○
	The Dual VVT-i (Variable Valve Timing-intelligent) system is used.	○				○
	The ACIS (Acoustic Control Induction System) is used.	○				○
	An air injection system is used.					○
	The starter control (cranking hold function) is used.	○				
	An evaporative emission control system is used.					○