MAJOR TECHNICAL SPECIFICATIONS

Item / Area			U.S.A. and Mexico		U.S.A. and Canada	
Body Type			Wagon			
Vehicle Grade			SR5	Limited	SR5	Limited
Model Code			UPK60L-GKTSKA	UPK60L-GKTLKA	UPK65L-GKTSKA	UPK65L-GKTLKA
Major Dimensions & Vehicle Weights	Overall	Length mm (in.)	5210 (205.1)	5210 (205.1)	5210 (205.1)	5210 (205.1)
		Width mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height mm (in.)	1955 (77.0), 1895 (74.6)*1	1955 (77.0)	1955 (77.0), 1895 (74.6)*1	1955 (77.0)
	Wheel Base	mm (in.)	3100 (122.0)	3100 (122.0)	3100 (122.0)	3100 (122.0)
	Tread	Front mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear mm (in.)	1755 (69.1)	1755 (69.1)	1755 (69.1)	1755 (69.1)
	Effective Head Room	Front mm (in.)	—	—	—	—
		Rear No. 1 mm (in.)	—	—	—	—
		Rear No. 2 mm (in.)	—	—	—	—
	Effective Leg Room	Front mm (in.)	—	—	—	—
		Rear No. 1 mm (in.)	—	—	—	—
		Rear No. 2 mm (in.)	—	—	—	—
	Shoulder Room	Front mm (in.)	—	—	—	—
		Rear No. 1 mm (in.)	—	—	—	—
		Rear No. 2 mm (in.)	—	—	—	—
	Cargo Space	Length mm (in.)	—	—	—	—
		Width mm (in.)	—	—	—	—
		Height mm (in.)	—	—	—	—
	Overhang	Front mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance	mm (in.)	—	—	—	—
	Angle of Approach	degrees	26.9	26.9	27.1	27.1
	Angle of Departure	degrees	—	—	—	—
	Curb Weight	Front kg (lb)	1263 (2785)	1263 (2785)	1376 (3035)	1374 (3030)
		Rear kg (lb)	1308 (2885)	1317 (2905)	1331 (2935)	1335 (2945)
		Total kg (lb)	2571 (5670)	2580 (5690)	2707 (5970)	2710 (5975)
	Gross Vehicle Weight	Front kg (lb)	1383 (3049)	1366 (3013)	1487 (3279)	1473 (3248)
		Rear kg (lb)	1774 (3911)	1790 (3947)	1805 (3981)	1819 (4012)
		Total kg (lb)	3157 (6960)	3157 (6960)	3293 (7260)	3293 (7260)
	Fuel Tank Capacity	L (US gal, Imp. gal)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity (behind Front/Rear No. 1/Rear No. 2 Seats)	m^3 (cu. ft.)	3.42/2.25/0.80 (120.8/79.4/28.4)	3.42/2.25/0.80 (120.8/79.4/28.4)	3.42/2.25/0.80 (120.8/79.4/28.4)	3.42/2.25/0.80 (120.8/79.4/28.4)
Performance	Max. Speed	km/h (mph)	180 (111)	180 (111)	180 (111)	180 (111)
	Max. Cruising Speed	km/h (mph)	180 (111)	180 (111)	180 (111)	180 (111)
	Max. Permissible Speed	1st Gear km/h (mph)	61 (37)	61 (37)	61 (37)*4, 23 (14)*5	61 (37)*4, 23 (14)*5
		2nd Gear km/h (mph)	105 (65)	105 (65)	105 (65)*4, 40 (24)*5	105 (65)*4, 40 (24)*5
		3rd Gear km/h (mph)	154 (95)	154 (95)	154 (95)*4, 58 (36)*5	154 (95)*4, 58 (36)*5
		4th Gear km/h (mph)	180 (111)	180 (111)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
		5th Gear km/h (mph)	180 (111)	180 (111)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
		6th Gear km/h (mph)	180 (111)	180 (111)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
	Turning Diameter (Outside Front)	Wall to Wall m (ft.)	—	—	—	—
		Curb to Curb m (ft.)	—	—	—	—
Engine	Engine Type		1UR-FE	1UR-FE	1UR-FE	1UR-FE
	No. of Cyls. & Arrangement		8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism		32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
	Bore × Stroke	mm (in.)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)
	Displacement	cm^3 (cu. in.)	4608 (281.2)	4608 (281.2)	4608 (281.2)	4608 (281.2)
	Compression Ratio		10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	Fuel System		SFI	SFI	SFI	SFI
	Octane Rating		87 or higher	87 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)	kW @ rpm (HP @ rpm)	231 @ 5600 (310 @ 5600)	231 @ 5600 (310 @ 5600)	231 @ 5600 (310 @ 5600)	231 @ 5600 (310 @ 5600)
	Max. Torque (SAE-NET)	N·m @ rpm (ft.·lbf @ rpm)	443 @ 3400 (327 @ 3400)	443 @ 3400 (327 @ 3400)	443 @ 3400 (327 @ 3400)	443 @ 3400 (327 @ 3400)
Engine Electrical	Battery Capacity (5HR)	Voltage & Amp. hr.	12 - 64	12 - 64	12 - 64	12 - 64
	Generator Output	Watts	1560, 1800*3, 2160*2	1800, 2160*2	1560, 1800*3, 2160*2	1800, 2160*2
	Starter Output	kW	1.6/2.0*7	1.6/2.0*7	1.6/2.0*7	1.6/2.0*7
Chassis	Clutch Type		—	—	—	—
	Transmission Type		A760E	A760E	A760F	A760F
	Transmission Gear Ratio	1st	3.520	3.520	3.520	3.520
		2nd	2.042	2.042	2.042	2.042
		3rd	1.400	1.400	1.400	1.400
		4th	1.000	1.000	1.000	1.000
		5th	0.716	0.716	0.716	0.716
		6th	0.586	0.586	0.586	0.586
		Reverse	3.224	3.224	3.224	3.224
	Differential Gear Ratio (Front/Rear)		—/3.909	—/3.909	3.909/3.909	3.909/3.909
	Differential Gear Size (Front/Rear)	mm (in.)	—/252 (9.9)	—/252 (9.9)	220 (8.7)/252 (9.9)	220 (8.7)/252 (9.9)
	Transfer Gear Ratio 2WD/H4/L4		—	—	1.000/1.000/2.618	1.000/1.000/2.618
	Brake Type	Front	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type		Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size	in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	Proportioning Valve Type		—	—	—	—
	Suspension Type	Front	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
	Stabilizer Bar	Front	Standard	Standard	Standard	Standard
		Rear	Standard	Standard	Standard	Standard
	Steering Gear Type		Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)		18.0	18.0	18.0	18.0
	Power Steering Type		Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Models without roof rack
*2: Towing package
*3: Leather package or models with Rear Seat Entertainment (RSE) system
*4: Transfer in 2WD or H4
*5: Transfer in L4
*6: Models with sliding roof
*7: Cold area specification

U.S.A. and Mexico			U.S.A. and Canada		
Wagon					
SR5	Limited	Platinum	SR5	Limited	Platinum
USK60L-GKTSKA	USK60L-GKTLKA	USK60L-GKTZKA	USK65L-GKTSKA	USK65L-GKTLKA	USK65L-GKTZKA
5210 (205.1)	5210 (205.1)	5210 (205.1)	5210 (205.1)	5210 (205.1)	5210 (205.1)
2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)	2030 (79.9)
1955 (77.0), 1895 (74.6)*1	1955 (77.0)	1955 (77.0)	1955 (77.0), 1895 (74.6)*1	1955 (77.0)	1955 (77.0)
3100 (122.0)	3100 (122.0)	3100 (122.0)	3100 (122.0)	3100 (122.0)	3100 (122.0)
1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)	1725 (67.9)
10 1755 (69.1)	1755 (69.1)	1755 (69.1)	1755 (69.1)	1755 (69.1)	1755 (69.1)
1009 (39.7), 973 (38.3)*6	1009 (39.7), 973 (38.3)*6	973 (38.3)	1009 (39.7), 973 (38.3)*6	1009 (39.7), 973 (38.3)*6	973 (38.3)
1000 (39.4), 988 (38.9)*6	1000 (39.4), 988 (38.9)*6	988 (38.9)	1000 (39.4), 988 (38.9)*6	1000 (39.4), 988 (38.9)*6	988 (38.9)
978 (38.5), 914 (36.0)*6	978 (38.5), 914 (36.0)*6	914 (36.0)	978 (38.5), 914 (36.0)*6	978 (38.5), 914 (36.0)*6	914 (36.0)
965 (38.0)	965 (38.0)	965 (38.0)	965 (38.0)	965 (38.0)	965 (38.0)
15 899 (35.4)	899 (35.4)	899 (35.4)	899 (35.4)	899 (35.4)	899 (35.4)
876 (34.5)	876 (34.5)	876 (34.5)	876 (34.5)	876 (34.5)	876 (34.5)
1686 (66.4)	1686 (66.4)	1686 (66.4)	1686 (66.4)	1686 (66.4)	1686 (66.4)
1678 (66.1)	1678 (66.1)	1678 (66.1)	1678 (66.1)	1678 (66.1)	1678 (66.1)
1676 (66.0)	1676 (66.0)	1676 (66.0)	1676 (66.0)	1676 (66.0)	1676 (66.0)
20 —	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)	890 (35.0)
1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)	1220 (48.0)
25 251 (9.9)	251 (9.9)	244 (9.6)	254 (10.0)	254 (10.0)	244 (9.6)
26.9	26.9	27.0	27.0	27.0	27.2
20.0	20.0	20.0	21.0	21.0	21.0
1281 (2825)	1276 (2815)	1281 (2825)	1378 (3040)	1376 (3035)	1378 (3040)
1317 (2905)	1322 (2915)	1326 (2925)	1335 (2945)	1338 (2950)	1342 (2960)
30 2599 (5730)	2599 (5730)	2608 (5750)	2714 (5985)	2714 (5985)	2721 (6000)
1385 (3055)	1372 (3025)	1346 (2969)	1493 (3292)	1479 (3262)	1456 (3210)
1825 (4025)	1839 (4055)	1864 (4111)	1788 (3943)	1802 (3973)	1825 (4025)
3211 (7080)	3211 (7080)	3211 (7080)	3281 (7235)	3281 (7235)	3281 (7235)
100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
35 3.42/2.25/0.80 (120.8/79.4/28.4)	3.42/2.25/0.80 (120.8/79.4/28.4)	3.42/2.25/0.80 (120.8/79.4/28.4)	3.42/2.25/0.80 (120.8/79.4/28.4)	3.42/2.25/0.80 (120.8/79.4/28.4)	3.42/2.25/0.80 (120.8/79.4/28.4)
180 (111)	180 (111)	180 (111)	180 (111)	180 (111)	180 (111)
180 (111)	180 (111)	180 (111)	180 (111)	180 (111)	180 (111)
65 (40), 59 (36)*2	65 (40), 59 (36)*2	65 (40), 59 (36)*2	62 (38)*4, 59 (36)*2, 4 23 (14)*5, 22 (13)*2, 5	62 (38)*4, 59 (36)*2, 4 23 (14)*5, 22 (13)*2, 5	62 (38)*4, 59 (36)*2, 4 23 (14)*5, 22 (13)*2, 5
112 (69), 101 (62)*2	112 (69), 101 (62)*2	112 (69), 101 (62)*2	106 (65)*4, 101 (62)*2, 4 40 (24)*5, 38 (23)*2, 5	106 (65)*4, 101 (62)*2, 4 40 (24)*5, 38 (23)*2, 5	106 (65)*4, 101 (62)*2, 4 40 (24)*5, 38 (23)*2, 5
40 154 (95), 147 (91)*2	154 (95), 147 (91)*2	154 (95), 147 (91)*2	154 (95)*4, 147 (91)*2, 4 58 (36)*5, 56 (34)*2, 5	154 (95)*4, 147 (91)*2, 4 58 (36)*5, 56 (34)*2, 5	154 (95)*4, 147 (91)*2, 4 58 (36)*5, 56 (34)*2, 5
180 (111)	180 (111)	180 (111)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
180 (111)	180 (111)	180 (111)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
180 (111)	180 (111)	180 (111)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
—	—	—	—	—	—
45 11.9 (39.0)	11.9 (39.0)	11.9 (39.0)	11.9 (39.0)	11.9 (39.0)	11.9 (39.0)
3UR-FE	3UR-FE	3UR-FE	3UR-FE	3UR-FE	3UR-FE
8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
50 5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)	5663 (345.6)
10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
SFI	SFI	SFI	SFI	SFI	SFI
87 or higher	87 or higher	87 or higher	87 or higher	87 or higher	87 or higher
284 @ 5600 (381 @ 5600)	284 @ 5600 (381 @ 5600)	284 @ 5600 (381 @ 5600)	284 @ 5600 (381 @ 5600)	284 @ 5600 (381 @ 5600)	284 @ 5600 (381 @ 5600)
55 544 @ 3600 (401 @ 3600)	544 @ 3600 (401 @ 3600)	544 @ 3600 (401 @ 3600)	544 @ 3600 (401 @ 3600)	544 @ 3600 (401 @ 3600)	544 @ 3600 (401 @ 3600)
12 - 64	12 - 64	12 - 64	12 - 64	12 - 64	12 - 64
1560, 1800*3, 2160*2	1800, 2160*2	1800, 2160*2	1560, 1800*3, 2160*2	1800, 2160*2	1800, 2160*2
2.0	2.0	2.0	2.0	2.0	2.0
—	—	—	—	—	—
60 AB60E	AB60E	AB60E	AB60F	AB60F	AB60F
3.333	3.333	3.333	3.333	3.333	3.333
1.960	1.960	1.960	1.960	1.960	1.960
1.353	1.353	1.353	1.353	1.353	1.353
1.000	1.000	1.000	1.000	1.000	1.000
65 0.728	0.728	0.728	0.728	0.728	0.728
0.588	0.588	0.588	0.588	0.588	0.588
3.061	3.061	3.061	3.061	3.061	3.061
—/3.909, 4.300*2	—/3.909, 4.300*2	—/3.909, 4.300*2	3.909, 4.300*2/3.909, 4.300*2	3.909, 4.300*2/3.909, 4.300*2	3.909, 4.300*2/3.909, 4.300*2
—/252 (9.9)	—/252 (9.9)	—/252 (9.9)	220 (8.7)/252 (9.9)	220 (8.7)/252 (9.9)	220 (8.7)/252 (9.9)
70 —	—	—	1.000/1.000/2.618	1.000/1.000/2.618	1.000/1.000/2.618
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
75 —	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard
80 Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
18.0	18.0	18.0	18.0	18.0	18.0
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item / Area				U.S.A.		
Body Type				Wagon		
Vehicle Grade				SR5	Limited	Platinum
Model Code				USK65L-GKTSGA	USK65L-GKTLGA	USK65L-GKTZGA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5210 (205.1)	5210 (205.1)	5210 (205.1)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1955 (77.0), 1895 (74.6)*1	1955 (77.0)	1955 (77.0)
	Wheel Base		mm (in.)	3100 (122.0)	3100 (122.0)	3100 (122.0)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1755 (69.1)	1755 (69.1)	1755 (69.1)
	Effective Head Room	Front	mm (in.)	1009 (39.7), 973 (38.3)*6	1009 (39.7), 973 (38.3)*6	973 (38.3)
		Rear No. 1	mm (in.)	1000 (39.4), 988 (38.9)*6	1000 (39.4), 988 (38.9)*6	988 (38.9)
		Rear No. 2	mm (in.)	978 (38.5), 914 (36.0)*6	978 (38.5), 914 (36.0)*6	914 (36.0)
	Effective Leg Room	Front	mm (in.)	965 (38.0)	965 (38.0)	965 (38.0)
		Rear No. 1	mm (in.)	899 (35.4)	899 (35.4)	899 (35.4)
		Rear No. 2	mm (in.)	876 (34.5)	876 (34.5)	876 (34.5)
	Shoulder Room	Front	mm (in.)	1686 (66.4)	1686 (66.4)	1686 (66.4)
		Rear No. 1	mm (in.)	1678 (66.1)	1678 (66.1)	1678 (66.1)
		Rear No. 2	mm (in.)	1676 (66.0)	1676 (66.0)	1676 (66.0)
	Cargo Space	Length	mm (in.)	—	—	—
		Width	mm (in.)	—	—	—
		Height	mm (in.)	—	—	—
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance		mm (in.)	254 (10.0)	254 (10.0)	244 (9.6)
	Angle of Approach		degrees	27.0	27.0	27.0
	Angle of Departure		degrees	21.0	21.0	21.0
	Curb Weight	Front	kg (lb)	1378 (3040)	1376 (3035)	1378 (3040)
		Rear	kg (lb)	1335 (2945)	1338 (2950)	1342 (2960)
		Total	kg (lb)	2714 (5985)	2714 (5985)	2721 (6000)
	Gross Vehicle Weight	Front	kg (lb)	1493 (3292)	1479 (3262)	1456 (3210)
		Rear	kg (lb)	1788 (3943)	1802 (3973)	1825 (4025)
		Total	kg (lb)	3281 (7235)	3281 (7235)	3281 (7235)
	Fuel Tank Capacity		L (US gal, Imp. gal)	100 (26.4, 22.0)	100 (26.4, 22.0)	100 (26.4, 22.0)
	Luggage Compartment Capacity (behind Front/Rear No. 1/Rear No. 2 Seats)		m^3 (cu.ft.)	3.42/2.25/0.80 (120.8/79.4/28.4)	3.42/2.25/0.80 (120.8/79.4/28.4)	3.42/2.25/0.80 (120.8/79.4/28.4)
Performance	Max. Speed		km/h (mph)	180 (111)	180 (111)	180 (111)
	Max. Cruising Speed		km/h (mph)	180 (111)	180 (111)	180 (111)
	Max. Permissible Speed	1st Gear	km/h (mph)	62 (38)*4, 59 (36)*2, 4 23 (14)*5, 22 (13)*2, 5	62 (38)*4, 59 (36)*2, 4 23 (14)*5, 22 (13)*2, 5	62 (38)*4, 59 (36)*2, 4 23 (14)*5, 22 (13)*2, 5
		2nd Gear	km/h (mph)	106 (65)*4, 101 (62)*2, 4 40 (24)*5, 38 (23)*2, 5	106 (65)*4, 101 (62)*2, 4 40 (24)*5, 38 (23)*2, 5	106 (65)*4, 101 (62)*2, 4 40 (24)*5, 38 (23)*2, 5
		3rd Gear	km/h (mph)	154 (95)*4, 147 (91)*2, 4 58 (36)*5, 56 (34)*2, 5	154 (95)*4, 147 (91)*2, 4 58 (36)*5, 56 (34)*2, 5	154 (95)*4, 147 (91)*2, 4 58 (36)*5, 56 (34)*2, 5
		4th Gear	km/h (mph)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
		5th Gear	km/h (mph)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
		6th Gear	km/h (mph)	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5	180 (111)*4, 68 (42)*5
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	—	—	—
		Curb to Curb	m (ft.)	11.9 (39.0)	11.9 (39.0)	11.9 (39.0)
Engine	Engine Type			3UR-FBE	3UR-FBE	3UR-FBE
	No. of Cyls. & Arrangement			8-cylinder, V Type	8-cylinder, V Type	8-cylinder, V Type
	Valve Mechanism			32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
	Bore × Stroke		mm (in.)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	Displacement		cm^3 (cu. in.)	5663 (345.6)	5663 (345.6)	5663 (345.6)
	Compression Ratio			10.2 : 1	10.2 : 1	10.2 : 1
	Fuel System			SFI	SFI	SFI
	Octane Rating			87 or higher	87 or higher	87 or higher
	Max. Output (SAE-NET)		kW @ rpm (HP @ rpm)	284 @ 5600 (381 @ 5600)	284 @ 5600 (381 @ 5600)	284 @ 5600 (381 @ 5600)
	Max. Torque (SAE-NET)		N·m @ rpm (ft-lbf @ rpm)	544 @ 3600 (401 @ 3600)	544 @ 3600 (401 @ 3600)	544 @ 3600 (401 @ 3600)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 64	12 - 64	12 - 64
	Generator Output		Watts	1560, 1800*3, 2160*2	1800, 2160*2	1800, 2160*2
	Starter Output		kW	2.0	2.0	2.0
Chassis	Clutch Type			—	—	—
	Transmission Type			AB60F	AB60F	AB60F
	Transmission Gear Ratio	1st		3.333	3.333	3.333
		2nd		1.960	1.960	1.960
		3rd		1.353	1.353	1.353
		4th		1.000	1.000	1.000
		5th		0.728	0.728	0.728
		6th		0.588	0.588	0.588
		Reverse		3.061	3.061	3.061
	Differential Gear Ratio (Front/Rear)			3.909, 4.300*2/3.909, 4.300*2	3.909, 4.300*2/3.909, 4.300*2	3.909, 4.300*2/3.909, 4.300*2
	Differential Gear Size (Front/Rear)		mm (in.)	220 (8.7)/252 (9.9)	220 (8.7)/252 (9.9)	220 (8.7)/252 (9.9)
	Transfer Gear Ratio 2WD/H4/L4			1.000/1.000/2.618	1.000/1.000/2.618	1.000/1.000/2.618
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	Proportioning Valve Type			—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Double-wishbone	Double-wishbone	Double-wishbone
	Stabilizer Bar	Front		Standard	Standard	Standard
		Rear		Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18.0	18.0	18.0
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Models without roof rack
*2: Towing package
*3: Leather package or models with Rear Seat Entertainment (RSE) system
*4: Transfer in 2WD or H4
*5: Transfer in L4
*6: Models with sliding roof