MAJOR TECHNICAL SPECIFICATIONS

Item \ Area				G.C.C. Countries		
Body Type				Wagon		
Vehicle Grade				SR5	Limited	Platinum
Model Code				USK60L-GKTSKV	USK60L-GKTLKV	USK60L-GKTZKV
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5210 (205.1)	5210 (205.1)	5210 (205.1)
		Width	mm (in.)	2030 (79.9)	2030 (79.9)	2030 (79.9)
		Height	mm (in.)	1955 (77.0), 1895 (74.6)*	1955 (77.0)	1955 (77.0)
	Wheel Base		mm (in.)	3100 (122.0)	3100 (122.0)	3100 (122.0)
	Tread	Front	mm (in.)	1725 (67.9)	1725 (67.9)	1725 (67.9)
		Rear	mm (in.)	1755 (69.1)	1755 (69.1)	1755 (69.1)
	Room	Length	mm (in.)	—	—	—
		Width	mm (in.)	—	—	—
		Height	mm (in.)	—	—	—
	Cargo Space	Length	mm (in.)	—	—	—
		Width	mm (in.)	—	—	—
		Height	mm (in.)	—	—	—
	Overhang	Front	mm (in.)	890 (35.0)	890 (35.0)	890 (35.0)
		Rear	mm (in.)	1220 (48.0)	1220 (48.0)	1220 (48.0)
	Min. Running Ground Clearance		mm (in.)	250 (9.8)	250 (9.8)	245 (9.6)
	Angle of Approach		degrees	27.0	27.0	27.0
	Angle of Departure		degrees	20.0	20.0	20.0
	Curb Weight	Front	kg (lb)	1255 - 1290 (2767 - 2844)	1270 - 1305 (2800 - 2877)	1295 - 1300 (2855 - 2866)
		Rear	kg (lb)	1270 - 1320 (2800 - 2910)	1300 - 1365 (2866 - 3009)	1350 - 1360 (2976 - 2998)
		Total	kg (lb)	2525 - 2610 (5567 - 5754)	2570 - 2670 (5666 - 5886)	2645 - 2660 (5831 - 5864)
	Gross Vehicle Weight	Front	kg (lb)	1370 (3020)	1395 (3075)	1360 (2998)
		Rear	kg (lb)	1950 (4299)	1925 (4244)	1960 (4321)
		Total	kg (lb)	3320 (7319)	3320 (7319)	3320 (7319)
	Fuel Tank Capacity		ℓ (Imp.gal.)	100 (22.0)	100 (22.0)	100 (22.0)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—
Performance	Max. Speed		km/h (mph)	180 (112)	180 (112)	180 (112)
	Max. Permissible Speed	1st Gear	km/h (mph)	65 (40)	65 (40)	65 (40)
		2nd Gear	km/h (mph)	112 (70)	112 (70)	112 (70)
		3rd Gear	km/h (mph)	154 (96)	154 (96)	154 (96)
		4th Gear	km/h (mph)	180 (112)	180 (112)	180 (112)
		5th Gear	km/h (mph)	180 (112)	180 (112)	180 (112)
		6th Gear	km/h (mph)	180 (112)	180 (112)	180 (112)
	Min. Turning Radius	Tire	m (ft.)	—	—	—
		Body	m (ft.)	—	—	—
Engine	Engine Type			3UR-FE	3UR-FE	3UR-FE
	Valve Mechanism			32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i	32-valve DOHC with Dual VVT-i
	Bore × Stroke		mm (in.)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)	94.0 × 102.0 (3.70 × 4.02)
	Displacement		cm^3 (cu.in.)	5663 (345.6)	5663 (345.6)	5663 (345.6)
	Compression Ratio			10.2 : 1	10.2 : 1	10.2 : 1
	Fuel System			EFI	EFI	EFI
	Research Octane No.			91 or higher	91 or higher	91 or higher
	Max. Output		kW/rpm	284/5600	284/5600	284/5600
	Max. Torque		N·m/rpm	544/3600	544/3600	544/3600
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 64	12 - 64	12 - 64
	Alternator Output		Watts	1800	2160	2160
	Starter Output		kW	2.0	2.0	2.0
Chassis	Clutch Type			—	—	—
	Transaxle Type			AB60E	AB60E	AB60E
	Gear Ratio	In 1st		3.333	3.333	3.333
		In 2nd		1.960	1.960	1.960
		In 3rd		1.353	1.353	1.353
		In 4th		1.000	1.000	1.000
		In 5th		0.728	0.728	0.728
		In 6th		0.588	0.588	0.588
		In Reverse		3.061	3.061	3.061
	Differential Gear Ratio (Front/Rear)			—/3.909	—/3.909	—/3.909
	Differential Gear Size (Front/Reaf)		mm (in.)	—/252 (9.92)	—/252 (9.92)	—/252 (9.92)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Ventilated Disc	Ventilated Disc	Ventilated Disc
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Tandem, 8 + 9	Tandem, 8 + 9	Tandem, 8 + 9
	Proportioning Valve Type			—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Double-wishbone	Double-wishbone	Double-wishbone
	Stabilizer Bar	Front		Standard	Standard	Standard
		Rear		Standard	Standard	Standard
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			18.0	18.0	18.0
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type

*: Models without roof rack