PARKING BRAKE

SERVICE DATA

Parking brake pedal travel at 294 N (30 kgf, 66.0 lbf):		3 - 5 clicks
Rear brake disc inside diameter	Standard inside diameter: Maximum inside diameter:	190 mm (7.48 in.) 191 mm (7.52 in.)
Parking brake shoe lining thickness	Standard thickness: Minimum thickness:	2.5 mm (0.098 in.) 1.0 mm (0.039 in.)
Parking brake shoe clearance between rear shoe and lever		Less than 0.35 mm (0.0138 in.)

TORQUE SPECIFICATIONS

Part Tightened	N*m	kgf*cm	ft*lbf
Wheel nut	103	1,050	76
Parking brake cable lock nut	5.4	55	48 in.*lbf
Parking brake control pedal set bolt	39	398	29
Parking brake control pedal set nut	39	398	29
Parking brake cable assembly No.1 clump bolt x Body	5.6	57	50 in.*lbf
Parking brake cable assembly No.1 x Body	8	82	71 in.*lbf
Parking brake cable No.2 x Backing plate	8	82	71 in.*lbf
Parking brake cable No.2 x Body	8	82	71 in.*lbf
Parking brake cable No.2 x Cable retainer	5.4	55	48 in.*lbf
Parking brake cable No.3 x Backing plate	8	82	71 in.*lbf
Parking brake cable No.3 x Body	8	82	71 in.*lbf
Parking brake cable No.3 x Cable retainer	5.4	55	48 in.*lbf