HOW TO PROCEED WITH TROUBLESHOOTING

HINT:

- Troubleshooting of the wireless door lock control system is based on the premise that the power door lock system, the power slide door system, the power back door system and the power window system are operating normally. Therefore, before troubleshooting the wireless door lock control system, first make certain that these systems are operating normally.
- Troubleshoot in accordance with the procedures on the following pages.

1	VEHICLE BROUGHT TO WORKSHOP

NEXT

2	CUSTOMER PROBLEM ANALYSIS

(a) Interview the customer to confirm the trouble (See page IN-35).

NEXT

3	DTC CHECK

(a) Check for DTC and note any codes that are output.
(b) Delete the DTC.
(c) Recheck for DTC. Try to prompt the DTC by simulating the original activity that the DTC suggests.
  (1) If the DTC does not reoccur, proceed to A.
  (2) If the DTC reoccur, proceed to B.

B → Go to step 6

A

4	PROBLEM SYMPTOMS TABLE

(a) When problem is not listed on problem symptoms table, proceed to A.
(b) When problem is listed on problem symptoms table, proceed to B.

B → Go to step 6

A

5	PERFORM TROUBLESHOOTING ACCORDING TO MALFUNCTION SYMPTOM

(a) Terminals of ECU (See page DL-56).

(b) Operation check (See page DL-46).

6	ADJUST, REPAIR OR REPLACE

NEXT

7	CONFIRMATION TEST

NEXT

END