■PERFORMANCE AND SPECIFICATION

1. Performance

Models			Regular Cab	Double Cab	CrewMax
Heater	Heater Output	W	5300	5600	5700
	Air Flow Volume	m^3/h	310	330	350
	Power Consumption	W	220	220	220
Air Conditioning	Cooling Capacity	W	5860	5860	6350
	Air Flow Volume	m^3/h	520	520	550
	Power Consumption	W	300	300	300

2. Specification

A/C Type				Manual	Automatic
Ventilation and Heater Core	Heater Core	Type		SFA (Straight Flow Aluminum) -II	
		Size W × H × L mm (in.)		263.9 × 100 × 27 (10.4 × 3.9 × 1.06)	
		Fin Pitch mm (in.)		1.5 (0.06)	
	Blower	Fan Type		Semi Sirocco	
		Fan Size Dia. × H mm (in.)		165 × 70 (6.5 × 2.8)	
Air Conditioning	Condenser	Type		MF (Multi-Flow) -IV	
		Size W × H × L mm (in.)		640 × 511 × 16 (25.2 × 20.1 × 0.6)	
		Fin Pitch mm (in.)		3.15 (0.12)	
	Evaporator	Type		RS (Revolutionary super-slim Structure)	
		Size W × H × L mm (in.)		293.1 × 215 × 50 (11.5 × 8.5 × 2.0)	
		Fin Pitch mm (in.)		3.0 (0.12)	
	A/C Compressor	Type	1GR-FE	10S17C	-
			2UZ-FE/3UR-FE	10S20C	10S20C
		Pulley		Steel with Magnetic Clutch	
	Refrigerant	Type		HFC 134a	
		Charge Volume		570 to 630 gram	